






REV.	DESCRIPTION	DATE
A	NEW DRAWING	2/5/2007



TOLERANCE:
X.X ±0.2mm
X.XX ±0.1mm
X.XXX ±0.05mm



SPECIFICATIONS:
RATING: 16V DC @ 2A
CONTACT RESISTANCE: 50m OHMS MAX
INSULATION RESISTANCE: 100M OHMS MIN: 500V DC
VOLTAGE WITHSTAND: 500V AC R.M.S. FOR 1 MINUTE
LIFE: 5,000 CYCLES

	MATERIAL	PLATING
TERMINAL 1	Brass	Silver
TERMINAL 2	Copper Alloy	Silver
TERMINAL 3	Brass	Silver
SHIELD 4	Cold Rolled Steel	Nickel
BODY	PA6T	

MODEL NO.	PJ-043-SMT
SCHEMATIC	

CENTER PIN DIAMETER 1.0mm Dia.



CUI INC

20050 SW 112th Ave.
Tualatin, OR 97062
Phone: 503-612-2300
800-275-4899
Fax: 503-612-2383
Website: www.cui.com

TITLE: 1.0mm SURFACE MOUNT POWER JACK	REV: A
PART NO. PJ-043-SMT	UNITS: MM [INCHES]
DRAWN BY: ZRJ	APPROVED BY:
	SCALE: 4:1

PC FILE NAME:
PJ-043-SMT

COPYRIGHT 2007 BY CUI INC.