

Oscilloscope Accessories

Model PR-32A

Demodulator Probe

All purpose demodulator probe, usable with most oscilloscopes. Features light weight design and 48" (1.2m) coaxial cable.

Features

| | model PR-32A |
|-------------------|------------------|
| Bandwidth | 100kHz-650MHz |
| Accuracy | $\pm 3\text{dB}$ |
| Voltage | 200V |
| HF Voltage | 50Veff |
| Actuating Voltage | 250mV |
| Input Capacitance | 5pF |
| Cable Length | 48" (1.2m) |
| Body Color | Black |



PR-32A

Model CC-25

BNC / N Type Adapter Kit

The kit contains the most popular In-Series and Between Series BNC and N-type adapters. Solve your hookup problems easily. Bodies are brass, nickel plated with gold plated center contacts.

- Nine BNC and N Type adapters
- 50Ω impedance
- 500Vrms Rating



CC-25

Adapter Legend

| | model CC-25 |
|-----------------------------------|-------------------------------------|
| a. BNC female to female | e. N female to female |
| b. BNC female to N female | f. BNC male to male |
| c. N "T" female to male to female | g. BNC "T" female to male to female |
| | i. BNC female to N male |



AD-110

Model AD-110

BNC Adapter

Fully Insulated BNC male to 4mm sheathed Jack. Use DMM test leads on BNC female connectors.

- IEC61010-1 500V CAT I
- 50Ω impedance
- Fully Insulated



TE-26

Model TE-26

BNC 50Ω Feedthru Termination

Connect 50Ω impedance accessories to 1MΩ impedance instruments.

- 50Ω impedance
- 2W power



CC-41A



CC-110

Models CC-41A and CC-150

BNC Cable Assemblies

Standard BNC cable assemblies in three convenient lengths. Black, molded strain release boots provides for long-life. RG58C/U cable and 50Ω impedance. CC-110 is a special fully insulated BNC male to male cable assembly. Meets IEC61010 safety standards. Uses highly flexible RG58 Type cable in two meter length. Color: Black.

Features

| | models | | | |
|--------------|------------|--------------------|--------------------|-------------|
| | CC-41A | CC-150 | CC-155 | CC-110 |
| Impedance | 50Ω | 50Ω | 50Ω | 50Ω |
| Cable | RG58 C/U | RG58 Type | RG58 Type | RG58 Type |
| Connectors | BNC male | Insulated BNC male | Insulated BNC male | BNC male |
| Voltage | 500Vrms | 150V CAT II | 150V CAT II | 150V CAT II |
| VSWR | ≤ 1.2 | ≤ 1.2 | ≤ 1.2 | ≤ 1.2 |
| Cable Length | 40" (1.0m) | 48" (1.2m) | 60" (1.5m) | 80" (2.0m) |



CC-21



CC-130

Models CC-21 & CC-130

Special BNC Cable Assemblies

Standard BNC to Alligator clips or Sheathed Stacking Plugs. Model CC-21, Black, molded strain release boots provides for long-life. RG58C/U cable with 50Ω impedance. Model CC-130 with fully insulated BNC male to Sheathed Stacking 4mm plugs. Meets IEC61010 safety standards. Includes highly flexible RG58 Type cable in 2.0 meter length. Color: Black.

Features

| | model | |
|--------------|--------------------------|--------------------------------|
| | CC-21 | CC-130 |
| Impedance | 50Ω | 50Ω |
| Cable | RG58 C/U | RG58 Type |
| Connectors | BNC m to Alligator Clips | Insulated BNC male to 4mmPlugs |
| Voltage | 500Vrms | 150V CAT II |
| VSWR | ≤ 1.2 | ≤ 1.2 |
| Cable Length | 40" (1.0m) | 80" (2.0m) |