

IP68 ETHERNET CIRCULAR SCPE, SCRES SERIES

SPECIFICATIONS

Mates with: SCRES

For complete specifications see www.samtec.com?SCPE



Insulator Material:

Polycarbonate

Contact Material:

Phosphor Bronze

Shield Material:

Phosphor Bronze

Wire:

24 AWG

Overmold:

PA66 GF13 FR

Operating Temp Range:

-40°C to +70°C

RoHS Compliant:


Yes

ALSO AVAILABLE

Other wire lengths.
Dust Cap: DCA-17-02
Contact Samtec.

APPLICATION	SERIES
USB	SCPU
POWER	SCP1
HIGH DENSITY	SCP2
TIGER EYE	SCP3

Note: Some lengths, styles and options are non-standard, non-returnable.



FIELD TERMINATION KIT

- Ethernet Field Termination Kit available for long cable run and small-opening applications, so housings can be customer-installed after the runs are complete.
 - SCPFE-17-G-01 Series (For cable outside diameter range of 5.00-5.75mm)
 - SCPFE-17-G-02 Series (For cable outside diameter range of 5.75-6.50mm)
- Call Samtec.



SPECIFICATIONS

Mates with: SCPE

For complete specifications and recommended panel hole layout see www.samtec.com?SCRES



Insulator Material:

PBT

Contact Material:

Phosphor Bronze

Shield Material:

Phosphor Bronze

O-Ring:

Silicone

Mold:

PA66 IM FR BK

Operating Temp Range:

-20°C to +75°C


RoHS Compliant:

Yes

ALSO AVAILABLE

Dust Cap: DCA-17-01
Panel Plug: SCPPA-17-01
Contact Samtec.

Note: Some lengths, styles and options are non-standard, non-returnable.



APPLICATION SPECIFIC OPTION

Sealed circular Ethernet panel interface.
(Use standard Ethernet cable from panel to board.)
Call Samtec.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM