

N-Channel 150-V (D-S) MOSFET

PRODUCT SUMMARY


V_{DS} (V)	$R_{DS(on)}$ (Ω)	I_D (A)	Q_g (Typ.)
150	0.135 at $V_{GS} = 10$ V	3.4	20 nC
	0.142 at $V_{GS} = 6$ V	3.3	

FEATURES

- Halogen-free According to IEC 61249-2-21 Available
- PWM-Optimized TrenchFET® Power MOSFET
- 100 % R_g Tested
- Avalanche Tested




PowerPAK® 1212-8



Ordering Information: Si7818DN-T1-E3 (Lead (Pb)-free)
Si7818DN-T1-GE3 (Lead (Pb)-free and Halogen-free)

APPLICATIONS

- Primary Side Switching Circuits



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS $T_A = 25$ °C, unless otherwise noted

Parameter	Symbol	10 s	Steady State	Unit
Drain-Source Voltage	V_{DS}	150	± 20	V
Gate-Source Voltage	V_{GS}			
Continuous Drain Current ($T_J = 150$ °C) ^a	I_D	3.4	2.2	A
		2.7	1.7	
Pulsed Drain Current	I_{DM}	10	1.3	A
Continuous Source Current (Diode Conduction) ^a	I_S			
Single Avalanche Current	I_{AS}	9	4	mJ
Single Avalanche Energy	E_{AS}			
Maximum Power Dissipation ^a	P_D	3.8	1.5	W
		2.0	0.8	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 150	260	°C
Soldering Recommendations (Peak Temperature) ^{b, c}				

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient ^a	R_{thJA}	26	33	°C/W
		65	81	
Maximum Junction-to-Case (Drain)	R_{thJC}	1.9	2.4	

Notes:

- Surface Mounted on 1" x 1" FR4 board.
- See Reliability Manual for profile. The PowerPAK 1212-8 is a leadless package. The end of the lead terminal is exposed copper (not plated) as a result of the singulation process in manufacturing. A solder fillet at the exposed copper tip cannot be guaranteed and is not required to ensure adequate bottom side solderinterconnection.
- Rework Conditions: manual soldering with a soldering iron is not recommended for leadless components.

MOSFET SPECIFICATIONS $T_J = 25^\circ\text{C}$, unless otherwise noted



Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit	
Static							
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}$, $I_D = 250 \mu\text{A}$	2		4	V	
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0 \text{ V}$, $V_{GS} = \pm 20 \text{ V}$			± 100	nA	
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 150 \text{ V}$, $V_{GS} = 0 \text{ V}$			1	μA	
		$V_{DS} = 150 \text{ V}$, $V_{GS} = 0 \text{ V}$, $T_J = 55^\circ\text{C}$			5		
		$V_{DS} \geq 5 \text{ V}$, $V_{GS} = 10 \text{ V}$	10			A	
On-State Drain Current ^a	$I_{D(\text{on})}$	$V_{GS} = 10 \text{ V}$, $I_D = 3.4 \text{ A}$		0.112	0.135	Ω	
		$V_{GS} = 6 \text{ V}$, $I_D = 3.3 \text{ A}$		0.117	0.142		
		$V_{DS} = 15 \text{ V}$, $I_D = 3.4 \text{ A}$		17		S	
Diode Forward Voltage ^a	V_{SD}	$I_S = 3.2 \text{ A}$, $V_{GS} = 0 \text{ V}$		0.78	1.2	V	
Dynamic^b							
Total Gate Charge	Q_g	$V_{DS} = 75 \text{ V}$, $V_{GS} = 10 \text{ V}$, $I_D = 3.4 \text{ A}$		20	30	nC	
Gate-Source Charge	Q_{gs}			2.7			
Gate-Drain Charge	Q_{gd}			4.7			
Gate Resistance	R_g	$f = 1 \text{ MHz}$		0.8	1.7	2.6	Ω
Turn-On Delay Time	$t_{d(\text{on})}$	$V_{DD} = 100 \text{ V}$, $R_L = 100 \Omega$ $I_D \geq 1 \text{ A}$, $V_{GEN} = 10 \text{ V}$, $R_g = 6 \Omega$		10	15	ns	
Rise Time	t_r			10	15		
Turn-Off Delay Time	$t_{d(\text{off})}$			25	40		
Fall Time	t_f			15	25		
Source-Drain Reverse Recovery Time	t_{rr}			50	75		
Reverse Recovery Charge	Q_{rr}	$I_F = 3.2 \text{ A}$, $dI/dt = 100 \text{ A}/\mu\text{s}$		100	150	nC	







Notes:





a. Pulse test; pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2\%$.


b. Guaranteed by design, not subject to production testing.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TYPICAL CHARACTERISTICS 25°C , unless otherwise noted


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

On-Resistance vs. Drain Current

Capacitance

Gate Charge

On-Resistance vs. Junction Temperature

Source-Drain Diode Forward Voltage

On-Resistance vs. Gate-to-Source Voltage

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted


Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?73252.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.