






REV.	DESCRIPTION	DATE
A	NEW DRAWING	11/15/2005
B	added dimension	2/11/2008



TOLERANCE:
X.X ±0.2mm
X.XX ±0.1mm
X.XXX ±0.05mm



MODEL NO.	SJ1-2533-SMT
SCHEMATIC	

SPECIFICATIONS:
 RATING: 16V DC @ 300mA
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 50M OHMS MIN: 500V DC
 VOLTAGE WITHSTAND: 500V AC R.M.S. FOR 1 MINUTE
 LIFE: 5,000 CYCLES

	MATERIAL	PLATING	TITLE: 2.5mm SMT AUDIO JACK-STEREO	REV: B
TERMINAL 1	Copper Alloy	Gold	PART NO. SJ1-2533-SMT	UNITS: MM [INCHES]
TERMINAL 2	Copper Alloy	Gold		
TERMINAL 3	Copper Alloy	Gold		
HOUSING	PA6T		DRAWN BY: ZRJ	APPROVED BY:
			SCALE: 4:1	



CUI INC

20050 SW 112th Ave.
 Tualatin, OR 97062
 Phone: 503-612-2300
 800-275-4899
 Fax: 503-612-2383
 Website: www.cui.com

PC FILE NAME:
 SJ1-2533-SMT

COPYRIGHT 2008 BY CUI INC.