







1. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

2. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.6mm THICK CIRCUIT BOARD.

PT. NO.	PARTS NAME	MATERIAL	Q'TY	NOTE
1	HOUSING	PBT RESIN GLASS REINFORCED (UL94V-0)	1	COLOR : BLACK
2	SLIDER		1	
3	CONTACT	PHOSPHOR BRONZE	n	PLATING : Sn Ni UNDER PLATED (LEAD FREE)

n : NO. OF CONTACTS

mat'l. code				surface 58 ✓ ISO 1302		tolerance ISO 406 ISO 1101		projection 		product family 58KF				CODE JP		
ltr	ecn no	dr	date	tolerances unless otherwise specified								title 1.25mm SPACING FPC/FFC CONNECTOR (Cat. No. SLD__S-1LF)				
A	J05-0435	H.T	7/8/'05	angles		linear ±0.3										
B	J05-0733	H.T	10/28/'05													
C	J06-0503	H.T	11/28/'06													
				dr		 11/28/06						dwg no		sheet 1 of 1		size
				enr		 11/28/06						JSA 96550		A4		
				chr		 11/28/06										
				appd		 11/28/06										
sheet		revision		C						type Product Customer Drawing						