
THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, MITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

© 2005, Projects Unlimited Inc.

**SPECIFICATIONS** 

	REVISIONS		
LTR	DESCRIPTION	DATE	APPROVED
_	RELEASED FROM ENGINEERING	5/17/06	

PARAMETERS	VALUES	UNITS
RATED VOLTAGE (SQUARE WAVE)	3	Vp-p
OPERATING VOLTAGE RANGE	2 ~ 5	Vp-p
RATED CURRENT (MAX)	35	mΑ
COIL RESISTANCE	47±7	ОНМ
MINIMUM SPL @ 10 CM	80	dBA
RESONANT FREQUENCY	2000±200	Hz
OPERATING TEMPERATURE	-40 ~ +85	•c
STORAGE TEMPERATURE	-40 ~ +85	•c
HOUSING MATERIAL	PPS	-
TERMINAL MATERIAL	GOLD PLATED BRASS	_
WEIGHT	2	grams



## NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

TRANSDUCER APPROVALS DATE DRAWN J.D. 5/06 CHECKED DRAWING NO. E.P. SIZE 5/06 SMT-1220-TW-R APPROVED B.R. 5/06 SMT-1220-TW-R.DWG SHEET 1 OF DO NOT SCALE DRAWING SCALE: N.T.S.

Dayton , Ohio

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN
MILLIMETERS, TOLERANCES ARE ±0.5 AND
ANGLES ARE ±3'.