



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SU10KRT3UHV

SmartOnline Expandable Rack / Tower UPS System - On-line, double-conversion protection for mission critical applications

Highlights



- 10,000VA (10kVA) / 8,000W on-line 6U rack / tower UPS (3U Power Module + 3U Battery Pack)
- Enhanced serial communications ports, SNMP/Web card slot and EPO jack
- Maintains 200, 208, 220, 230 or 240V output +/-2% during brownouts to 156 and overvoltages to 276V
- Internal fault tolerant auto bypass mode and detachable hardwired PDU with manual bypass switch enables hot-swap UPS replacement without powering off connected loads
- Expandable runtime with optional BP240V10RT3U battery packs
- \$250,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

Description

Tripp Lite 10,000VA (10kVA) SmartOnline Rack/Tower UPS. The SmartOnline SU10KRT3UHV on-line, double conversion UPS protects server, networking or telecommunications equipment from blackouts, voltage fluctuations and surges in a compact tower/rackmount housing. In rack configuration, power module and battery pack occupy only 3 rack spaces each (6U total). Upright tower placement of entire system supported with included tower stands. Large capacity 10,000VA/8000W power module converts raw input AC to DC, then back to perfect sine wave AC output within 2% of user-selectable 200/208/220/230/240V AC output voltages. Frequency regulation locks output power to 50/60Hz (+/-0.2 Hz), removing harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types. Perfectly regulated, continuous sine wave output with zero transfer time offers guaranteed compatibility with all equipment types. Hardwire input and output connections support a variety of permanent or PDU style power connections. Detachable hardwired PDU with manual bypass switch enables hot-swap UPS replacement without powering off connected loads. Battery support can be extended through the addition of optional external battery packs, sold separately (part# BP240V10RT3U). Includes slot for internal SNMP/Web card, plus DB9 enhanced serial monitoring port for unattended shutdown, remote control and monitoring of UPS system and power data.

Applications

Ideal for protection of critical 200/208/220/230/240V equipment in server rooms, internetworking closets and telecommunications systems in rackmount or tower applications. Common applications include corporate or departmental servers, workstations, hubs, routers, bridges, CAD/CAM workstations, concentrators, IP telephony and traditional PBX switching systems.

Package Includes

- SU10KRT3UHV Rack-Tower UPS System with hardwire distribution module and 1 BP240V10RT3U battery pack
- PowerAlert Software and cabling
- Mounting hardware for 4 post rack enclosures/tower stands
- Instruction manual with warranty information

Features

- True on-line, double conversion UPS provides pure, sine wave AC output at all times
- World-wide compatibility with Euro 50Hz and High Voltage North American 60Hz power
- Maintains continuous operation through blackouts, voltage fluctuations and surges with zero transfer time

Removes harmonic distortion, electrical impulses, frequency variations and other hard to solve power problems
 10,000VA/8,000W power capacity with hardwire input/output connections
 Accepts input voltages between 156 and 276, regulating output within 2% of selectable 200/208/220/230/240V AC output
 Standard included 3U battery pack provides 10 minutes runtime at half load (5,000VA) and 4 minutes at full load (10,000VA)
 Expandable runtime with multiple external battery packs, sold separately (part# BP240V10RT3U)
 Innovative design makes unit adaptable for rackmount, tower, or stacking applications
 Power module and battery pack require only 3 rack spaces each (6U total rack space usage)
 DB9 serial port for network interface; SNMP compatible
 Slot for optional SNMP/Web card (part# SNMPWEBCARD)
 PowerAlert unattended shutdown software and 6 ft. network cable included
 Fault tolerant auto-bypass maintains continuous utility output to connected equipment, even in cases where the UPS is overloaded or suffers an internal failure that requires service
 Detachable hardwired PDU with manual bypass switch enables hot-swap UPS replacement without powering off connected loads
 Diagnostic LEDs and LCD provide complete overview of operating conditions, UPS status and more
 Mounting hardware included
 Includes RJ11 EPO (emergency power off) port and interconnection cable
 2 year manufacturers product warranty
 \$250,000 Ultimate Lifetime [connected equipment insurance](#)

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	208V AC (200/208/220/230/240V)
Frequency compatibility	50/60Hz
OUTPUT	
Output VA	10000
Output watts	8000
Output nominal voltage	208V AC (200/220/230/240V)
Output voltage regulation	Maintains pure sine wave output at all times, regulated within 2% of selected nominal output voltage, less than 5% total harmonic distortion
Output frequency regulation	Regulates line frequency to 50/60Hz +/- 0.05Hz
Outlet quantity / type	Hardwire via detachable distribution module
INPUT	
Maximum input amps	46.7A (200V), 44.9A (208V), 42.4A (220V), 40.6A (230V), 38.9A (240V) max.
Input connection type	Hardwire via detachable distribution module
BATTERY	
Full load runtime	Included batteries — 4 min (10,000VA)
Half load runtime	Included batteries — 10 min (5,000VA)
Expandable battery runtime	Supports extended runtime with optional external battery packs BP240V10RT3U (multi-pack compatible)
DC system voltage	240V DC
Typical battery lifespan	3-6 years, depending on usage
Battery recharge rate	Less than 8 hours to 90% (included battery set only)
VOLTAGE REGULATION	
Voltage regulation description	On-line, double-conversion process allows this UPS to maintain output voltage within +/-2% of selected nominal voltage at all times
Overvoltage correction	Maintains continuous operation without using battery power during overvoltages to 276V AC, reducing output within 2% of selected nominal

Brownout correction	Maintains continuous operation without using battery power during brownout / undervoltage conditions to 156V AC, increasing output within 2% of selected nominal
LEDS ALARMS & SWITCHES	
Front panel LEDs	6 LED DISPLAY: line power, bypass, inverter, charger, output AC and battery operation. SELECTABLE LCD DISPLAY: input/output voltage, Hz, battery voltage and charge level and detailed warnings regarding all major UPS functions.
Alarms	Multi-function audible alarm offers notification of UPS start, backup operation, low battery, overload, UPS fault, inverter fault, DC bus fault, overtemperature, remote shutdown, shutdown imminent and shutdown complete
Switches	Includes main power off/on switch, plus 2 switches to set and execute scrollable LCD functions
SURGE / NOISE SUPPRESSION	
AC surge suppression	1320 joules
AC suppression response time	Instantaneous
EMI / RFI AC noise suppression	Yes
PHYSICAL	
Shipping weight (lbs)	327.56
Shipping weight (kg)	147.4
Unit weight (lbs)	Power Module 54.8 lbs. (59.8 lbs w/SUPDMB710HW); Battery Pack: 158.73 lbs.
Unit weight (kg)	Power Module: 24.66kg (26.91kg w/SUPDMB710HW), Battery Pack: 71.43kg
Unit Dimensions (HWD/in)	Power Module 5.14 x 17.5 x 25 (30.25 in. depth w/SUPDMB710HW), Battery Pack 5.16 x 17.5 x 2
Unit Dimensions (HWD/cm)	Power Module 13.1 x 44.5 x 63.5 (76.8 cm depth w/SUPDMB710HW); Battery Pack 13.1 x 44.5 x 63.5
Material of construction	Steel
Form factors supported	Rack (6U)
Cooling method	Built-in cooling fan
Battery Access	User replaceable, hot swappable external battery pack
ENVIRONMENTAL	
Operating Temperature	+32 to +104 degrees Fahrenheit
Storage Temperature	+5 to +122 degrees Fahrenheit
Relative Humidity	0 to 95%, non-condensing
COMMUNICATIONS	
Network monitoring port	Includes 2 built-in DB9 monitoring ports (1-RS232 / 1-contact closure)
Software and cabling included	Includes PowerAlert UPS monitoring software for all common network and standalone operating systems. Cabling included.
SNMP compatibility	Built-in accessory slot accommodates internal SNMP / Web card and other network accessories
WatchDog compatibility	Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment ideal for unattended kiosk applications
LINE / BATTERY TRANSFER	
Transfer time from line power to battery mode	Zero transfer time: on-line UPS continuously converts incoming AC to DC, then back to AC. When line power is interrupted, UPS maintains continuous output from battery reserves with absolutely no disruption in output AC power.
Low voltage transfer to battery power	Maintains continuous operation during undervoltages as low as 156V AC. Below this point, output is maintained utilizing battery reserves.

High voltage transfer to battery power	Maintains continuous operation during overvoltages to 276V AC. Above this point, output is maintained utilizing battery reserves.
SPECIAL FEATURES	
EPO port	Includes dedicated EPO (emergency power off) interface and cabling
Cold Start	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
Appearance	Attractive black steel rackmount housing
BATTERY PACK ACCESSORY (optional)	
Battery Pack Accessory (optional)	BP240V10RT3U (optional)
CERTIFICATIONS	
Certifications	Tested to UL1778 (USA), Tested to CSA (Canada), FCC Class A (emissions), NOM (Mexico)
WARRANTY	
Product warranty	2 year product warranty
Connected equipment insurance (USA and Canada Only)	\$250,000 connected equipment insurance (USA, Puerto Rico, and Canada only)
Optional coverage	3 year, 5 year, next day and on-site warranty coverage available for select opportunities - contact Tripp Lite

Related Items

Extended Warranties		
WEXT3-SU10KHV	3-Year Extended Warranty - For SU10KRT3UHV only	Qty: [optional]
External Battery Packs		
BP240V10RT3U	External Battery Pack and Cable. 3U, Expandable, Black 3-Point Connector	Qty: [optional]
BP240V557C-1PH	External battery pack for use with select Tripp Lite UPS Systems	Qty: [optional]
BP240V787C-1PH	External battery pack for use with select Tripp Lite UPS Systems	Qty: [optional]
BP240V1407C-1PH	External battery pack for use with select Tripp Lite UPS Systems	Qty: [optional]
BP240V1037C-1PH	External battery pack for use with select Tripp Lite UPS Systems	Qty: [optional]
Power Distribution		
SUPDMB710IEC	Detachable PDU option with IEC output connections for compatible SmartOnline UPS Systems	Qty: [optional]
Rackmount/Wallmount Kits		
2POSTRMKITWM	buy 2	Qty: [optional]
Shutdown Cable Kits		
AS400CABLE KIT	Power Management Tools - UPS Communication Cable Kit for System i / AS400 / iSeries Servers	Qty: [optional]
SNMP Accessories		
ENVIROSENSE	Power Management Tools - Environmental Sensor	Qty: [optional]
SNMPWEBCARD	Power Management Tools - Internal SNMP/Web Card	Qty: [optional]
Start-Up/Warranty Services		
W02-BW0	Regular business hours start-up, excludes on-site warranty.	Qty: [optional]
W02-BW2-1BD	Regular business hours start-up and two year on-site, next business day break/fix warranty service for locations within 350 miles of a covered service area.	Qty: [optional]

W02-BW2-247	Regular business hours start-up and two year on-site, 24-by-7 break/fix warranty service for locations within 250 miles of a covered service area.	Qty: [optional]
W02-BW3-1BD	Regular business hours start-up and three year on-site, next business day break/fix warranty service for locations within 350 miles of service area.	Qty: [optional]
W02-BW3-247	Regular business hours start-up and three year on-site, 24-by-7 break/fix warranty service for locations within 250 miles of service area.	Qty: [optional]
W02-EW0	Evening or weekend hours start-up, excludes on-site warranty.	Qty: [optional]
W02-EW2-1BD	Evening or weekend hours start-up and two year on-site, next business day break/fix warranty service for locations within 350 miles of service area.	Qty: [optional]
W02-EW2-247	Evening or weekend hours start-up and two year on-site, 24-by-7 break/fix warranty service for locations within 250 miles of service area.	Qty: [optional]
W02-EW3-1BD	Evening or weekend hours start-up and three year on-site, next business day break/fix warranty service for locations within 350 miles of service area.	Qty: [optional]
W02-EW3-247	Evening or weekend hours start-up and three year on-site, 24-by-7 break/fix warranty service for locations within 250 miles of service area.	Qty: [optional]
W02-BW1-1BD	Regular business hours start-up and one year on-site, next business day break/fix warranty service for locations within 350 miles of a covered service area.	Qty: [optional]
W02-BW1-247	Regular business hours start-up and one year on-site, 24-by-7 break/fix warranty service for locations within 250 miles of a covered service area.	Qty: [optional]
W02-EW1-1BD	Evening or weekend hours start-up and one year on-site, next business day break/fix warranty service for locations within 350 miles of service area.	Qty: [optional]
W02-EW1-247	Evening or weekend hours start-up and one year on-site, 24-by-7 break/fix warranty service for locations within 250 miles of service area.	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.triplite.com/EN/products/model.cfm?txtModelID=2472.