



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SU750XL

SmartOnline Expandable Tower UPS System - On-line, double-conversion protection for mission-critical applications



Highlights

- 750VA/600W on-line expandable runtime tower UPS system
- HID-compliant USB port, serial port and SNMP/WEB card slot
- Maintains 120V +/-2% output during overvoltages to 138V and brownouts as low as 65V
- NEMA 5-15P (120V 15A) input plug, 6 x NEMA 5-15R outlets, two individually controllable single-outlet load banks
- Fault-tolerant auto-bypass
- \$250,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

Description

The SU750XL on-line, double-conversion UPS protects critical server, networking or telecommunications equipment from blackouts, brownouts, voltage fluctuations and surges. Large-capacity 750VA/600W UPS continuously converts incoming AC to DC, then back to perfect sine wave AC output at 120V AC (+/-2%). Removes harmonic distortion, fast electrical impulses, frequency fluctuations and other hard-to-solve power problems not addressed by other UPS systems. True sine wave output and zero transfer time offer guaranteed compatibility with all equipment types. Includes 6 UPS supported outlets; 2 single-outlet load banks can be independently controlled via a software interface to selectively reboot remote equipment or shed less critical loads to extend battery runtime for the most critical equipment. Extended runtime available with optional BP24V34, BP24V15RT2U, BP24V28-2U, or BP24V70-3U external battery packs. Includes slot for internal SNMP/WEB card, plus DB9 enhanced serial monitoring port for unattended shutdown, remote control and monitoring of UPS system and power data. Includes USB and DB9 serial ports. Built-in DB9 port offers both enhanced RS-232 enabled monitoring data, plus contact closure monitoring ability. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. Includes Tripp Lite's PowerAlert UPS power management software. Compatible with Tripp Lite's Watchdog service monitoring/rebooting software. Upright tower form factor; attractive all-black color scheme.

Applications

Ideal for protection of critical 120V servers, networking equipment and sensitive electronics. Common applications include corporate or departmental servers, workstations, hubs, routers, bridges, CAD/CAM workstations, concentrators, IP telephony and traditional PBX switching systems.

Package Includes

- SU750XL UPS System
- PowerAlert Software CD and cabling
- EPO (Emergency Power Off) cabling
- Owner's manual with warranty information

Features

- True on-line, double-conversion UPS provides constant, pure sine wave AC output
- Maintains continuous operation with zero transfer time through blackouts, brownouts, voltage fluctuations and surges
- Removes harmonic distortion, electrical impulses, frequency variations and other hard-to-solve power problems

Accepts input voltages between 80-138V (65-138V at loads under 70%), regulating output to 120V AC +/-2%
 750VA/600W output capacity with 6 x NEMA5-15R outlets
 Two built-in individually switchable load banks can be controlled via software interface to selectively reboot remote equipment or shed less critical loads to extend battery runtime for the most critical equipment (1 outlet per bank)
 Standard internal battery set provides 11 min. runtime at half load and 4 min. at full load
 Extended runtime available with optional BP24V34, BP24V15RT2U, BP24V28-2U, or BP24V70-3U external battery packs
 HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
 DB9 serial network interface supports RS-232 and contact closure messaging
 Slot for optional SNMP/WEB card (part# SNMPWEBCARD)
 Included PowerAlert UPS power management software and cabling provides monitoring of in-depth site power conditions, full UPS status and fault warnings, output load level and load bank power control
 Compatible with Tripp Lite's WatchDog service monitoring/rebooting software (part# WATCHDOGSW)
 Fault-tolerant auto-bypass maintains continuous utility output to connected equipment, even in cases where the UPS is overloaded or suffers an internal failure that requires service
 Diagnostic LEDs
 Upright tower format; attractive all-black color scheme
 \$250,000 Ultimate Lifetime [connected equipment insurance](#) (USA & Canada only)
 2-year warranty

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120V (110V, 100V) AC
Frequency compatibility	50/60 Hz compatible
OUTPUT	
Output VA	750
Output watts	600
Output nominal voltage	120 VAC
Output voltage regulation	Maintains full-time sine wave output within 2% of 120V, less than 5% total harmonic distortion
Output frequency regulation	Regulates line frequency to 50/60Hz +/- 0.05Hz
Outlet quantity / type	6 x NEMA 5-15R
Customized load management receptacles	2 individually controllable single-outlet load banks support load shedding and remote reboot on demand of locked network devices. Configurable with PowerAlert Software to switch off optional loads, like monitors, to increase available runtime for servers and other critical devices.
Overload protection	15A input breaker
INPUT	
Maximum input amps	6.2A
Input connection type	NEMA 5-15P
Input cord length	10 ft.
Recommended Electrical Service	15A 120V
BATTERY	
Full load runtime	4 min.
Half load runtime	11 min.
DC system voltage	24VDC
Typical battery lifespan	4-6 years typical

Battery recharge rate	4-6 hours to 90%
Replacement Battery Cartridge	RBC24-SUTWR
VOLTAGE REGULATION	
Voltage regulation description	On-line, double-conversion power conditioning maintains output within 2% of 120V at all times
Overvoltage correction	Maintains output of 120V +/-2% during overvoltages to 138VAC
Brownout correction	Maintains output of 120V +/-2% during undervoltages to 80VAC
Severe brownout correction	Maintains output of 120V +/-2% during undervoltages to 65VAC (during load conditions of 70% or less)
LEDS ALARMS & SWITCHES	
Front panel LEDs	14 status LEDs offer LINE POWER, ONLINE, BYPASS, ON BATTERY, OVERLOAD, BATTERY LOW, REPLACE BATTERY and FAULT status information. Also includes 4 LED meters for LOAD LEVEL/BATTERY LEVEL display (Battery level readout requires pressing power on/test switch)
Alarms	Multi-function audible alarm offers notification of UPS start, backup operation, low battery warning, overload, UPS fault and remote shutdown
Switches	Includes combination main power on/test and main power off switch
SURGE / NOISE SUPPRESSION	
AC suppression response time	Instantaneous
Dataline suppression	RJ45 1-line tel/DSL/Ethernet
EMI / RFI AC noise suppression	Yes
PHYSICAL	
Shipping weight (lbs)	34.2
Shipping weight (kg)	15.4
Shipping Dimensions (HWD/in)	14.25 x 10 x 18.5
Shipping Dimensions (HWD/cm)	36.2 x 25.4 x 47
Unit weight (lbs)	28.7
Unit weight (kg)	12.92
Unit Dimensions (HWD/in)	10 x 6.75 x 13.25
Unit Dimensions (HWD/cm)	25.4 x 17.1 x 33.7
Material of construction	Steel
Form factors supported	Tower
Cooling method	Fan
Battery Access	Supports battery access and hot-swap replacement without powering connected equipment off
ENVIRONMENTAL	
Operating Temperature	+32 to +104 degrees Fahrenheit/0 to +40 degrees Celsius
Storage Temperature	+5 to +122 degrees Fahrenheit/-15 to +50 degrees Celsius

Relative Humidity	0 to 95%, non-condensing
Line mode BTU/hr. (Max.)	305 BTU/hr.
COMMUNICATIONS	
Network monitoring port	Includes USB and DB9 serial ports. Built-in DB9 port offers both enhanced RS-232 enabled monitoring data, plus contact closure monitoring ability. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X.
Software and cabling included	PowerAlert Software CD-ROM and complete cabling
SNMP compatibility	Includes slot for optional SNMPWEBCARD accessory (#SNMPWEBCARD)
WatchDog compatibility	Compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of applications/OS or hard power off/on reboot of connected equipment ideal for unattended kiosk applications
LINE / BATTERY TRANSFER	
Transfer time from line power to battery mode	ZERO — on-line UPS continuously converts incoming AC to DC, then back to AC. When commercial power is interrupted, UPS maintains continuous output from battery reserves with absolutely no disruption in output AC power.
Low voltage transfer to battery power	Maintains continuous operation during undervoltages as low as 80V (65V during load conditions of 70% or less). Below the switchover point, output is supported from battery-derived AC power.
High voltage transfer to battery power	Maintains continuous operation without using battery power during overvoltages to 138V. Above this point, output is supported from battery-derived AC power.
SPECIAL FEATURES	
EPO port	Supports EPO (emergency power off) with included cabling
Cold Start	Inverter can be cold started to enable temporary AC output during a power failure
Appearance	Attractive all-black color scheme
BATTERY PACK ACCESSORY (optional)	
Battery Pack Accessory (optional)	BP24V34 (limit 1)
CERTIFICATIONS	
Certifications	Tested to UL1778 (USA), CSA C22.2 No. 107.3 (Canada), Class B (Emissions), RoHS-compliant, FCC Part 68/ Industry Canada (telecommunications)
WARRANTY	
Product warranty	2 years
Connected equipment insurance (USA and Canada Only)	\$250,000 (USA and Canada only)
Optional coverage	3-5 year warranties, plus next day and on-site warranty coverage available for select opportunities. Contact Tripp Lite for additional information.

Related Items

Extended Warranties		
WEXT3-500-1500	3-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 1500VA or less	Qty: [optional]
WEXT5-500-1500	5-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 1500VA or less	Qty: [optional]

External Battery Packs		
BP24V28-2U	BP24V28-2U - External Battery Pack for UPS System	Qty: [optional]
BP24V70-3U	BP24V70-3U - External Battery Pack for UPS System	Qty: [optional]
BP24V15RT2U	BP24V15RT2U - External Battery Pack for UPS System	Qty: [optional]

Power Distribution		
PS7224	Tripp Lite Power Strip - Multiple outlets wherever you need them	Qty: [optional]
PDU1215	Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment	Qty: [optional]

Shutdown Cable Kits		
AS400CABLE KIT	Power Management Tools - UPS Communication Cable Kit for System i / AS400 / iSeries Servers	Qty: [optional]

SNMP Accessories		
ENVIROSENSE	Power Management Tools - Environmental Sensor	Qty: [optional]
SNMPWEBCARD	Power Management Tools - Internal SNMP/Web Card	Qty: [optional]

Surge Protectors		
DTEL2	Network Surge Suppressor - Essential protection for data and communication lines	Qty: [optional]
DNET1	Network Surge Suppressor - Essential protection for data and communication lines	Qty: [optional]
DCATV	Network Surge Suppressor - Essential protection for TV/VCR coaxial lines	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/EN/products/model.cfm?txtModelID=3299.