



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SUPER7COAX

Protect It! Surge Suppressor



Highlights

- 7 outlets/7 ft. cord
- 2350 joule rating
- Coaxial surge protection
- \$75,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

Description

The SUPER7COAX surge suppressor from Tripp Lite has 7 outlets and a 7-ft. cord with a space-saving right-angle plug. The unit has 2350 joules of surge energy absorption to handle the strongest surges. Built-in coax jacks prevent surges from damaging your cable/satellite equipment. Diagnostic LEDs alert the user to potential power problems. \$75,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only). No warranty cards required for coverage!

Applications

Audio/visual devices, cable television connections, home theater systems, personal computers, CAD/CAM/CAE workstations, network nodes, fileservers, point-of-sale terminals, and more.

Package Includes

Super7Coax Surge Suppressor
Warranty information with instruction manual

Features

- 7 outlets
- 7-ft. cord with space-saving right-angle plug
- Built-in Type F coax jacks prevent surges from damaging your cable/satellite equipment
- \$75,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only) covers connected equipment - No warranty cards required for coverage!
- Surge energy absorption: 2,350 joules; 54,500 amps
- 15 amp circuit breaker
- 2 diagnostic LEDs indicate AC present, line fault & protection present
- EMI/RFI noise filtering
- Keyhole supports for wall mounting
- Recessed power switch
- Lifetime product warranty

Specifications

SYSTEM OVERVIEW

Voltage compatibility	120 VAC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15
Output watts	1800
Outlet quantity / type	7 NEMA 5-15R
Outlet orientation	Single row of 5, plus 2 side mounted outlets
Transformer accommodation	Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 5 transformers total
INPUT	
Input connection type	NEMA 5-15P
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	7 ft.
Input cord length (m)	2.1
Recommended Electrical Service	120V (110-125V)
Input plug features	Space-saving right angle input plug
LEDS ALARMS & SWITCHES	
Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
Switches	Two position on/off power switch
SURGE / NOISE SUPPRESSION	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	2350 joules
Clamping voltage (RMS)	150V
AC suppression response time	< 1 ns
UL1499 let through rating	330V - UL Verified
EMI / RFI filtering	Up to 20 dB
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No
Cable (Coax) Protection	Yes
Cable (Coax) Protection Details	1 line
Network (Ethernet) Protection	No
PHYSICAL	
Shipping weight (lbs)	1.52
Shipping weight (kg)	0.7
Shipping Dimensions (HWD/in)	14 x 5.15 x 1.8
Shipping Dimensions (HWD/cm)	35.5 x 13.1 x 4.6
Unit weight (lbs)	1.5
Unit weight (kg)	0.7
Unit Dimensions (HWD/in)	13 x 5 x 1.5

Unit Dimensions (HWD/cm)	33 x 12.7 x 3.8
Material of construction	Plastic
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting
AC line cord color	Gray
Style	Strip
CERTIFICATIONS	
UL1449 1998 Rev. (AC Suppression)	UL1449
UL1363 (Power Tap)	UL1363
UL497A (Communications)	UL497A
FCC Part 68 (Communications)	FCC Part 68
cUL / CSA (Canada)	cUL
Industry Canada (Communications)	Industry Canada
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product warranty	Lifetime
Connected equipment insurance (USA and Canada Only)	\$75,000

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/EN/products/model.cfm?txtModelID=129.

©2009 Tripp Lite. All Rights Reserved.