

KT Series

Right Angle Sealed Tact Switch for SMT



Features/Benefits

- High shear force with extended bracket
- Easy to pick & place with top plate tab
- Rubber or hard plastic actuator
- Press fit or snap fit caps

Typical Applications

- Telecommunications
- Computer products
- Instrumentation
- Power supply

Specification

CONTACT ARRANGEMENT: SPST, N.O.
TERMINALS: Gullwing type for SMT

Electrical

CONTACT RATING: 1.0 VA max. @ 50 V AC or DC max.
ELECTRICAL & MECHANICAL LIFE: 100,000 make-and-break cycles at full load.
DIELECTRIC STRENGTH: 250 Vrms min. @ sea level.
CONTACT RESISTANCE: Below 50 mΩ typ. initial @ 2-4 V DC, 100 mA.
INSULATION RESISTANCE: 10⁹ Ω min.

Environmental

OPERATING TEMPERATURE: -40°C to 90°C

Process

SOLDERABILITY: Per MIL-STD-202F method 208D, or EIA RS-186E method 9 (1 hour steam aging).
DEGREE OF PROTECTION: IP57; protection against harmful dust deposits, full-scale voltage protection, temporary immersion.

Packaging

Switches supplied in rigid dispensing tubes or anti-static tape and reels per EIA 481-2 (800 pieces per reel.). Tape and cover strip are conductive for use near statically sensitive components.

NOTE: Specifications listed above are for switches with standard options.
For information on specific and custom switches, consult Customer Service Center.

How To Order

Our easy build-a-switch concept allows you to mix and match options to create the switch you need. To order, select desired option from each category and place it in the appropriate box.

SWITCH

Actuator

- B0** Soft, flush
- B1** Soft, 0,64 mm
- B2** Soft, 2,24 mm
- P2** Hard, 2,36 mm
- P3** Hard, 1,50 mm
- P4** Hard, 3,96 mm
- S1** ø0,1 mm for caps
- S2** ø0,14 mm with anti-rotation

Orientation

- S** Side actuated

Mounting Bracket

- AM** Right angle
- A1M** Right angle with front solder pad
- A2M** Right angle with front solder pad pick & place tab
- A3M** Right angle with pick & place tab

Actuating Force

- 3** 3 N (300 grams)

Contact Plating

- 1** Silver
- 3** Gold

Color

- (NONE)** No cap
- 0380** Snap fit, high temperature, ivory, ø8 mm

BUTTON

To order buttons in bulk



Button Type

- 02** Press fit, ø4 mm
- 03** Snap fit, high temperature, ø8 mm

Button Color


- 90** Black
- 80** Ivory




ITT Industries


Cannon

KT Series Right Angle Sealed Tact Switch for SMT


SERIES 

KT11




ACTUATOR 


B0 SOFT, FLUSH



B1 SOFT, 0.64 mm




B2 SOFT, 2.24 mm




B0, B1 & B2 available with A & A1 mounting bracket only.


P2 HARD, 2.36 mm



P3 HARD, 1.50 mm




P4 HARD, 3.96 mm




P4 recommended with A1 & A2 mounting bracket only.

S1 $\phi 0.1$ mm FOR PRESS FIT CAPS



S2 $\phi 0.14$ mm FOR SNAP FIT CAPS




S1 & S2 preferred with A1 & A2 mounting bracket only.



Dimensions are shown: mm (inch)
Dimensions subject to change


KT Series Right Angle Sealed Tact Switch

ORIENTATION






S SIDE ACTUATED

MOUNTING BRACKET





AM RIGHT ANGLE

A1M RIGHT ANGLE WITH FRONT SOLDER PAD



A2M RIGHT ANGLE WITH FRONT SOLDER PAD AND PICK & PLACE TAB


A3M RIGHT ANGLE WITH PICK & PLACE TAB




KT Series Right Angle Sealed Tact Switch

MOUNTING BRACKET

PAD LAYOUT
AM & A3M Mounting Bracket



PAD LAYOUT
A1M & A2M Mounting Bracket



ACTUATING FORCE

OPTION CODE	FORCE
3	3 N (300 grams)


CONTACT PLATING

OPTION CODE	MATERIAL
1	SILVER
3	GOLD

BUTTON

(NONE) NO BUTTON

0380 SNAP FIT, HIGH TEMPERATURE, ivory, Ø8 mm





BUTTON
To order buttons in bulk

B	T	N	K	T	1	1	BUTTON COLOR
							BUTTON TYPE

Button Type

02 PRESS FIT, ø4 mm

03 SNAP FIT, HIGH TEMPERATURE, Ø8 mm



Button Color

OPTION CODE	BUTTON COLOR
90	BLACK
80	IVORY

