

Wire Connection Products

Double row terminal blocks

Series TB200 & TB200HB

Specifications

Description: Double row terminal blocks.

Ratings:

- Volts: — 300V* (TB200)
- 600V* (TB200HB)

Amps: — 30A*

Center Spacing: 0.437" or 7/16" (11.10 mm).

Wire Range: #12 - 22 AWG CU.

Screw Size: #6-32 phillslot screws.

Poles: 2 to 30.

Torque Rating: 9 in-lb.

Distance Between Barriers: 0.353" (8.97mm).

Mounting: #6 screws.

Operating Temperature: +130/-40°C (+266/-40°F).

Construction: Molded, black thermoplastic base with tin-plated brass terminals and zinc-plated steel screws.

Breakdown Voltage: 4800V.

Agency Information: UL/CSA; IEC Compliance; CE Certified.

Flammability Rating: UL 94V0.

* Max rating shown; some options may be rated lower - consult factory.


Dimensions - in

Poles	A	B	Poles	A	B	Poles	A	B
02	1.63	1.31	12	6.00	5.68	22	10.37	10.06
03	2.07	1.75	13	6.44	6.12	23	10.81	10.50
04	2.51	2.18	14	6.87	6.56	24	11.25	10.93
05	2.94	2.62	15	7.31	7.00	25	11.68	11.37
06	3.38	3.06	16	7.75	7.43	26	12.12	11.81
07	3.82	3.50	17	8.19	7.87	27	12.56	12.25
08	4.25	3.93	18	8.62	8.31	28	13.00	12.68
09	4.69	4.37	19	9.06	8.75	29	13.44	13.12
10	5.13	4.81	20	9.50	9.18	30	13.87	13.56
11	5.57	5.25	21	9.94	9.62			


1" = 25.4mm.



TB200 - in (mm)



TB200HB



Catalog Number Build-A-Code

Series	Poles	Screw Options	Marking	Hardware Options
TB <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
200 = Standard 200HB = High barrier	02 to 30	Blank = Steel phillslot, zinc-plated 00 = Screws shipped bulk B = Brass phillslot, nickel-plated BS = Brass Sems phillslot, nickel-plated SP = Steel Sems phillslot, zinc-plated P = Steel Sems (P-style) ST = Stainless steel, phillslot SS = Stainless steel Sems, phillslot STR = Stainless steel, phillips (recess)	L1 to L6 - (See page 296) Marker strips (See page 297) Covers (See page 296)	QC1 to QC20 = Quick connects J201 = Flat slip-on jumper (2 position only) OJ3 = Over barrier jumpers OJ5 = Over barrier jumpers OJ7 = Over barrier jumpers