









PCB PATTERN



CIRCUIT DIAGRAM



$1.40 \pm .10$
[$.055 \pm .004$ in]



NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. RATING: 12VDC, 50mA
- ▲ 5. OPERATING FORCE: 180 ± 50 gms
6. TRAVEL: $0.3\text{mm} \pm 0.1$
7. CONTACT RESISTANCE: 100 MILLI OHMS MAX. (INITIAL)
8. MECHANICAL/ELECTRICAL LIFE 100,000 CYCLES MIN.
- ▲ 9. PACKAGE: TAPE AND REEL - 3000 PIECES PER REEL.
10. ▲ DENOTES CRITICAL PARAMETER

E-SWITCH®

A	14789	RELEASED FOR PRODUCTION	3/25/05	AR
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY
TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

TITLE TL1014AF180QG

SCALE 8:1

DATE 3/25/05

DR AR

DWG D400001

REV A