

(TLP2530)


DEGITAL LOGIC ISOLATION
 LINE RECEIVER
 POWER SUPPLY CONTROL
 SWITCHING POWER SUPPLY
 TRANSISTOR INVERTER

The TOSHIBA TLP2530 and TLP2531 dual photocouplers consist of a pair of GaAlAs light emitting diode and integrated photodetector. This unit is 8-lead DIP package.

Separate connection for the photodiode bias and output transistor collectors improve the speed up to a hundred times that of a conventional phototransistor coupler by reducing the base-collector capacitance.


- TTL Compatibel
- Switching Speed : $t_{pHL}=0.3\mu s$, $t_{pLH}=0.3\mu s$ (Typ.)
 (@ $R_L=1.9k\Omega$)
- Guaranteed Performance Over Temp : $0\sim 70^\circ C$
- Isolation Voltage : 2500Vrms (Min.)
- UL Recognized : UL1577, File No. E67349

Unit in mm




Weight : 0.54g

PIN CONFIGURATION (TOP VIEW)



1. : ANODE.1
2. : CATHODE.1
3. : CATHODE.2
4. : ANODE.2
5. : GND
6. : V_{O2} (OUTPUT 2)
7. : V_{O1} (OUTPUT 1)
8. : V_{CC}

SCHEMATIC



© The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.

© These TOSHIBA products are intended for use in general commercial applications (office equipment, communication equipment, measuring equipment, domestic appliances, etc.), please make sure that you consult with us before you use these TOSHIBA products in equipment which requires extraordinarily high quality and/or reliability, and in equipment which may involve life threatening or critical application, including but not limited to such uses as atomic energy control, airplane or spaceship instrumentation, traffic signals, medical instrumentation, combustion control, all types of safety devices, etc. TOSHIBA cannot accept and hereby disclaims liability for any damage which may occur in case the TOSHIBA products are used in such equipment or applications without prior consultation with TOSHIBA.

(TLP2530)

RECOMMENDED OPERATING CONDITIONS

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage	V _{CC}	0	—	12	V
Forward Current, Each Channel	I _F	—	16	25	mA
Operating Temperature	T _{opr}	−25	—	85	°C

ABSOLUTE MAXIMUM RATINGS

CHARACTERISTIC		SYMBOL	RATING	UNIT
LED	Forward Current (Each channel)	(Note 1) I _F	25	mA
	Pulse Forward Current (Each channel)	(Note 2) I _{FP}	50	mA
	Total Pulse Forward Current (Each channel)	(Note 3) I _{FPT}	1	A
	Reverse Voltage (Each channel)	V _R	5	V
	Diode Power Dissipation (Each channel)	(Note 4) P _D	45	mW
DETECTOR	Output Current (Each channel)	I _O	8	mA
	Peak Output Current (Each channel)	I _{OP}	16	mA
	Supply Voltage	V _{CC}	−0.5~15	V
	Output Voltage (Each channel)	V _O	−0.5~15	V
	Output Power Dissipation (Each channel)	(Note 5) P _o	35	mW
Operating Temperature Range		T _{opr}	−55~100	°C
Storage Temperature Range		T _{stg}	−55~125	°C
Lead Solder Temperature (10s)**		T _{sol}	260	°C
Isolation Voltage (AC, 1min., R.H. ≤ 60%)		(Note 7) BV _S	2500	V _{rms}

Note 1 : Derate 0.8mA above 70°C.

Note 2 : 50% duty cycle, 1ms pulse width. Derate 1.6mA/°C above 70°C.

Note 3 : Pulse width 1μs, 300pps.

Note 4 : Derate 0.9mW/°C above 70°C.

Note 5 : Derate 1mW/°C above 70°C.

** 1.6mm below seating plane.

TLP2530 – 2

1996 – 4 – 8

TOSHIBA CORPORATION

(TLP2530)

ELECTRICAL CHARACTERISTICS
 OVER RECOMMENDED TEMPERATURE (Ta = 0°C~70°C, Unless otherwise noted)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.**	MAX.	UNIT
Current Transfer Ratio (Each Channel)	TLP2530	CTR	IF = 16mA, VO = 0.4V VCC = 4.5V, Ta = 25°C (Note 6)	7	30	—	%
	TLP2531			19	30	—	
	TLP2530	CTR	IF = 16mA, VO = 0.5V VCC = 4.5V (Note 6)	5	—	—	%
	TLP2531			15	—	—	
Logic Low Output Voltage (Each Channel)	TLP2530	VOL	IF = 16mA, IO = 1.1mA VCC = 4.5V	—	0.1	0.4	V
	TLP2531		IF = 16mA, IO = 2.4mA VCC = 4.5V	—	0.1	0.4	V
Logic High Output Current (Each Channel)	IOH		IF = 0mA, VO = VCC = 5.5V Ta = 25°C	—	3	500	nA
			IF = 0mA, VO = VCC = 15V	—	—	50	μA
Logic Low Supply Current	ICCL		IF1 = IF2 = 16mA VO1 = VO2 = Open VCC = 15V	—	160	—	μA
Logic High Supply Current	ICCH		IF1 = IF2 = 0mA VO1 = VO2 = Open VCC = 15V	—	0.05	4	μA
Input Forward Voltage (Each Channel)	VF		IF = 16mA, Ta = 25°C	—	1.65	1.7	V
Temperature Coefficient of Forward Voltage (Each Channel)	ΔVF / ΔTa		IF = 16mA	—	−2	—	mV / °C
Input Reverse Breakdown Voltage (Each Channel)	BVR		IR = 10 μA, Ta = 25°C	5	—	—	V
Input Capacitance (Each Channel)	CIN		f = 1MHz, VF = 0	—	60	—	pF
Input-Output Insulation Leakage Current	II-O		Relative Humidity = 45% t = 5s, VI-O = 3000Vdc Ta = 25°C (Note 7)	—	—	1.0	μA
Resistance (Input-Output)	RI-O		VI-O = 500Vdc (Note 7)	—	10 ¹²	—	Ω
Capacitance (Input-Output)	CI-O		f = 1MHz (Note 7)	—	0.6	—	pF
Input-Input Leakage Current	II-I		Relative Humidity = 45% t = 5s, VI-I = 500V (Note 8)	—	0.005	—	μA
Resistance (Input-Input)	RI-I		VI-I = 500Vdc (Note 8)	—	10 ¹¹	—	Ω
Capacitance (Input-Input)	CI-I		f = 1MHz (Note 8)	—	0.25	—	pF

** All typicals at Ta = 25°C.

(TLP2530)

SWITCHING CHARACTERISTICS (Unless otherwise specified, $T_a = 25^\circ\text{C}$, $V_{CC} = 5\text{V}$, $I_F = 16\text{mA}$)

CHARACTERISTIC	SYMBOL	TEST CIRCUIT	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Propagation Delay Time to Logic Low at Output (Each Channel)	TLP2530	t_{pHL}	1	$R_L = 4.1\text{k}\Omega$	—	0.3	μs
	TLP2531				—	0.2	
Propagation Delay Time to Logic High at Output (Each Channel)	TLP2530	t_{pLH}	1	$R_L = 4.1\text{k}\Omega$	—	0.5	μs
	TLP2531				—	0.3	
Common Mode Transient Immunity at Logic High Level Output (Each Channel, Note 9)	TLP2530	CM_H	2	$I_F = 0\text{mA}$, $V_{CM} = 400\text{V}_{p-p}$ $R_L = 4.1\text{k}\Omega$	—	1000	$\text{V} / \mu\text{s}$
	TLP2531			$I_F = 0\text{mA}$, $V_{CM} = 400\text{V}_{p-p}$ $R_L = 1.9\text{k}\Omega$	—	1000	
Common Mode Transient Immunity at Logic Low Level Output (Each Channel, Note 9)	TLP2530	CM_L	2	$V_{CM} = 400\text{V}_{p-p}$ $R_L = 4.1\text{k}\Omega$, $I_F = 16\text{mA}$	—	−1000	$\text{V} / \mu\text{s}$
	TLP2531			$V_{CM} = 400\text{V}_{p-p}$ $R_L = 1.9\text{k}\Omega$, $I_F = 16\text{mA}$	—	−1000	
Bandwidth (Each Channel, Note 10)	BW	3	$R_L = 100\Omega$	—	2	—	MHz

Note 6 : DC CURRENT TRANSFER RATIO is defined as the ratio of output collector current, I_O , to the forward LED input current, I_F , times 100%.

Note 7 : Device considered a two-terminal device : Pins 1, 2, 3 and 4 shorted together and Pins 5, 6, 7, and 8 shorted together.

Note 8 : Measured between pins 1 and 2 shorted together, and pins 3 and 4 shorted together.

Note 9 : Common mode transient immunity in Logic High level is the maximum tolerable (Positive) dV_{cm}/dt on the leading edge of the common mode pulse, V_{cm} , to assure that the output will remain in a Logic High state (i.e., $V_O > 2.0\text{V}$). Common mode transient immunity in Logic Low level is the maximum tolerable (negative) dV_{cm}/dt on the trailing edge of the common mode pulse signal, V_{cm} , to assure that the output will remain in a Logic Low state (i.e., $V_O > 0.8\text{V}$).

Note 10 : The frequency at which the ac output voltage is 3dB below the low frequency asymptote.



TLP2530 – 4

1996 – 4 – 8



TOSHIBA CORPORATION

(TLP2530)

TEST CIRCUIT 1 : SWITCHING TIME, t_{pHL} , t_{pLH}




TEST CIRCUIT 2 : TRANSIENT IMMUNITY AND TYPICAL WAVEFORM



$$CM_H = \frac{320(V)}{t_r(\mu s)}, CM_L = \frac{320(V)}{t_f(\mu s)}$$

TEST CIRCUIT 3 : FREQUENCY RESPONSE









TLP2530 - 5

1996 - 4 - 8

TOSHIBA CORPORATION

(TLP2530)



TLP2530 - 6

1996 - 4 - 8

TOSHIBA CORPORATION

(TLP2530)

