

TELECOMMUNICATION MODEM COUPLING TRANSFORMER FOR V.90 WET APPLICATION


A. Electrical Specifications (@ 25°C)

1. Pri Source Impedance; 600Ω
2. Sec Load Impedance; 301Ω
3. Insertion Loss;
4.00dB MAX @ 1KHz, 0dBm, 65mADC
4. Frequency Response (relative to 1KHz)
±3.5dB @ 300Hz to 600Hz, 0dBm
±1.0dB @ 600Hz to 4KHz, 0dBm
5. Longitudinal Balance;
60dB MIN @ 200Hz to 1KHz
40dB MIN @ 1KHz to 4KHz
6. Return Loss; 15dB TYP @ 1KHz, 0dBm
7. DC Resistance;
(1-2) = 150Ω ±15%
(3-4) = 150Ω ±15%
8. Turns Ratio; (1-2):(4-3) = 1:1.00±2%
9. Dielectric Strength;
1875Vrms 1 second Pri to Sec
10. Total Harmonic Distortion;
-82dB MAX @ 600Hz, -10dBm, 65mADC


B. Marking; TTC-5013C, TAMURA, date code and country of origin
"C" designates UL approved family classification

C. Safety: UL 1950 3rd Edition, UL60950, EN60950

D. Schematic Diagram



E. Mechanical Specifications


Black dot
indicates
pin 1

Country
of origin

Date
Code


UL #E208555

PREPARED BY:

K. BRENNAN

ENGINEER:

M. PITCHAI

QUALITY CONTROL:

T. CLEM

APPROVED:

Y. SEKIGUCHI

DWG CONTROL NO.

P-A1-12513

ACAD\TTC\A1125131.DWG

REV

B

MODEM COUPLING
TRANSFORMER

TAMURA CORPORATION OF AMERICA

43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624
(951) 699-1270 FAX 9516769482

TTC-5013

MODEL SPECIFICATION

DIM: mm[In] SCL: 1/1 SH: 1 OF 1

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.

MODEL NUMBER

TTC-5013