



HONEYWELL PART NUMBER
V15H16-CZ100A06-K
PRODUCT CODE
CFW2049



CHARACTERISTICS		ELECTRICAL DATA		DESIGN UNITS: MM		DRAWN	KSR	01APR08	Honeywell				
CONTACT ARRANGEMENT S.P.D.T		EN 17 COC 16(4)A 250V~ 25T150 μ 5E4 RV c RV 16A 1/2HP 125/250VAC		TOLERANCES UNLESS NOTED:		CHECK	RJ	01APR08					
OPERATING FORCE: 60gf MAX. DIFFERENTIAL FORCE: _____ RELEASE FORCE: 10gf MIN. FREE POSITION: _____ OPERATING POSITION: 20.6±1.6MM. PRE-TRAVEL: 3.2MM MAX. DIFFERENTIAL TRAVEL: 1.2MM MAX. OVER-TRAVEL: 1.3MM MIN. FULL OVERTRAVEL FORCE: _____				NO PLACE X ± ± ONE PLACE .X ± ± TWO PLACE .XX ± ± 0.40 THREE PLACE .XXX ± ± ANGLES X ± ± 2°		THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.			SIZE B TYPE I CAGE CODE DRAWING NAME V15H16-CZ100A06-K REV A				
				THIRD ANGLE PROJECTION 		INTERPRET PER ASME Y14.5M-1994 OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY							