## **WS 5 SERIES**

## **End Strippers**

- For 600 volt to 35 KV cables
- .260 to 1.265 in (6.60 to 32.13 mm) cable O.D.
- Strips XLPE, polyethylene and EPR insulation\*
- Precision stripping of insulation only or insulation and semicon simultaneously
- Ideal for primary URD cableGuarded cutting blade prevents injury
- WS 5 and WS 5DA permit accurate preset stripping lengths of up to 4 in (101.60 mm). Bar removable for infinite stripping • Accepts SW 2 ratchet wrench for leverage
- Stop bar with drill adapter can be purchased separately or comes with WS 5DA. Metric stop bar is also available
- Bushing insert fits over cable
  - Bushing insert presets cutting blade depth Bushings can be changed easily and quickly
- U.S. Patent No.: 3,361,015 Japan: 1,131,678 Canada: 827,962
- Made in the U.S.A.
- Model WS 5B available to strip from 3/4" up to 5-3/4" lengths (Part No.: 37710)
- Length: 6 in (152 mm) Weight: 1 lb (454 g)
- \* See instruction sheet for detailed information

Ordering Information: Choose tool and bushing (below)

Cracing information. Choose tool and busining (below)					
Model	Part Number	Insulation Materials	Insulation Thickness Max. (mils)	Replacement Blade	Rotating Stop Bar
WS 5 WS 5 DA	10327 10336	XLPE or EPR XLPE or EPR	400 400	CB 7-2 CB 7-2	10346 10337
WO D DA	10336	ALPE OF EPR	400	UD 7-2	10337

CB 7-2 Replacement Blade Part No.: 10324

## Adjustable End Strippers

- Upgraded model of the WS 5
- Same basic function as the WS 5 Model plus:
  - New adjustable strip stop with rotary mechanism eliminates the need for hex wrench
    - New adjustment window, with inch and metric readings allows easy setting of stop for precise strip lengths
      - Strip lengths from 0.625
        - in (15.9 mm) up to 2.5 in maximum (63.5 mm) For 600 volt to 35 KV cables

          - 0.260 to 1.265 in (6.60 to 32.13 mm) Cable O.D.
            - Strips XLPE, polyethylene, and EPR\* insulation up to 400 mils thick
              - Precision stripping of insulation only or with semicon over insulation\*
              - Ideal for primary URD cable
              - Guarded cutting blade prevents injury
- Accepts SW 2 ratchet wrench for leverage
  WS 5A-DA comes with 3/8" drill adapter
- Drill adapter also available separately. Tools purchased prior to December 2005 require retrofit. Contact customer service for details
- Made in the U.S.A.

WS 5A-DA

- Length: 8 in (203 mm)
  Weight: 1.2 lb (544 g)
- Replacement Blade: CB 7-2 (Part No.: 10324)
- WS 5A Part No.: 37415
  WS 5A-DA Part No.: 38750
- \* See instruction sheet for detailed information