

## Quad 2-Input NAND Schmitt Trigger

The MC74VHCT132A is an advanced high speed CMOS Schmitt NAND trigger fabricated with silicon gate CMOS technology. It achieves high speed operation similar to equivalent Bipolar Schottky TTL while maintaining CMOS low power dissipation.

Pin configuration and function are the same as the MC74VHC00, but the inputs have hysteresis and, with its Schmitt trigger function, the VHCT132A can be used as a line receiver which will receive slow input signals.

The VHCT inputs are compatible with TTL levels. This device can be used as a level converter for interfacing 3.3V to 5.0V, because it has full 5V CMOS level output swings.

The VHCT132A input structures provide protection when voltages between 0V and 5.5V are applied, regardless of the supply voltage. The output structures also provide protection when  $V_{CC} = 0V$ . These input and output structures help prevent device destruction caused by supply voltage – input/output voltage mismatch, battery backup, hot insertion, etc.

The internal circuit is composed of three stages, including a buffer output which provides high noise immunity and stable output. The inputs tolerate voltages up to 7V, allowing the interface of 5V systems to 3V systems.

- High Speed:  $t_{PD} = 4.9ns$  (Typ) at  $V_{CC} = 5V$
- Low Power Dissipation:  $I_{CC} = 2\mu A$  (Max) at  $T_A = 25^\circ C$
- TTL-Compatible Inputs:  $V_{IL} = 0.8V$ ;  $V_{IH} = 2.0V$
- Power Down Protection Provided on Inputs
- Balanced Propagation Delays
- Designed for 2V to 5.5V Operating Range
- Low Noise:  $V_{OLP} = 0.8V$  (Max)
- Pin and Function Compatible with Other Standard Logic Families
- Latchup Performance Exceeds 300mA
- ESD Performance: HBM > 2000V; Machine Model > 200V
- Chip Complexity: 72 FETs or 18 Equivalent Gates

## MC74VHCT132A



**D SUFFIX**  
14-LEAD SOIC PACKAGE  
CASE 751A-03



**DT SUFFIX**  
14-LEAD TSSOP PACKAGE  
CASE 948G-01



**M SUFFIX**  
14-LEAD SOIC EIAJ PACKAGE  
CASE 965-01

### ORDERING INFORMATION

|               |           |
|---------------|-----------|
| MC74VHCTXXAD  | SOIC      |
| MC74VHCTXXADT | TSSOP     |
| MC74VHCTXXAM  | SOIC EIAJ |

### FUNCTION TABLE

| Inputs |   | Output<br>$\bar{Y}$ |
|--------|---|---------------------|
| A      | B |                     |
| L      | L | H                   |
| L      | H | H                   |
| H      | L | H                   |
| H      | H | L                   |

# MC74VHCT132A




Figure 1. Logic Diagram




Figure 2. Pinout: 14-Lead Packages (Top View)

# MC74VHCT132A

## MAXIMUM RATINGS\*

| Symbol           | Parameter                                                        | Value                          | Unit |
|------------------|------------------------------------------------------------------|--------------------------------|------|
| V <sub>CC</sub>  | DC Supply Voltage                                                | – 0.5 to + 7.0                 | V    |
| V <sub>in</sub>  | DC Input Voltage                                                 | – 0.5 to + 7.0                 | V    |
| V <sub>out</sub> | DC Output Voltage                                                | – 0.5 to V <sub>CC</sub> + 0.5 | V    |
| I <sub>IK</sub>  | Input Diode Current                                              | – 20                           | mA   |
| I <sub>OK</sub>  | Output Diode Current                                             | ± 20                           | mA   |
| I <sub>out</sub> | DC Output Current, per Pin                                       | ± 25                           | mA   |
| I <sub>CC</sub>  | DC Supply Current, V <sub>CC</sub> and GND Pins                  | ± 50                           | mA   |
| P <sub>D</sub>   | Power Dissipation in Still Air, SOIC Packages†<br>TSSOP Package† | 500<br>450                     | mW   |
| T <sub>stg</sub> | Storage Temperature                                              | – 65 to + 150                  | °C   |

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high-impedance circuit. For proper operation, V<sub>in</sub> and V<sub>out</sub> should be constrained to the range GND ≤ (V<sub>in</sub> or V<sub>out</sub>) ≤ V<sub>CC</sub>. Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or V<sub>CC</sub>). Unused outputs must be left open.

\* Absolute maximum continuous ratings are those values beyond which damage to the device may occur. Exposure to these conditions or conditions beyond those indicated may adversely affect device reliability. Functional operation under absolute-maximum-rated conditions is not implied.

† Derating — SOIC Packages: – 7 mW/°C from 65° to 125°C  
TSSOP Package: – 6.1 mW/°C from 65° to 125°C

## RECOMMENDED OPERATING CONDITIONS

| Symbol           | Parameter                                | Min  | Max             | Unit |
|------------------|------------------------------------------|------|-----------------|------|
| V <sub>CC</sub>  | DC Supply Voltage                        | 4.5  | 5.5             | V    |
| V <sub>in</sub>  | DC Input Voltage                         | 0    | 5.5             | V    |
| V <sub>out</sub> | DC Output Voltage                        | 0    | V <sub>CC</sub> | V    |
| T <sub>A</sub>   | Operating Temperature, All Package Types | – 40 | + 85            | °C   |

## DC ELECTRICAL CHARACTERISTICS

| Symbol           | Parameter                                                    | Test Conditions                                                                 | V <sub>CC</sub><br>V | T <sub>A</sub> = 25°C |                   |                      | T <sub>A</sub> ≤ 85°C |                      | T <sub>A</sub> ≤ 125°C |                      | Unit |
|------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------|----------------------|-----------------------|-------------------|----------------------|-----------------------|----------------------|------------------------|----------------------|------|
|                  |                                                              |                                                                                 |                      | Min                   | Typ               | Max                  | Min                   | Max                  | Min                    | Max                  |      |
| V <sub>T+</sub>  | Positive Threshold Voltage                                   |                                                                                 | 3.0<br>4.5<br>5.5    |                       |                   | 1.7<br>2.0<br>2.0    |                       | 1.6<br>2.0<br>2.0    |                        | 1.6<br>2.0<br>2.0    | V    |
| V <sub>T–</sub>  | Negative Threshold Voltage                                   |                                                                                 | 3.0<br>4.5<br>6.0    | 0.35<br>0.5<br>0.6    |                   |                      | 0.35<br>0.5<br>0.6    |                      | 0.35<br>0.5<br>0.6     |                      | V    |
| V <sub>H</sub>   | Hysteresis Voltage                                           |                                                                                 | 3.0<br>4.5<br>5.5    | 0.30<br>0.40<br>0.50  |                   | 1.20<br>1.40<br>1.60 | 0.30<br>0.40<br>0.50  | 1.20<br>1.40<br>1.60 | 0.30<br>0.40<br>0.50   | 1.20<br>1.40<br>1.60 | V    |
| V <sub>OH</sub>  | Minimum High-Level Output Voltage<br>I <sub>OH</sub> = –50μA | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OH</sub> = –50μA | 2.0<br>3.0<br>4.5    | 1.9<br>2.9<br>4.4     | 2.0<br>3.0<br>4.5 |                      | 1.9<br>2.9<br>4.4     |                      | 1.9<br>2.9<br>4.4      |                      | V    |
|                  |                                                              | I <sub>OH</sub> = –4mA<br>I <sub>OH</sub> = –8mA                                | 4.5<br>5.5           | 2.58<br>3.94          |                   |                      | 2.48<br>3.80          |                      | 2.34<br>3.66           |                      |      |
| V <sub>OL</sub>  | Maximum Low-Level Output Voltage                             | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OL</sub> = 50μA  | 2.0<br>3.0<br>4.5    |                       | 0.0<br>0.0<br>0.0 | 0.1<br>0.1<br>0.1    |                       | 0.1<br>0.1<br>0.1    |                        | 0.1<br>0.1<br>0.1    | V    |
|                  |                                                              | I <sub>OL</sub> = 4mA<br>I <sub>OL</sub> = 8mA                                  | 4.5<br>5.5           |                       |                   | 0.36<br>0.36         |                       | 0.44<br>0.44         |                        | 0.52<br>0.52         |      |
| I <sub>IN</sub>  | Maximum Input Leakage Current                                | V <sub>IN</sub> = 5.5V or GND                                                   | 0 to 5.5             |                       |                   | ± 0.1                |                       | ± 1.0                |                        | ± 1.0                | μA   |
| I <sub>CC</sub>  | Maximum Quiescent Supply Current                             | V <sub>IN</sub> = V <sub>CC</sub> or GND                                        | 5.5                  |                       |                   | 2.0                  |                       | 20                   |                        | 40                   | μA   |
| I <sub>CCT</sub> | Quiescent Supply Current                                     | Input: V <sub>IN</sub> = 3.4V                                                   | 5.5                  |                       |                   | 1.35                 |                       | 1.50                 |                        | 1.65                 | mA   |
| I <sub>OPD</sub> | Output Leakage Current                                       | V <sub>OUT</sub> = 5.5V                                                         | 0.0                  |                       |                   | 0.5                  |                       | 5.0                  |                        | 10                   | μA   |

# MC74VHCT132A

## AC ELECTRICAL CHARACTERISTICS (Input $t_r = t_f = 3.0\text{ns}$ )

| Symbol                   | Parameter                                      | Test Conditions                                                             | $T_A = 25^\circ\text{C}$ |             |              | $T_A = -40 \text{ to } 85^\circ\text{C}$ |              | $T_A \leq 125^\circ\text{C}$ |              | Unit |
|--------------------------|------------------------------------------------|-----------------------------------------------------------------------------|--------------------------|-------------|--------------|------------------------------------------|--------------|------------------------------|--------------|------|
|                          |                                                |                                                                             | Min                      | Typ         | Max          | Min                                      | Max          | Min                          | Max          |      |
| $t_{PLH}$ ,<br>$t_{PHL}$ | Maximum Propagation Delay, A or B to $\bar{Y}$ | $V_{CC} = 3.3 \pm 0.3 \text{ V}$ $C_L = 15\text{pF}$<br>$C_L = 50\text{pF}$ |                          | 7.6<br>10.1 | 11.9<br>15.4 | 1.0<br>1.0                               | 14.0<br>17.5 |                              | 16.5<br>20.0 | ns   |
|                          |                                                | $V_{CC} = 5.0 \pm 0.5 \text{ V}$ $C_L = 15\text{pF}$<br>$C_L = 50\text{pF}$ |                          | 4.9<br>6.4  | 7.7<br>9.7   | 1.0<br>1.0                               | 9.0<br>11.0  |                              | 11.0<br>13.0 |      |
| $C_{in}$                 | Maximum Input Capacitance                      |                                                                             |                          | 4           | 10           |                                          | 10           |                              | 10           | pF   |

|                 |                                         |                                         |    |
|-----------------|-----------------------------------------|-----------------------------------------|----|
| C <sub>PD</sub> | Power Dissipation Capacitance (Note 1.) | Typical @ 25°C, V <sub>CC</sub> = 5.0 V | pF |
|                 |                                         | 16                                      |    |

1.  $C_{PD}$  is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation:  $I_{CC(OPR)} = C_{PD} \cdot V_{CC} \cdot f_{in} + I_{CC}/4$  (per gate).  $C_{PD}$  is used to determine the no-load dynamic power consumption;  $P_D = C_{PD} \cdot V_{CC}^2 \cdot f_{in} + I_{CC} \cdot V_{CC}$ .

## NOISE CHARACTERISTICS (Input $t_r = t_f = 3.0\text{ns}$ , $C_L = 50\text{pF}$ , $V_{CC} = 5.0 \text{ V}$ )

| Symbol    | Characteristic                           | $T_A = 25^\circ\text{C}$ |      | Unit |
|-----------|------------------------------------------|--------------------------|------|------|
|           |                                          | Typ                      | Max  |      |
| $V_{OLP}$ | Quiet Output Maximum Dynamic $V_{OL}$    | 0.3                      | 0.8  | V    |
| $V_{OLV}$ | Quiet Output Minimum Dynamic $V_{OL}$    | -0.3                     | -0.8 | V    |
| $V_{IHD}$ | Minimum High Level Dynamic Input Voltage |                          | 3.5  | V    |
| $V_{ILD}$ | Maximum Low Level Dynamic Input Voltage  |                          | 1.5  | V    |






Figure 3. Switching Waveforms



\*Includes all probe and jig capacitance

Figure 4. Test Circuit

(a) A Schmitt-Trigger Squares Up Inputs With Slow Rise and Fall Times



(b) A Schmitt-Trigger Offers Maximum Noise Immunity





Figure 5. Typical Schmitt-Trigger Applications

# MC74VHCT132A

## OUTLINE DIMENSIONS

### D SUFFIX SOIC-14 CASE 751A-03 ISSUE F




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 8.55        | 8.75 | 0.337     | 0.344 |
| B   | 3.80        | 4.00 | 0.150     | 0.157 |
| C   | 1.35        | 1.75 | 0.054     | 0.068 |
| D   | 0.35        | 0.49 | 0.014     | 0.019 |
| F   | 0.40        | 1.25 | 0.016     | 0.049 |
| G   | 1.27 BSC    |      | 0.050 BSC |       |
| J   | 0.19        | 0.25 | 0.008     | 0.009 |
| K   | 0.10        | 0.25 | 0.004     | 0.009 |
| M   | 0°          | 7°   | 0°        | 7°    |
| P   | 5.80        | 6.20 | 0.228     | 0.244 |
| R   | 0.25        | 0.50 | 0.010     | 0.019 |

**DT SUFFIX  
TSSOP  
CASE 948G-01  
ISSUE O**




- NOTES:**
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  2. CONTROLLING DIMENSION: MILLIMETER.
  3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
  4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
  5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
  6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
  7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

|     | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
| DIM | MIN         | MAX  | MIN       | MAX   |
| A   | 4.90        | 5.10 | 0.193     | 0.200 |
| B   | 4.30        | 4.50 | 0.169     | 0.177 |
| C   | ----        | 1.20 | ----      | 0.047 |
| D   | 0.05        | 0.15 | 0.002     | 0.006 |
| F   | 0.50        | 0.75 | 0.020     | 0.030 |
| G   | 0.65 BSC    |      | 0.026 BSC |       |
| H   | 0.50        | 0.60 | 0.020     | 0.024 |
| J   | 0.09        | 0.20 | 0.004     | 0.008 |
| J1  | 0.09        | 0.16 | 0.004     | 0.006 |
| K   | 0.19        | 0.30 | 0.007     | 0.012 |
| K1  | 0.19        | 0.25 | 0.007     | 0.010 |
| L   | 6.40 BSC    |      | 0.252 BSC |       |
| M   | 0°          | 8°   | 0°        | 8°    |

# MC74VHCT132A

## OUTLINE DIMENSIONS

M SUFFIX  
SO-14  
CASE 965-01  
ISSUE O



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH OR PROTRUSIONS AND ARE MEASURED AT THE PARTING LINE. MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
5. THE LEAD WIDTH DIMENSION (b) DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE LEAD WIDTH DIMENSION AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OR THE FOOT. MINIMUM SPACE BETWEEN PROTRUSIONS AND ADJACENT LEAD TO BE 0.46 (0.018).

|                | MILLIMETERS |       | INCHES    |       |
|----------------|-------------|-------|-----------|-------|
| DIM            | MIN         | MAX   | MIN       | MAX   |
| A              | ---         | 2.05  | ---       | 0.081 |
| A <sub>1</sub> | 0.05        | 0.20  | 0.002     | 0.008 |
| b              | 0.35        | 0.50  | 0.014     | 0.020 |
| c              | 0.18        | 0.27  | 0.007     | 0.011 |
| D              | 9.90        | 10.50 | 0.390     | 0.413 |
| E              | 5.10        | 5.45  | 0.201     | 0.215 |
| e              | 1.27 BSC    |       | 0.050 BSC |       |
| H <sub>E</sub> | 7.40        | 8.20  | 0.291     | 0.323 |
| 0.50           | 0.50        | 0.85  | 0.020     | 0.033 |
| L <sub>E</sub> | 1.10        | 1.50  | 0.043     | 0.059 |
| M              | 0°          | 10°   | 0°        | 10°   |
| Q <sub>1</sub> | 0.70        | 0.90  | 0.028     | 0.035 |
| Z              | ---         | 1.42  | ---       | 0.056 |

**ON Semiconductor** and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

## PUBLICATION ORDERING INFORMATION

### NORTH AMERICA Literature Fulfillment:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** ONlit@hibbertco.com  
Fax Response Line: 303-675-2167 or 800-344-3810 Toll Free USA/Canada

**N. American Technical Support:** 800-282-9855 Toll Free USA/Canada

**EUROPE:** LDC for ON Semiconductor – European Support

**German Phone:** (+1) 303-308-7140 (Mon–Fri 2:30pm to 7:00pm CET)  
**Email:** ONlit-german@hibbertco.com

**French Phone:** (+1) 303-308-7141 (Mon–Fri 2:00pm to 7:00pm CET)  
**Email:** ONlit-french@hibbertco.com

**English Phone:** (+1) 303-308-7142 (Mon–Fri 12:00pm to 5:00pm GMT)  
**Email:** ONlit@hibbertco.com

**EUROPEAN TOLL-FREE ACCESS\*: 00-800-4422-3781**

\*Available from Germany, France, Italy, UK, Ireland

### CENTRAL/SOUTH AMERICA:

**Spanish Phone:** 303-308-7143 (Mon–Fri 8:00am to 5:00pm MST)  
**Email:** ONlit-spanish@hibbertco.com

**Toll-Free from Mexico:** Dial 01-800-288-2872 for Access –  
then Dial 866-297-9322

**ASIA/PACIFIC:** LDC for ON Semiconductor – Asia Support

**Phone:** 1-303-675-2121 (Tue–Fri 9:00am to 1:00pm, Hong Kong Time)  
**Toll Free** from Hong Kong & Singapore:  
**001-800-4422-3781**

**Email:** ONlit-asia@hibbertco.com

**JAPAN:** ON Semiconductor, Japan Customer Focus Center

4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-0031  
**Phone:** 81-3-5740-2700  
**Email:** r14525@onsemi.com

**ON Semiconductor Website:** <http://onsemi.com>

For additional information, please contact your local  
Sales Representative.