


0331/9353




Basic Part Number	Length L	Depth N
0331-0	3,81	3,23
9353-0	4,32	3,73

X3XX-X-15-XX-18-XX-10-0

Solder mount in 1,80 min. mounting hole


7405



7405-0-18-XX-18-XX-10-0

Press-fit in 2,13 mounting hole


3450



3450-0-15-XX-18-XX-04-0

Solder mount in 1,09 min. mounting hole

9354/7406




Basic Part Number	Length L
7406-0	3,05
9354-0	4,32

XXXX-0-15-XX-18-XX-10-0

Solder mount in 1,80 min. mounting hole

0319




0319-X-15-XX-18-XX-04-0

Solder mount in 1,07 min. mounting hole

Basic Part Number	Length A
0319-0	6,1
0319-1	7,11


1313



1313-0-15-XX-18-XX-04-0

Press-fit in 1,42 mounting hole

6628




6628-0-18-XX-18-XX-10-0

Surface mount

Also available on 12mm wide carrier tape: 3.700 parts per 330mm reel. Order as: 6628-0-58-XX-18-XX-10-0


3520



3520-0-15-XX-18-XX-10-0

Solder mount in 1,78 min. mounting hole

8331



8331-0-15-XX-18-XX-10-0

Solder mount in 1,80 min. mounting hole

SPECIFICATIONS

SHELL MATERIAL:
Brass Alloy 360, 1/2 Hard

CONTACT MATERIAL:
Beryllium Copper Alloy 172, HT

PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY

TOLERANCES ON:
LENGTHS: ± 0,13
DIAMETERS: ± 0,05
ANGLES: ± 2°

ORDER CODE: XXXX - X - 1X - XX - 18 - XX - XX - 0

BASIC PART #

SPECIFY SHELL FINISH:

01 5,08µm TIN/LEAD OVER NICKEL

80 5,08µm TIN OVER NICKEL

15 0,25µm GOLD OVER NICKEL

SPECIFY CONTACT FINISH:

01 5,08µm TIN/LEAD OVER NICKEL

80 5,08µm TIN OVER NICKEL

27 0,76µm GOLD OVER NICKEL

CONTACT

#18 CONTACT (DATA ON PAGE 211)

