

0355	0354	3490	3808
0355-0-15-XX-02-XX-10-0 Solder mount in 2,59 min. mounting hole	0354-0-15-XX-02-XX-10-0 Pentagonal press-fit in 2,64 min. plated thru hole	3490-0-15-XX-02-XX-10-0 Press-fit in 2,31 mounting hole	3808-0-15-XX-02-XX-10-0 Press-fit in 2,29 mounting hole

9184	9222	Carrier tape format for 9184 & 9222.	
9184-0-15-XX-02-XX-40-0 Bottom entry, surface mount 2,34 min. plated thru hole. Also available on carrier tape, Order as: 9184-0-57-XX-02-XX-40-0	9222-2-15-XX-02-XX-40-0 Bottom entry, surface mount 2,08 min. plated thru hole Also available on carrier tape, Order as: 9222-2-57-XX-02-XX-40-0	Carrier tape format for 9184 & 9222. 1,500 pieces per 330mm reel	

--	--	--	--

SPECIFICATIONS SHELL MATERIAL: Brass Alloy 360, 1/2 Hard CONTACT MATERIAL: Beryllium Copper Alloy 172, HT PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY TOLERANCES ON: LENGTHS: ± 0,13 DIAMETERS: ± 0,05 ANGLES: ± 2°	ORDER CODE: XXXX - X - 15 - XX - 02 - XX - 10 - 0 BASIC PART # → SPECIFY SHELL FINISH: → 01 5,08µm TIN/LEAD OVER NICKEL 80 5,08µm TIN OVER NICKEL ◇ 15 0,25µm GOLD OVER NICKEL ◇ SPECIFY CONTACT FINISH: → 01 5,08µm TIN/LEAD OVER NICKEL 80 5,08µm TIN OVER NICKEL ◇ 27 0,76µm GOLD OVER NICKEL ◇ CONTACT #02 CONTACT (DATA ON PAGE 213)
---	---