




0291



0291-0-15-XX-16-XX-10-0
Hex press-fit in 1,7 plated
thru hole

0293



0293-0-15-XX-16-XX-10-0
Press-fit in 1,7 mounting hole

0287



0287-0-15-XX-16-XX-10-0
Solder mount in 1,65 min. mounting hole
Also available on 8mm wide carrier
tape: 3,250 parts per 330mm reel.
Order as: 0287-0-57-XX-16-XX-10-0

0285



0285-0-15-XX-16-XX-10-0
Solder mount in 1,65 min.
mounting hole

0284



0284-0-15-XX-16-XX-10-0
Solder mount in 1,78 min.
mounting hole

8114



8114-0-15-XX-16-XX-04-0
Press-fit from underside of pc board
into 1,65 mounting hole

0407



0407-0-15-XX-16-XX-04-0
Press-fit in 1,68 mounting hole

0415



0415-0-15-XX-16-XX-10-0
Solder mount in 1,6 min. mounting hole
Also available on 24mm wide carrier
tape: 1,500 parts per 330mm reel.
Order as: 0415-0-57-XX-16-XX-10-0

0303



0303-0-19-XX-16-XX-10-0
Wire Termination
Press-fit in 1,70 mounting hole

0306


0306-0-19-XX-16-XX-10-0
Wire Termination
#18 gage crimp barrel

0273


0273-0-15-XX-16-XX-10-0
Press-fit in 1,98 mounting hole

7520


7520-0-15-XX-16-XX-10-0
Press-fit in 1,68 mounting hole

SPECIFICATIONS

SHELL MATERIAL:
Brass Alloy 360, 1/2 Hard

CONTACT MATERIAL:
Beryllium Copper Alloy 172, HT

**PART MANUFACTURED IN
INCHES, METRIC FOR REF ONLY**

TOLERANCES ON:
LENGTHS: ± 0,13
DIAMETERS: ± 0,05
ANGLES: ± 2°

ORDER CODE: XXXX - X - 1X - XX - 16 - XX - XX - 0

BASIC PART #

SPECIFY SHELL FINISH:
01 5,08µm TIN/LEAD OVER NICKEL
80 5,08µm TIN OVER NICKEL
15 0,25µm GOLD OVER NICKEL

SPECIFY CONTACT FINISH:
01 5,08µm TIN/LEAD OVER NICKEL
80 5,08µm TIN OVER NICKEL
27 0,76µm GOLD OVER NICKEL



CONTACT
#16 CONTACT (DATA ON PAGE 210)