



Description:

This product is designed for use in ESD controlled areas where there are ESD sensitive devices. All sheet protectors are made from a stable, amine-free, clear, static dissipative polyethylene 6 Mil thick film. Dissipative agent is extruded in and is slow blooming with an effective shelf life in excess of two years. These products are designed to hold 8 1/2" x 11" sheets and can be cleaned for use in Class 100 Clean Rooms.

Humidity independent.
N-Octanoic Acid Free.
Does not promote corrosion.
Has no measurable outgassing.

Electrical Properties:

Static Decay:	< 1.0 sec.	per FTMS 101C, Method 4046
Surface Resistivity:	$10^{10} - 10^{12}$ Ohms/sq.	per ASTM D-257
Polycarbonate Haze:	Negligible	per 72 hour contact
Corrosivity:	Negligible	per FTMS 101C-3005

Specifications:

Melt Index:	.050 gm/10 min.	per ASTM D-1238
Density:	0.923 gm/cc	per ASTM D-1505
Haze:	10%	per ASTM D-1003
60° gloss:	90	per ASTM D-2457
45° gloss:	56	per ASTM D-2457
Dart impact:	230 gms	per ASTM D-1709
Coefficient of friction:	0.50	per ASTM D-1894

- A. Sheet protector has holes for standard US three ring binder.
Wording across ring hole area:

"DESCO IND. INC. #07470 STATIC SAFE"

SHEET PROTECTOR, STATIC SAFE, 6 MIL

DESCO

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: www.desco.com
PHONE (909) 627-8178 FAX (909) 627-7449

DESCO EAST: 90 HUDSON RD, CANTON, MA 02021-1407
PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER
07470

DATE:
3/05