





- ⑤ PART WITH PICK-UP CAP, P/N XXXXXXXX-XXX LF
- ⑥ THE STD PACKAGING IS IN TRAY
- 7 FOR TAPE & REEL PACKAGING, SUFFIX \*-TR\* ADDED.  
P/N XXXXXXXX-XXX -TR LF
- 8 THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.
- ⑨ THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
- ⑩ PART NUMBERS ENDING IN "LF" MEANS FOR NOTE 8 LEAD FREE IDENTIFICATION
  - (i) XXXXXXXX-XXXLF IS EQUIVALENT TO PREVIOUS P/N XXXXXXXX-XXX
  - (ii) XXXXXXXX-XXXCLF IS EQUIVALENT TO PREVIOUS P/N XXXXXXXX-XXXC

mat'l. code				surface ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection 		product family <b>SAS</b>		
litr ecn no dr date				angles unless otherwise specified						title <b>SAS RECEPTACLE WIDE BASE HYBRID TYPE ASSY</b>		
E				linear		= ±0.20						
				± 2°								
				dr GL L00		2005-02-23				dwg no sheet 2 of 2 size		
				engr GL L00		2005-02-23				10036876		A4
				chr GL L00		2007-02-14						
				appd JOEY NG		2007-02-14						
sheet		revision								type CUSTOMER Drawing		