

4

NOTES: (cont'd)


6 THE STD PACKAGING IS IN TRAY.

7 THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH 1.57MM THICK CIRCUIT BOARD.

⑧ THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.

⑨ PART NUMBER ENDING IN "LF" MEANS FOR NOTE 8 LEAD FREE IDENTIFICATION.

P/N XXXXXXXX-XXXLF IS EQUIVALENT TO PREVIOUS P/N XXXXXXXX-XXX.



1 THIS PRODUCT MEETS THE SATA SPEC REV 1.0a (5)

2 MATERIAL:

1) HOUSING : HIGH TEMP. THERMOPLASTIC, UL 94V-0
COLOR : BLACK

2) TERMINAL : COPPER ALLOY


3 FINISH :

1) TERMINAL : 3u" Au PLATING (CONTACT POINT) OVER 50u" MIN NICKEL

2) SOLDER TAIL : 50u" MIN TIN OVER 50u" MIN NICKEL

4 TRUE POSITION NOTES APPLY AT TERMINAL TIP

CUSTOMER COPY



AFC

DESCRIPTION	QTY	UNIT	PRICE	TOTAL
S-ATA COMB CABLE RECE. CONNECTOR	1	EA	1.00	1.00

PRODUCT NO.	10043820
-------------	----------

SCALE	2 : 1	SHT <u>1</u> OF <u>1</u>
-------	-------	--------------------------