

THREE PHASE BRIDGE

Power Module


Features

- Low V_F
- Low profile package
- Direct Mounting to heatsink
- Flat-Pin/ Round-Pin versions with PCB solderable terminals
- Low junction-to-case Thermal Resistance
- 3500 V_{RMS} insulation voltage
- UL approval pending

Applications: Power conversion machines

- Welding
- UPS
- SMPS
- Motor Drives
- General Purpose & Heavy Duty Applications

45 A
75 A
100 A




Description

A range of extremely compact three-phase rectifier bridges offering efficient and reliable operation.


The low profile package has been specifically conceived to maximize space saving and optimize the electrical layout of the application specific Power Supplies.

Major Ratings and Characteristics

Parameters	40MT	70MT	100MT	Units
I _O	45	75	100	A
@ T _C	100	80	80	°C
I _{FSM} @ 50Hz	270	380	450	A
@ 60Hz	280	398	470	
I ² t @ 50Hz	365	724	1013	A ² s
@ 60Hz	325	660	920	
I ² √t	3650	7240	10130	A ² √s
V _{RRM}	1400 & 1600			V
T _{STG} range	-40 to 125			°C
T _J range	-40 to 150			



MT...PA



MT...PB

MTP 3-Phase Rectifier Series

Bulletin I27145 rev. B 06/02

International
IOR Rectifier

ELECTRICAL SPECIFICATIONS

Voltage Ratings

Type number	Voltage Code reverse voltage V	V_{RRM} , maximum repetitive peak reverse voltage V	V_{RSM} , maximum non-repetitive peak V	I_{RRM} max. @ $T_J = 150^\circ\text{C}$ mA
40-70-100MT140P	140	1400	1500	5
40-70-100MT160P	160	1600	1700	

Forward Conduction

Parameter		40MT	70MT	100MT	Units	Conditions			
I _O	Maximum DC output current @ Case temperature	45	75	100	A	120° Rect conduction angle			
		100	80	80	°C				
I _{FSM}	Maximum peak, one-cycle forward, non-repetitive on state surge current	270	380	450	A	t = 10ms	No voltage	Initial T _J = T _J max.	
		280	398	470		t = 8.3ms	reapplied		
		225	320	380		t = 10ms	100% V _{RRM}		
		240	335	400		t = 8.3ms	reapplied		
I ² t	Maximum I ² t for fusing	365	724	1013	A ² s	t = 10ms	No voltage		Initial T _J = T _J max.
		325	660	920		t = 8.3ms	reapplied		
		253	512	600		t = 10ms	100% V _{RRM}		
		240	467	665		t = 8.3ms	reapplied		
I ² √t	Maximum I ² √t for fusing	3650	7240	10130	A ² √s	t = 0.1 to 10ms, no voltage reapplied			
V _{F(TO)}	Value of threshold voltage	0.78	0.82	0.75	V	@ T _J max.			
r _t	Slope resistance	14.8	9.5	8.1	mΩ				
V _{FM}	Maximum forward voltage drop	1.45 I _{pk} = 40A	1.45 I _{pk} = 70A	1.51 I _{pk} = 100A	V	T _J = 25°C t _p = 400μs single junction			

Insulation Table

Parameter	40MT	70MT	100MT	Units	Conditions
V_{INS} RMS insulation voltage	3500			V	$T_J = 25^\circ\text{C}$ all terminal shorted f = 50Hz, t = 1s

Thermal and Mechanical Specifications

Parameter	40MT	70MT	100MT	Units	Conditions
T _j Maximum junction operating temperature range	- 40 to 150			°C	
T _{stg} Maximum storage temperature range	-40 to 125			°C	
R _{thJC} Maximum thermal resistance, junction to case	0.27	0.23	0.19	K/W	DC operation per module
	1.6	1.38	1.14		DC operation per junction
	0.38	0.29	0.22		120° Rect conduction angle per module
	2.25	1.76	1.29		120° Rect conduction angle per junction
R _{thCS} Maximum thermal resistance, case to heatsink	0.1			K/W	Per module. Mounting surface smooth, flat and greased. Heatsink compound thermal conductivity = 0.42W/mK
T Mounting torque ± 10% to heatsink	4			Nm	A mounting compound is recommended and the torque should be rechecked after a period of 3 hours to allow for the spread of the compound.
wt Approximate weight	65			g	Lubricated threads.

Clearance and Creepage Distances

Parameter	MT...PA	MT...PB	Units
Clearance (external shortest distance in air between terminals which are not internally short circuited together)	10.9	12.3	mm
Creepage distance (shortest distance along external surface of the insulating material between terminals which are not internally short circuited together)	10.9	12.3	mm

Ordering Information Table

Device Code 10 0 MT 160 P B 1 2 3 4 5					
1	- Current rating code	4 = 45A 7 = 75A 10 = 100A			
2	- Circuit configuration code: 0 = 3-Phase Rectifier Bridge				
3	- Essential part number				
4	- Voltage code: code x 10 = V _{RRM} (See Voltage Ratings table)				
5	- Pinout code:	A = Flat pins B = Round pins			


Bulletin 127145 rev. B 06/02

IOR Rectifier

MT...PA
(Flat pin)

Electrical circuit

Dimensions in millimeters






Fig. 1 - Current Rating Characteristics




Fig. 2 - On-state Voltage Drop Characteristics




Fig. 3 - Maximum Non-Repetitive Surge Current




Fig. 4 - Maximum Non-Repetitive Surge Current




Fig. 5 - Current Rating Nomogram (1 Module Per Heatsink)

MTP 3-Phase Rectifier Series

Bulletin I27145 rev. B 06/02

International
IOR Rectifier




Fig. 6 - Current Rating Characteristics




Fig. 7 - On-state Voltage Drop Characteristics




Fig. 8 - Maximum Non-Repetitive Surge Current




Fig. 9 - Maximum Non-Repetitive Surge Current




Fig. 10 - Current Rating Nomogram (1 Module Per Heatsink)




Fig. 11 - Current Rating Characteristics




Fig. 12 - On-state Voltage Drop Characteristics




Fig. 13 - Maximum Non-Repetitive Surge Current




Fig. 14 - Maximum Non-Repetitive Surge Current




Fig. 15 - Current Rating Nomogram (1 Module Per Heatsink)

MTP 3-Phase Rectifier Series

Bulletin I27145 rev. B 06/02

International
IR Rectifier




Fig. 16 - Thermal Impedance Z_{thJC} Characteristics

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial Level.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7309
06/02



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.