






- High temperature thermo-plastic insulator with standoffs is compatible with standard automatic insertion equipment.
- Soft copper alloy machined pins allows clinching. Chamfered contact entry allows for ease of IC insertion without bent leads.
- Hi-Rel, 4-finger BeCu #30 contact is rated at 3 amps. See page 208 for details.
- Series 110 use MM #1005 pins. See page 135 for details.



Total number of pins				Quantity per tube	Ordering Information	
	A	B	C			
6	0.3	0.3	0.4	67	110-XX-306-41-605000	
8	0.4	0.3	0.4	50	110-XX-308-41-605000	
14	0.7	0.3	0.4	28	110-XX-314-41-605000	
16	0.8	0.3	0.4	25	110-XX-316-41-605000	
18	0.9	0.3	0.4	22	110-XX-318-41-605000	
20	1.0	0.3	0.4	20	110-XX-320-41-605000	
24	1.2	0.3	0.4	16	110-XX-324-41-605000	
22	1.1	0.4	0.5	18	110-XX-422-41-605000	
24	1.2	0.6	0.7	16	110-XX-624-41-605000	
28	1.4	0.6	0.7	14	110-XX-628-41-605000	
32	1.6	0.6	0.7	12	110-XX-632-41-605000	
40	2.0	0.6	0.7	10	110-XX-640-41-605000	
XX= Plating Code See Below					For RoHS compliance select  plating code.	

SPECIFY PLATING CODE XX=			93			43	
Sleeve (Pin)			200μ" Sn/Pb			200μ" Sn	
Contact (Clip)			30μ" Au			30μ" Au	