

8467 8467-0-15-XX-21-XX-04-0 Hex press-fit in 0,91 plated thru hole	6192 6192-0-15-XX-21-XX-04-0 Square press-fit in 0,81 plated thru hole	9553 9553-0-15-XX-X1-XX-04-0 Hex press-fit in 1,04 plated thru hole	5531 5531-0-15-XX-21-XX-10-0 Hex press-fit in 1,04 plated thru hole
7553 7553-0-15-XX-11-XX-10-0 Hex press-fit in 1,04 plated thru hole	9407 9407-0-15-XX-11-XX-10-0 Solder mount in 1,02 min. mounting hole	9462 9462-0-15-XX-21-XX-04-0 Hex press-fit in 1,09 plated thru hole	1147 1147-0-18-XX-21-XX-10-0 Press-fit in 1,09 min. mounting hole
3061 3061-0-19-XX-21-XX-10-0 Wire Termination	0579 0579-0-15-XX-X1-XX-10-0 Press-fit in 1,02 mounting hole	8874 8874-0-15-XX-11-XX-10-0 Bottom entry Surface mount	0613 0613-0-15-XX-21-XX-10-0 Press-fit in 1,19 mounting hole

SPECIFICATIONS

SHELL MATERIAL:
Brass Alloy 360, 1/2 Hard

CONTACT MATERIAL:
Beryllium Copper Alloy 172, HT

PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY

TOLERANCES ON:
LENGTHS: ± 0,13
DIAMETERS: ± 0,05
ANGLES: ± 2°

ORDER CODE: XXXX - X - XX - XX - XX - XX - XX - 0

BASIC PART # _____

SPECIFY SHELL FINISH: _____

01 5,08µm TIN/LEAD OVER NICKEL

80 5,08µm TIN OVER NICKEL

15 0,25µm GOLD OVER NICKEL

SPECIFY CONTACT FINISH: _____

02 2,54µm TIN/LEAD OVER NICKEL

84 2,54µm TIN OVER NICKEL

27 0,76µm GOLD OVER NICKEL



SELECT CONTACT
#11 or #21 CONTACT (DATA ON PAGE 206)