





REV.	DATE	DESCRIPTION
NC	05/05/97	INITIAL RELEASE
A	01/11/07	UPDATE DRAWING FORMAT



RECOMMENDED
CABLE STRIPPING DIM'S



NOTE:

1. CRIMPED FERRULE HEX CRIMP SIZE .429"
2. CRIMPED CONTACT PIN HEX CRIMP SIZE .118"

8					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007" .315 – 1.180 = ± 0.015" 1.180 – 4.724 = ± 0.020"	APPROVALS	DATE	Amphenol Connex				
7						DRAWN	G.R.S.					01/11/07
6						CHECKED			PART DESCRIPTION TNC REVERSE POLARITY CRIMP JACK (FOR BELDEN 9913, 9914)			
5						ISSUED						
4	FERRULE	COPPER	NICKEL	1		SHEET	1 OF 1		PART NO. 122392RP			
3	CONTACT PIN	BRASS	GOLD	1	CAD FILE C:/122/122392RP.DWG							
2	INSULATOR	TEFLON	NATURAL	1				DWG. NO. 122392RP.DWG				
1	BODY	BRASS	NICKEL	1	REV. A							
	DESCRIPTION	MATERIAL	FINISH	QTY					SIZE A			
					SCALE NA							