

					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY.		APPROVALS		DATE		Amphenol Connex						
8					UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007” .315 – 1.180 = ± 0.015” 1.180 – 4.724 = ± 0.020” DO NOT SCALE DRAWING	DRAWN	G.R.S.	10/10/07									
7						CHECKED			PART DESCRIPTION								
6						ISSUED			SMA REVERSE POLARITY CRIMP JACK (FOR RG-58/U, 58C/U CABLE)								
5						SHEET	1 OF 1		PART NO.								
4	FERRULE	COPPER	GOLD	1					132116RP								
3	CONTACT PIN	BRASS	GOLD	1		CAD FILE	C:/132/132116RP.DWG			DWG. NO.	132116RP.DWG	REV.	NC	SIZE	A	SCALE	NA
2	INSULATOR	TEFLON	NATURAL	1													
1	BODY	BRASS	GOLD	1													
DESCRIPTION					MATERIAL	FINISH	QTY										