



Series 810 and 822 Thrifty Model Vertisockets™ with Bifurcated Contacts

FEATURES



- These low-cost Vertisockets™ are recommended for high-volume vertical display mounting applications
- Very useful for connection of board-to-board jumpers and for DIP switches, as well as LED devices

SPECIFICATIONS

- Standard Body Material: black UL 94V-0 4/6 Nylon
- Bifurcated Contacts: Grade-A Spring-tempered Phosphor Bronze per QQ-B-750
- Standard Contact Plating: 50µ [1.27µm] min. matte Tin per ASTM B545-97 over 50µ Nickel per QQ-N-290: TL = 90/10 Tin/Lead per MIL-T-10727 Type 1 over 50µ Nickel per QQN-290
- Contact Current Rating: 1 amp
- Operating Temperature: 221°F [105°C]
- Insertion Force: 110 grams/pin average
- Withdrawal Force: 75 grams/pin average
- Accepts Flat Leads up to 0.014 [0.36] thick and 0.020 [0.51] wide; Round Leads up to 0.020 [0.51] diameter
- Accepts Lead Lengths of 0.075-0.160 [1.91-4.06]


MOUNTING CONSIDERATIONS

- Suggested PCB Hole Size : P/N 14-810-90R = 0.036 ±0.002 [0.91 ±0.05] diameter
: P/N XX-822-90E = 0.044 ±0.002 [1.12 ±0.05] diameter




ORDERING INFORMATION

14-810-90RXXXX



ORDERING INFORMATION

XX-822-90EXXXX



OTHER SIZES AVAILABLE - CONSULT FACTORY

No. of Pins	Dim. "A"	Dim. "B"
8	8.450 [11.43]	0.300 [7.62]
14	14.750 [19.05]	0.600 [15.24]
16	16.850 [21.59]	0.700 [17.78]
18	18.950 [24.13]	0.800 [20.32]
20	20.1050 [26.67]	0.900 [22.86]



Bristol, PA 19007-6810 USA
TEL (215) 781-9956 • FAX (215) 781-9845
WWW.ARIESELEC.COM • INFO@ARIESELEC.COM

