RING TONGUE (R type) Non-insulated



File No.: E42024 LR20812 670021

Actual
Refer to page 135 for actual size of the terminal.

Applicable Wire AWG#(mm²)	Stud size		Part No.		Standard	Dimensions mm (in.)								Tool No.	Qty/box
	American	Metric	JST	JIS		ød2	B	L	F	E	øD	ød1	T		
26 to 22 (0.2 to 0.5)	1-2	2	0.5-2			2.2 (.087)	5.2 (.205)	12.4 (.488)	5.8 (.228)	4.0 (.157)	2.0 (.079)	1.0 (.039)	0.5 (.020)	YHT-2622 YA-1 YA-2 BCT-0514	1,000
	3-4	3	0.5-3			3.2 (.126)	5.2 (.205)	12.4 (.488)	5.8 (.228)						
	5-6	3.5	0.5-3.7			3.7 (.146)	6.6 (.260)	15.0 (.591)	7.7 (.303)						
	8	4	0.5-4			4.3 (.169)	6.6 (.260)	15.0 (.591)	7.7 (.303)						
	10	5	0.5-5			5.3 (.209)	8.0 (.315)	15.0 (.591)	7.0 (.276)						
22 to 16 (0.25 to 1.65)	1-2	2	1.25-2			2.2 (.087)	5.5 (.217)	11.5 (.453)	4.0 (.157)	4.8 (.189)	3.4 (.134)	1.7 (.067)	0.8 (.031)	YHT-2210 YA-1 YA-2 YA-4 BCT-0514	1,000
	3-4	3	1.25-3	R1.25-3		3.2 (.126)	5.5 (.217)	11.5 (.453)	4.0 (.157)						
	3-4	3	1.25-MS3			3.2 (.126)	5.5 (.217)	13.2 (.520)	5.6 (.220)						
	3-4	3	1.25-M3.3			3.2 (.126)	6.6 (.260)	14.4 (.567)	6.3 (.248)						
	3-4	3	1.25-L3			3.2 (.126)	8.0 (.315)	15.8 (.622)	7.0 (.276)						
	5-6	3.5	1.25-3.7			3.7 (.146)	5.5 (.217)	11.5 (.453)	4.0 (.157)						
	5-6	3.5	1.25-M3	R1.25-3.5		3.7 (.146)	6.6 (.260)	14.4 (.567)	6.3 (.248)						
	5-6	3.5	1.25-L3.7			3.7 (.146)	8.0 (.315)	15.8 (.622)	7.0 (.276)						
	8	4	1.25-M4			4.3 (.169)	6.6 (.260)	14.4 (.567)	6.3 (.248)						
	8	4	1.25-4	R1.25-4		4.3 (.169)	8.0 (.315)	15.8 (.622)	7.0 (.276)						
	10	5	1.25-5	R1.25-5		5.3 (.209)	8.0 (.315)	15.8 (.622)	7.0 (.276)						
	10	5	1.25-5NS			5.3 (.209)	9.0 (.354)	20.4 (.803)	11.1 (.437)						
	10	5	1.25-L5			5.3 (.209)	11.6 (.457)	21.7 (.854)	11.1 (.437)						
	1/4	6	1.25-6			6.4 (.252)	11.6 (.457)	21.7 (.854)	11.1 (.437)						
	5/16	8	1.25-8			8.4 (.331)	11.6 (.457)	21.7 (.854)	11.1 (.437)						
	3/8	9	1.25-9			9.8 (.386)	13.6 (.535)	25.5 (1.004)	13.9 (.547)						
	3/8	10	1.25-10			10.5 (.413)	13.6 (.535)	25.5 (1.004)	13.9 (.547)						
	1/2	12	1.25-12			13.0 (.512)	19.0 (.748)	31.0 (1.220)	16.7 (.657)						500
16 to 14 (1.04 to 2.63)	1-2	2	2-S2			2.2 (.087)	6.4 (.252)	12.3 (.484)	4.3 (.169)	4.8 (.189)	4.1 (.161)	2.3 (.091)	0.8 (.031)	YHT-2210 YA-1 YA-2 YA-4 BCT-0514	1,000
	3-4	3	2-MS3			3.2 (.126)	5.5 (.217)	13.2 (.520)	5.6 (.220)						
	3-4	3	2-S3.3			3.2 (.126)	6.4 (.252)	12.3 (.484)	4.3 (.169)						
	3-4	3	2-M3.3			3.2 (.126)	6.6 (.260)	14.4 (.567)	6.3 (.248)						
	3-4	3	2-3			3.2 (.126)	8.5 (.335)	16.8 (.661)	7.8 (.307)						
	5-6	3.5	2-S3			3.7 (.146)	6.4 (.252)	12.3 (.484)	4.3 (.169)						
	5-6	3.5	2-M3	R2-3.5		3.7 (.146)	6.6 (.260)	14.4 (.567)	6.3 (.248)						
	5-6	3.5	2-P3.5			3.7 (.146)	7.0 (.276)	16.0 (.630)	7.7 (.303)						
	5-6	3.5	2-3.7			3.7 (.146)	8.5 (.335)	16.8 (.661)	7.8 (.307)						
	8	4	2-M4			4.3 (.169)	6.6 (.260)	14.4 (.567)	6.3 (.248)						
	8	4	2-P4			4.3 (.169)	7.0 (.276)	16.0 (.630)	7.7 (.303)						
	8	4	2-4	R2-4		4.3 (.169)	8.5 (.335)	16.8 (.661)	7.8 (.307)						
	10	5	2-M5			5.3 (.209)	8.5 (.335)	16.8 (.661)	7.8 (.307)						
	10	5	2-5NS			5.3 (.209)	9.0 (.354)	20.3 (.799)	11.0 (.433)						
	10	5	2-5	R2-5		5.3 (.209)	9.5 (.374)	16.8 (.661)	7.3 (.287)						
	1/4	6	2-6	R2-6		6.4 (.252)	12.0 (.472)	21.8 (.858)	11.0 (.433)						
	5/16	8	2-8	R2-8		8.4 (.331)	12.0 (.472)	21.8 (.858)	11.0 (.433)						
	3/8	9	2-9			9.8 (.386)	13.6 (.535)	25.5 (1.004)	13.9 (.547)						
	3/8	10	2-10			10.5 (.413)	13.6 (.535)	25.5 (1.004)	13.9 (.547)						
	1/2	12	2-12			13.0 (.512)	19.0 (.748)	31.0 (1.220)	16.7 (.675)						500
	1/2	14	2-14			15.0 (.591)	27.0 (1.063)	39.5 (1.555)	21.2 (.835)						
	5/8	16	2-16			17.0 (.669)	27.0 (1.063)	39.5 (1.555)	21.2 (.835)						
	3/4	20	2-20			21.0 (.827)	27.0 (1.063)	39.5 (1.555)	21.2 (.835)						

Note:1) Products with the JIS mark conform to JIS C2805.
2) The part numbers indicated in the above table are for products with a brazed seam.
When ordering products with a nominal size of 0.5 to 5.5 with a butted seam, add the prefix "WS" to the part number (ex.2-4 —>**WS2-4**).
3) Delivery lead times may vary depending on the product. Contact JST for details.



Actual

Refer to page 135 for actual size of the terminal.

Applicable Wire AWG# (mm²)	Stud size		Part No.		Standard	Dimensions mm (in.)								Tool No.	Qty/box
	American	Metric	JST	JIS		ød2	B	L	F	E	øD	ød1	T		
14 to 12 (3.5)	3-4	3	**3.5-R3**		UL	3.2 (.126)	8.0 (.315)	17.8 (.707)	9.0 (.354)	4.8 (.189)	4.8 (.189)	2.7 (.106)	1.0 (.039)	YHT-2210 (Dies mark. 5) BCT-0514	1,000
	8	4	**3.5-R4**		UL	4.3 (.169)	8.0 (.315)	17.8 (.707)	9.0 (.354)						
	8	4	**3.5-4**		UL	4.3 (.169)	10.3 (.406)	18.6 (.732)	8.6 (.339)						
	10	5	**3.5-R5**		UL	5.3 (.209)	8.0 (.315)	17.8 (.707)	9.0 (.354)						
	10	5	**3.5-5**		UL	5.3 (.209)	10.3 (.406)	18.6 (.732)	8.6 (.339)						
	1/4	6	**3.6-6**		UL	6.4 (.252)	10.3 (.406)	18.6 (.732)	8.6 (.339)						
12 to10 (2.63 to 6.64)	3-4	3	**5.5-S3.3**		UL SP	3.2 (.126)	7.2 (.283)	15.7 (.618)	5.9 (.232)	6.2 (.244)	5.6 (.220)	3.4 (.134)	1.0 (.039)	YHT-2210 YA-1 YA-2 YA-4 BCT-0514	
	3-4	3	**5.5-3**		UL SP	3.2 (.126)	9.5 (.374)	19.8 (.780)	8.3 (.327)	6.8 (.268)					
	5-6	3.5	**5.5-S3**		UL SP	3.7 (.146)	7.2 (.283)	15.7 (.618)	5.9 (.232)	6.2 (.244)					1,000
	5-6	3.5	**5.5-3.7**		UL SP	3.7 (.146)	9.5 (.374)	19.8 (.780)	8.3 (.327)	6.8 (.268)					
	8	4	**5.5-S4**		UL SP	4.3 (.169)	7.2 (.283)	15.7 (.618)	5.9 (.232)	6.2 (.244)					
	8	4	**5.5-4NS**		UL	4.3 (.169)	8.0 (.315)	19.1 (.752)	8.3 (.327)	6.8 (.268)					100
	8	4	**5.5-4**	**R5.5-4**	UL SP JIS	4.3 (.169)	9.5 (.374)	19.8 (.780)	8.3 (.327)						1,000
	10	5	**5.5-5NS**		UL	5.3 (.209)	8.0 (.315)	19.1 (.752)	8.3 (.327)						100
	10	5	**5.5-5**	**R5.5-5**	UL SP JIS	5.3 (.209)	9.5 (.374)	19.8 (.780)	8.3 (.327)						1,000
	10	5	**5.5-S5**		UL SP	5.3 (.209)	13.2 (.520)	22.4 (.882)	9.0 (.354)						500
	1/4	6	**5.5-6NS**		UL	6.4 (.252)	9.0 (.354)	24.3 (.957)	13.0 (.512)						100
	1/4	6	**5.5-6**	**R5.5-6**	UL SP JIS	6.4 (.252)	12.0 (.472)	25.8 (1.016)	13.0 (.512)						500
	1/4	6	**5.5-S6**		UL SP	6.4 (.252)	13.2 (.520)	22.4 (.882)	9.0 (.354)						
	1/4	6	**5.5-L6**		UL	6.4 (.252)	15.0 (.591)	28.0 (1.102)	13.7 (.539)						
	5/16	8	**5.5-S8**		UL SP	8.4 (.331)	13.2 (.520)	22.4 (.882)	9.0 (.354)						
	5/16	8	**5.5-8**	**R5.5-8**	UL SP JIS	8.4 (.331)	15.0 (.591)	28.0 (1.102)	13.7 (.539)						
	3/8	9	**5.5-9**		UL SP	9.8 (.386)	15.0 (.591)	28.0 (1.102)	13.7 (.539)						
	3/8	10	**5.5-10**	**R5.5-10**	UL SP JIS	10.5 (.413)	15.0 (.591)	28.0 (1.102)	13.7 (.539)						
	3/8	10	**5.5-L10**		UL SP	10.5 (.413)	19.2 (.756)	32.4 (1.276)	16.0 (.630)						
	7/16	12	**5.5-12**		UL SP	13.0 (.512)	19.2 (.756)	32.4 (1.276)	16.0 (.630)						
	1/2	14	**5.5-14**		UL SP	15.0 (.591)	32.0 (1.260)	48.1 (1.894)	25.3 (.996)						200
	5/8	16	**5.5-16**		UL SP	17.0 (.669)	32.0 (1.260)	48.1 (1.894)	25.3 (.996)						
	11/16	18	**5.5-18**		UL SP	19.0 (.748)	32.0 (1.260)	48.1 (1.894)	25.3 (.996)						
	3/4	20	**5.5-20**		UL SP	21.0 (.827)	32.0 (1.260)	48.1 (1.894)	25.3 (.996)						

Note: 1) Products with the JIS mark JIS conform to JIS C2805.
2) The part numbers indicated in the above table are for products with a brazed seam.
When ordering products with a nominal size of 0.5 to 5.5 with a butted seam, add the prefix "WS" to the part number (ex.5.5-4 —>**WS5.5-4**).
3) Delivery lead times may vary depending on the product. Contact JST for details.

RING TONGUE (R type) Non-insulated

Actual

Refer to page 135 to 136 for actual size of the terminal.



Applicable Wire AWG#(mm²)	Stud size		Part No.		Standard	Dimensions mm (in.)								Tool No.	Qty/box
	American	Metric	JST	JIS		ød2	B	L	F	E	øD	ød1	T		
8 (6.64 to 10.52)	8	4	8-NK4		Ⓤ Ⓢ	4.3 (.169)	9.0 (.354)	16.5 (.650)	5.8 (.228)	6.2 (.244)	7.1 (.280)	4.5 (.177)	1.2 (.047)	YHT-8S YA-4 YPT-60-21 YF-1 YET-60-1 E-4 (Note 2)	500
	8	4	8-4NS		Ⓤ	4.3 (.169)	8.0 (.315)	21.8 (.858)	9.3 (.366)	8.5 (.335)				YHT-8S YA-4, YA-5 YPT-60-21 YPT-150-1 BCT-0514 BCT-860 BCT-8150 YF-1 YET-60-1 E-4 YET-150-1	100
	8	4	8-4		Ⓤ Ⓢ	4.3 (.169)	12.0 (.472)	23.8 (.937)	9.3 (.366)	8.5 (.335)					500
	10	5	8-NK5		Ⓤ	5.3 (.209)	9.0 (.354)	16.5 (.650)	5.8 (.228)	6.2 (.244)				YHT-8S YA-4 YPT-60-21 YF-1 YET-60-1 E-4 (Note 2)	500
	10	5	8-5NS		Ⓤ	5.3 (.209)	9.0 (.354)	22.3 (.878)	9.3 (.366)	8.5 (.335)				YHT-8S YA-4 YA-5 YPT-60-21 YPT-150-1 BCT-0514 BCT-860 BCT-8150 YF-1 YET-60-1 E-4 YET-150-1	100
	10	5	8-5	R8-5	Ⓤ Ⓢ ㋭	5.3 (.209)	12.0 (.472)	23.8 (.937)	9.3 (.366)						500
	10	5	8-L5NS		Ⓤ	5.3 (.209)	9.0 (.354)	26.8 (1.055)	13.8 (.543)						100
	10	5	8-L5		Ⓤ Ⓢ	5.3 (.209)	15.0 (.591)	29.8 (1.173)	13.8 (.543)						500
	1/4	6	8-6NS		Ⓤ	6.4 (.252)	9.6 (.378)	22.6 (.890)	9.3 (.366)						100
	1/4	6	8-6	R8-6	Ⓤ Ⓢ ㋭	6.4 (.252)	12.0 (.472)	23.8 (.937)	9.3 (.366)						500
	1/4	6	8-L6		Ⓤ Ⓢ	6.4 (.252)	15.0 (.591)	29.8 (1.173)	13.8 (.543)						500
	5/16	8	8-8NS		Ⓤ	8.4 (.331)	11.5 (.453)	28.1 (1.106)	13.8 (.543)						100
	5/16	8	8-8	R8-8	Ⓤ Ⓢ ㋭	8.4 (.331)	15.0 (.591)	29.8 (1.173)	13.8 (.543)						500
	3/8	9	8-9		Ⓤ Ⓢ	9.8 (.386)	15.0 (.591)	29.8 (1.173)	13.8 (.543)						500
	3/8	10	8-10	R8-10	Ⓤ Ⓢ ㋭	10.5 (.413)	15.0 (.591)	29.8 (1.173)	13.8 (.543)						500
	3/8	10	8-L10			10.5 (.413)	20.0 (.787)	33.5 (1.319)	15.0 (.591)						500
	7/16	11	8-11		Ⓤ Ⓢ	11.5 (.453)	20.0 (.787)	33.5 (1.319)	15.0 (.591)						500
	7/16	12	8-12		Ⓤ Ⓢ	13.0 (.512)	20.0 (.787)	33.5 (1.319)	15.0 (.591)						500
	1/2	14	8-14		Ⓤ Ⓢ	15.0 (.591)	31.6 (1.244)	50.0 (1.969)	25.7 (1.012)						200
	5/8	16	8-16		Ⓤ Ⓢ	17.0 (.669)	31.6 (1.244)	50.0 (1.969)	25.7 (1.012)						200
	11/16	18	8-18		Ⓤ Ⓢ	19.0 (.748)	31.6 (1.244)	50.0 (1.969)	25.7 (1.012)						200
	3/4	20	8-20		Ⓤ Ⓢ	21.0 (.827)	31.6 (1.244)	50.0 (1.969)	25.7 (1.012)						200

Note:1) Products with the JIS mark ㋭ conform to JIS C2805.
2) Please use the die AD-901S for the pneumatic tool YA-4, and the die 8NK-6 for the hydraulic tools YPT-60-21/YET-60-1.
3) Delivery lead times may vary depending on the product. Contact JST for details.



Actual
Refer to page 136 for actual size of the terminal.

Applicable Wire AWG#(mm²)	Stud size		Part No.		Standard	Dimensions mm (in.)								Tool No.	Qty/box
	American	Metric	JST	JIS		ød2	B	L	F	E	øD	ød1	T		
6 (10.52 to 16.78)	8	4	14-4		Ⓤ	4.3 (.169)	12.0 (.472)	29.8(1.173)	13.3 (.524)	10.5 (.413)	9.0 (.354)	5.8 (.228)	1.5 (.059)	YA-4 YA-5 YPT-60-21 YPT-150-1 BCT-0514 BCT-860 BCT-8150 YF-1 YET-60-1 E-4 YET-150-1	200
	8	4	14-NK4			4.3 (.169)	12.2 (.480)	23.0 (.906)	7.7 (.303)	9.2 (.362)					
	10	5	14-5NS		Ⓤ	5.3 (.209)	9.0 (.354)	28.3(1.114)	13.3 (.524)	10.5 (.413)					100
	10	5	14-5	R14-5	Ⓤ Ⓢ ㊐	5.3 (.209)	12.0 (.472)	29.8(1.173)	13.3 (.524)						200
	10	5	14-NK5		Ⓤ Ⓢ	5.3 (.209)	12.2 (.480)	23.0 (.906)	7.7 (.303)	9.2 (.362)					
	1/4	6	14-6NS		Ⓤ	6.4 (.252)	9.6 (.378)	28.6(1.126)	13.3 (.524)	10.5 (.413)					100
	1/4	6	14-6	R14-6	Ⓤ Ⓢ ㊐	6.4 (.252)	12.0 (.472)	29.8(1.173)	13.3 (.524)						200
	1/4	6	14-L6		Ⓤ	6.4 (.252)	16.0 (.630)	32.8(1.291)	14.5 (.571)						
	5/16	8	14-8NS		Ⓤ	8.4 (.331)	11.5 (.453)	30.8(1.213)	14.5 (.571)						100
	5/16	8	14-S8		Ⓤ	8.4 (.331)	12.0 (.472)	31.0(1.220)	14.5 (.571)						
	5/16	8	14-8	R14-8	Ⓤ Ⓢ ㊐	8.4 (.331)	16.0 (.630)	32.8(1.291)	14.5 (.571)						
	3/8	9	14-9		Ⓤ Ⓢ	9.8 (.386)	16.0 (.630)	32.8(1.291)	14.5 (.571)						
	3/8	10	14-10	R14-10	Ⓤ Ⓢ ㊐	10.5 (.413)	16.0 (.630)	32.8(1.291)	14.5 (.571)						
	3/8	10	14-L10		Ⓤ Ⓢ	10.5 (.413)	22.0 (.866)	41.0(1.614)	19.5 (.739)						
	7/16	11	14-11		Ⓤ Ⓢ	11.5 (.453)	22.0 (.866)	41.0(1.614)	19.5 (.739)						
	7/16	12	14-12	R14-12	Ⓤ Ⓢ ㊐	13.0 (.512)	22.0 (.866)	41.0(1.614)	19.5 (.739)						
	1/2	14	14-14	R14-14	Ⓤ Ⓢ ㊐	15.0 (.591)	30.0(1.181)	49.0(1.929)	23.5 (.925)						
	5/8	16	14-16		Ⓤ Ⓢ	17.0 (.669)	31.6(1.244)	51.5(2.028)	25.2 (.992)						
	11/16	18	14-18		Ⓤ Ⓢ	19.0 (.748)	31.6(1.244)	51.5(2.028)	25.2 (.992)						
	3/4	20	14-20		Ⓤ Ⓢ	21.0 (.827)	31.6(1.244)	51.5(2.028)	25.2 (.992)						
4 (16.78 to 26.66)	10	5	22-5NS		Ⓤ	5.3 (.209)	9.5 (.374)	28.7(1.130)	12.0 (.472)	12.0 (.472)	11.5 (.453)	7.7 (.303)	1.8 (.071)	YA-5 YPT-60-21 YPT-150-1 BCT-860 BCT-8150 YF-1 YET-60-1 E-4 YET-150-1	100
	10	5	22-S5		Ⓤ	5.3 (.209)	12.0 (.472)	30.0(1.181)	12.0 (.472)						
	10	5	22-5		Ⓤ Ⓢ	5.3 (.209)	16.5 (.650)	33.7(1.327)	13.5 (.531)						
	1/4	6	22-S6		Ⓤ Ⓢ	6.4 (.252)	12.0 (.472)	30.0(1.181)	12.0 (.472)						
	1/4	6	22-6	R22-6	Ⓤ Ⓢ ㊐	6.4 (.252)	16.5 (.650)	33.7(1.327)	13.5 (.531)						
	5/16	8	22-S8		Ⓤ Ⓢ	8.4 (.331)	12.0 (.427)	30.0(1.181)	12.0 (.472)						
	5/16	8	22-8	R22-8	Ⓤ Ⓢ ㊐	8.4 (.331)	16.5 (.650)	33.7(1.327)	13.5 (.531)						
	3/8	9	22-9		Ⓤ Ⓢ	9.8 (.386)	17.5 (.689)	36.7(1.445)	16.0 (.630)						
	3/8	10	22-S10		Ⓤ	10.5 (.413)	16.5 (.650)	33.7(1.327)	13.5 (.531)						
	3/8	10	22-10	R22-10	Ⓤ Ⓢ ㊐	10.5 (.413)	17.5 (.689)	36.7(1.445)	16.0 (.630)						
	7/16	11	22-11		Ⓤ Ⓢ	11.5 (.453)	22.0 (.866)	42.5(1.673)	19.5 (.768)						
	7/16	12	22-12	R22-12	Ⓤ Ⓢ ㊐	13.0 (.512)	22.0 (.866)	42.5(1.673)	19.5 (.768)						
	1/2	14	22-14	R22-14	Ⓤ Ⓢ ㊐	15.0 (.591)	30.0(1.181)	51.5(2.028)	24.5 (.965)						
	5/8	16	22-16		Ⓤ Ⓢ	17.0 (.669)	30.0(1.181)	51.5(2.028)	24.5 (.965)						
	11/16	18	22-18		Ⓤ Ⓢ	19.0 (.748)	30.0(1.181)	51.5(2.028)	24.5 (.965)						
	3/4	20	22-20		Ⓤ Ⓢ	21.0 (.827)	30.0(1.181)	51.5(2.028)	24.5 (.965)						

Note:1) Products with the JIS mark ㊐ conform to JIS C2805.
2) Delivery lead times may vary depending on the product. Contact JST for details.

RING TONGUE (R type) Non-insulated

Actual
Refer to page 137 for actual size of the terminal. (except for 38-S9)



Applicable Wire AWG# (mm²)	Stud size		Part No.		Standard	Dimensions mm (in.)								Tool No.	Qty/box
	American	Metric	JST	JIS		ød2	B	L	F	E	øD	ød1	T		
2 (26.66 to 42.42)	10	5	38-S5		Ⓤ Ⓢ	5.3 (.209)	15.5 (.610)	38.0(1.496)	16.0 (.630)	14.0 (.551)	13.3 (.524)	9.4 (.370)	1.8 (.071)	YA-5 YPT-60-21 YPT-150-1 BCT-860 BCT-8150 YF-1 YET-60-1 E-4 YET-150-1	100
	10	5	38-5		Ⓤ Ⓢ	5.3 (.209)	22.0 (.866)	42.7(1.681)	17.7 (.697)						
	1/4	6	38-S6		Ⓤ Ⓢ	6.4 (.252)	15.5 (.610)	38.0(1.496)	16.0 (.630)						
	1/4	6	38-6		Ⓤ Ⓢ	6.4 (.250)	22.0 (.866)	42.7(1.681)	17.7 (.697)						
	5/16	8	38-S8		Ⓤ Ⓢ	8.4 (.331)	15.5 (.610)	38.0(1.496)	16.0 (.630)						
	5/16	8	38-8	R38-8	Ⓤ Ⓢ Ⓙ	8.4 (.331)	22.0 (.866)	42.7(1.681)	17.7 (.697)						
	5/16	8	38-L8		Ⓤ	8.4 (.331)	30.0(1.181)	52.5(2.067)	23.5 (.925)						
	3/8	9	38-9		Ⓤ Ⓢ	9.8 (.386)	22.0 (.866)	42.7(1.681)	17.7 (.697)						
	3/8	9	38-S9		Ⓤ Ⓢ	9.8 (.386)	27.0(1.063)	38.0(1.496)	16.0 (.630)						
	3/8	10	38-S10		Ⓤ Ⓢ	10.5 (.413)	15.5 (.610)	38.0(1.496)	16.0 (.630)						
	3/8	10	38-10	R38-10	Ⓤ Ⓢ Ⓙ	10.5 (.413)	22.0 (.866)	42.7(1.681)	17.7 (.697)						
	3/8	10	38-L10		Ⓤ	10.5 (.413)	30.0(1.181)	52.5(2.067)	23.5 (.925)						
	7/16	11	38-11		Ⓤ Ⓢ	11.5 (.453)	22.0 (.866)	42.7(1.681)	17.7 (.697)						
	7/16	12	38-12	R38-12	Ⓤ Ⓢ Ⓙ	13.0 (.512)	22.0 (.866)	42.7(1.681)	17.7 (.697)						
	1/2	14	38-14	R38-14	Ⓤ Ⓢ Ⓙ	15.0 (.591)	30.0(1.181)	52.5(2.067)	23.5 (.925)						
	5/8	16	38-16		Ⓤ Ⓢ	17.0 (.669)	30.0(1.181)	52.5(2.067)	23.5 (.925)						
	11/16	18	38-18		Ⓤ Ⓢ	19.0 (.748)	30.0(1.181)	52.5(2.067)	23.5 (.925)						
	3/4	20	38-20		Ⓤ Ⓢ	21.0 (.827)	30.0(1.181)	52.5(2.067)	23.5 (.925)						
1/0 (42.42 to 60.57)	–	–	60-S0			–	22.0 (.866)	49.7(1.957)	20.7 (.815)	18.0 (.709)	15.5 (.610)	11.4 (.449)	2.0 (.079)	YA-5 YPT-60-21 YPT-150-1 BCT-860 BCT-8150 YF-1 YET-60-1 E-4 YET-150-1 YET-300-1 YET-300N	50
	1/4	6	60-S6			6.4 (.252)	16.0 (.630)	46.7(1.839)	20.7 (.815)						
	1/4	6	60-6		Ⓤ Ⓢ	6.4 (.252)	22.0 (.866)	49.7(1.957)	20.7 (.815)						
	5/16	8	60-S8		Ⓤ	8.4 (.331)	16.0 (.630)	46.7(1.839)	20.7 (.815)						
	5/16	8	60-8	R60-8	Ⓤ Ⓢ Ⓙ	8.4 (.331)	22.0 (.866)	49.7(1.957)	20.7 (.815)						
	3/8	9	60-9		Ⓤ Ⓢ	9.8 (.386)	22.0 (.866)	49.7(1.957)	20.7 (.815)						
	3/8	10	60-S10		Ⓤ	10.5 (.413)	16.0 (.630)	46.7(1.839)	20.7 (.815)						
	3/8	10	60-10	R60-10	Ⓤ Ⓢ Ⓙ	10.5 (.413)	22.0 (.866)	49.7(1.957)	20.7 (.815)						
	7/16	11	60-11		Ⓤ Ⓢ	11.5 (.453)	22.0 (.866)	49.7(1.957)	20.7 (.815)						
	7/16	12	60-12	R60-12	Ⓤ Ⓢ Ⓙ	13.0 (.512)	22.0 (.866)	49.7(1.957)	20.7 (.815)						
	1/2	14	60-14	R60-14	Ⓤ Ⓢ Ⓙ	15.0 (.591)	32.0(1.260)	57.5(2.264)	23.5 (.925)						
	5/8	16	60-16		Ⓤ Ⓢ	17.0 (.669)	32.0(1.260)	57.5(2.264)	23.5 (.925)						
	11/16	18	60-18		Ⓤ Ⓢ	19.0 (.748)	32.0(1.260)	57.5(2.264)	23.5 (.925)						
	3/4	20	60-20		Ⓤ Ⓢ	21.0 (.827)	32.0(1.260)	57.5(2.264)	23.5 (.925)						
	7/8	22	60-22		Ⓤ Ⓢ	23.0 (.906)	32.0(1.260)	57.5(2.264)	23.5 (.925)						
2/0 (60.57 to 76.28)	–	–	70-S0			–	24.0 (.945)	51.0(2.008)	20.0 (.787)	19.0 (.748)	17.5 (.689)	13.3 (.524)	2.0 (.079)	YPT-150-1 BCT-8150 YF-1 YET-150-1 E-4 YET-300-1 YET-300N	50
	1/4	6	70-6		Ⓤ Ⓢ	6.4 (.252)	24.0 (.945)	51.0(2.008)	20.0 (.787)						
	5/16	8	70-8		Ⓤ Ⓢ	8.4 (.331)	24.0 (.945)	51.0(2.008)	20.0 (.787)						
	3/8	9	70-9		Ⓤ Ⓢ	9.8 (.386)	24.0 (.945)	51.0(2.008)	20.0 (.787)						
	3/8	10	70-10		Ⓤ Ⓢ	10.5 (.413)	24.0 (.945)	51.0(2.008)	20.0 (.787)						
	7/16	11	70-11		Ⓤ Ⓢ	11.5 (.453)	24.0 (.945)	51.0(2.008)	20.0 (.787)						
	7/16	12	70-12		Ⓤ Ⓢ	13.0 (.512)	24.0 (.945)	51.0(2.008)	20.0 (.787)						
	1/2	14	70-14		Ⓤ Ⓢ	15.0 (.591)	32.0(1.260)	61.0(2.402)	26.0(1.024)						
	5/8	16	70-16		Ⓤ Ⓢ	17.0 (.669)	32.0(1.260)	61.0(2.402)	26.0(1.024)						
	11/16	18	70-18		Ⓤ Ⓢ	19.0 (.748)	32.0(1.260)	61.0(2.402)	26.0(1.024)						
	3/4	20	70-20		Ⓤ Ⓢ	21.0 (.827)	32.0(1.260)	61.0(2.402)	26.0(1.024)						
	7/8	22	70-22		Ⓤ Ⓢ	23.0 (.906)	32.0(1.260)	61.0(2.402)	26.0(1.024)						

Note:1) Products with the JIS mark Ⓙ conform to JIS C2805.
2) Part numbers containing "S0" or "L0" do not have stud holes.
3) Delivery lead times may vary depending on the product. Contact JST for details.



Actual

Refer to page 137 to 138 for actual size of the terminal.

Applicable Wire AWG#(mm²)	Stud size		Part No.		Standard	Dimensions mm (in.)								Tool No.	Qty/box
	American	Metric	JST	JIS		ød2	B	L	F	E	øD	ød1	T		
3/0 (76.28 to 96.3)	–	–	80-S0			–	27.0(1.063)	54.2(2.134)	20.7 (.815)	20.0 (.787)	19.5 (.768)	14.5 (.571)	2.3 (.091)	YPT-150-1 BCT-8150 YF-1 YET-150-1 E-4 YET-300-1 YET-300N	25
	–	–	80-L0			–	32.0(1.260)	68.0(2.677)	32.0 (1.260)						
	1/4	6	80-6		Ⓤ Ⓢ	6.4 (.252)	27.0(1.063)	54.2(2.134)	20.7 (.815)						
	5/16	8	80-8		Ⓤ Ⓢ	8.4 (.331)	27.0(1.063)	54.2(2.134)	20.7 (.815)						
	5/16	8	80-L8		Ⓤ Ⓢ	8.4 (.331)	32.0(1.260)	68.0(2.677)	32.0 (1.260)						
	3/8	9	80-9		Ⓤ Ⓢ	9.8 (.386)	27.0(1.063)	54.2(2.134)	20.7 (.815)						
	3/8	10	80-10	R80-10	Ⓤ Ⓢ Ⓙ	10.5 (.413)	27.0(1.063)	54.2(2.134)	20.7 (.815)						
	3/8	10	80-L10		Ⓤ Ⓢ	10.5 (.413)	32.0(1.260)	68.0(2.677)	32.0 (1.260)						
	7/16	11	80-11		Ⓤ Ⓢ	11.5 (.453)	27.0(1.063)	54.2(2.134)	20.7 (.815)						
	7/16	12	80-12	R80-12	Ⓤ Ⓢ Ⓙ	13.0 (.512)	27.0(1.063)	54.2(2.134)	20.7 (.815)						
	7/16	12	80-L12		Ⓤ Ⓢ	13.0 (.512)	32.0(1.260)	68.0(2.677)	32.0 (1.260)						
	1/2	14	80-14	R80-14	Ⓤ Ⓢ Ⓙ	15.0 (.591)	32.0(1.260)	68.0(2.677)	32.0 (1.260)						
	5/8	16	80-16	R80-16	Ⓤ Ⓢ Ⓙ	17.0 (.669)	32.0(1.260)	68.0(2.677)	32.0 (1.260)						
	11/16	18	80-18		Ⓤ Ⓢ	19.0 (.748)	32.0(1.260)	68.0(2.677)	32.0 (1.260)						
	3/4	20	80-20		Ⓤ Ⓢ	21.0 (.827)	32.0(1.260)	68.0(2.677)	32.0 (1.260)						
	7/8	22	80-22		Ⓤ Ⓢ	23.0 (.906)	32.0(1.260)	68.0(2.677)	32.0 (1.260)						
4/0 (96.3 to 117.2)	–	–	100-S0			–	28.5(1.122)	55.6(2.189)	20.4 (.803)	21.0 (.827)	22.3 (.878)	16.4 (.646)	2.6 (.102)	YPT-150-1 BCT-8150 YF-1 YET-150-1 E-4 YET-300-1 YET-300N	25
	–	–	100-L0			–	32.0(1.260)	69.0(2.717)	32.0 (1.260)						
	1/4	6	100-6		Ⓤ Ⓢ	6.4 (.252)	28.5(1.122)	55.6(2.189)	20.4 (.803)						
	5/16	8	100-8		Ⓤ Ⓢ	8.4 (.331)	28.5(1.122)	55.6(2.189)	20.4 (.803)						
	5/16	8	100-L8		Ⓤ Ⓢ	8.4 (.331)	32.0(1.260)	69.0(2.717)	32.0 (1.260)						
	3/8	9	100-9		Ⓤ Ⓢ	9.8 (.386)	28.5(1.122)	55.6(2.189)	20.4 (.803)						
	3/8	10	100-10	R100-10	Ⓤ Ⓢ Ⓙ	10.5 (.413)	28.5(1.122)	55.6(2.189)	20.4 (.803)						
	3/8	10	100-L10		Ⓤ Ⓢ	10.5 (.413)	32.0(1.260)	69.0(2.717)	32.0 (1.260)						
	7/16	11	100-11		Ⓤ Ⓢ	11.5 (.453)	28.5(1.122)	55.6(2.189)	20.4 (.803)						
	7/16	12	100-12	R100-12	Ⓤ Ⓢ Ⓙ	13.0 (.512)	28.5(1.122)	55.6(2.189)	20.4 (.803)						
	7/16	12	100-L12		Ⓤ Ⓢ	13.0 (.512)	32.0(1.260)	69.0(2.717)	32.0 (1.260)						
	1/2	14	100-14	R100-14	Ⓤ Ⓢ Ⓙ	15.0 (.591)	32.0(1.260)	69.0(2.717)	32.0 (1.260)						
	5/8	16	100-16	R100-16	Ⓤ Ⓢ Ⓙ	17.0 (.669)	32.0(1.260)	69.0(2.717)	32.0 (1.260)						
	11/16	18	100-18	R100-18	Ⓤ Ⓢ Ⓙ	19.0 (.748)	32.0(1.260)	69.0(2.717)	32.0 (1.260)						
	3/4	20	100-20	R100-20	Ⓤ Ⓢ Ⓙ	21.0 (.827)	32.0(1.260)	69.0(2.717)	32.0 (1.260)						
	7/8	22	100-22		Ⓤ Ⓢ	23.0 (.906)	32.0(1.260)	69.0(2.717)	32.0 (1.260)						

Note:1) Products with the JIS mark Ⓙ conform to JIS C2805.
2) Part numbers containing "S0" or "L0" do not have stud holes.
3) Delivery lead times may vary depending on the product. Contact JST for details.

RING TONGUE (R type) Non-insulated

Actual

Refer to page 138 for actual size of the terminal.



Applicable Wire AWG# (mm²)	Stud size		Part No.	Standard	Dimensions mm (in.)								Tool No.	Qty/box
	American	Metric			ød2	B	L	F	E	øD	ød1	T		
250/300 (117.2 to 152.05)	–	–	150-S0		–	36.0(1.417)	66.0(2.600)	23.0 (.906)	27.0 (1.063)	26.5 (1.043)	19.5 (.768)	3.2 (.126)	YPT-150-1 BCT-8150 YF-1 YET-150-1 E-4 YET-300-1 YET-300N	20
	–	–	150-L0		–	36.0(1.417)	81.0(3.189)	36.0 (1.417)						
	1/4	6	150-6	Ⓤ Ⓢ	6.4 (.252)	36.0(1.417)	66.0(2.600)	23.0 (.906)						
	5/16	8	150-8	Ⓤ Ⓢ	8.4 (.331)	36.0(1.417)	66.0(2.600)	23.0 (.906)						
	5/16	8	150-L8	Ⓤ Ⓢ	8.4 (.331)	36.0(1.417)	81.0(3.189)	36.0 (1.417)						
	3/8	9	150-9	Ⓤ Ⓢ	9.8 (.386)	36.0(1.417)	66.0(2.600)	23.0 (.906)						
	3/8	10	R150-10	Ⓤ Ⓢ Ⓙ	10.5 (.413)	36.0(1.417)	66.0(2.600)	21.0 (.827)						
	3/8	10	150-10	Ⓤ Ⓢ	10.5 (.413)	36.0(1.417)	66.0(2.600)	23.0 (.906)						
	3/8	10	150-L10	Ⓤ Ⓢ	10.5 (.413)	36.0(1.417)	81.0(3.189)	36.0 (1.417)						
	7/16	11	150-11	Ⓤ Ⓢ	11.5 (.453)	36.0(1.417)	66.0(2.600)	23.0 (.906)						
	7/16	12	R150-12	Ⓤ Ⓢ Ⓙ	13.0 (.512)	36.0(1.417)	66.0(2.600)	21.0 (.827)						
	7/16	12	150-12	Ⓤ Ⓢ	13.0 (.512)	36.0(1.417)	66.0(2.600)	23.0 (.906)						
	7/16	12	150-L12	Ⓤ Ⓢ	13.0 (.512)	36.0(1.417)	81.0(3.189)	36.0 (1.417)						
	1/2	14	R150-14	Ⓤ Ⓢ Ⓙ	15.0 (.591)	36.0(1.417)	68.0(2.677)	23.0 (.906)						
	5/8	16	150-16	Ⓤ Ⓢ	17.0 (.669)	36.0(1.417)	66.0(2.600)	23.0 (.906)						
	5/8	16	R150-16	Ⓤ Ⓢ Ⓙ	17.0 (.669)	36.0(1.417)	68.0(2.677)	23.0 (.906)						
	5/8	16	150-L16	Ⓤ Ⓢ	17.0 (.669)	36.0(1.417)	81.0(3.189)	36.0 (1.417)						
	11/16	18	R150-18	Ⓤ Ⓢ Ⓙ	19.0 (.748)	36.0(1.417)	81.0(3.189)	36.0 (1.417)						
	3/4	20	R150-20	Ⓤ Ⓢ Ⓙ	21.0 (.827)	36.0(1.417)	81.0(3.189)	36.0 (1.417)						
	7/8	22	150-22	Ⓤ Ⓢ	23.0 (.906)	36.0(1.417)	81.0(3.189)	36.0 (1.417)						
	15/16	24	150-24	Ⓤ Ⓢ	25.0 (.984)	36.0(1.417)	81.0(3.189)	36.0 (1.417)						
	1	27	150-27	Ⓤ Ⓢ	28.0 (1.102)	36.0(1.417)	81.0(3.189)	36.0 (1.417)						
350 (152.05 to 192.60)	–	–	180-S0		–	38.5(1.516)	69.0(2.717)	24.5 (.965)	28.5 (1.122)	28.5 (1.122)	21.0 (.827)	3.5 (.138)	YF-1 YET-300-1 E-4 YET-300N	20
	–	–	180-L0		–	38.5(1.516)	86.8(3.417)	39.0 (1.535)						
	5/16	8	180-8	Ⓤ Ⓢ	8.4 (.331)	38.5(1.516)	69.0(2.717)	24.5 (.965)						
	5/16	8	180-L8	Ⓤ Ⓢ	8.4 (.331)	38.5(1.516)	86.8(3.417)	39.0 (1.535)						
	3/8	10	180-10	Ⓤ Ⓢ	10.5 (.413)	38.5(1.516)	69.0(2.717)	24.5 (.965)						
	3/8	10	180-L10	Ⓤ Ⓢ	10.5 (.413)	38.5(1.516)	86.8(3.417)	39.0 (1.535)						
	7/16	11	180-11	Ⓤ Ⓢ	11.5 (.453)	38.5(1.516)	69.0(2.717)	24.5 (.965)						
	7/16	12	180-12	Ⓤ Ⓢ	13.0 (.512)	38.5(1.516)	69.0(2.717)	24.5 (.965)						
	7/16	12	180-L12	Ⓤ Ⓢ	13.0 (.512)	38.5(1.516)	86.8(3.417)	39.0 (1.535)						
	1/2	14	180-14	Ⓤ Ⓢ	15.0 (.591)	38.5(1.516)	69.0(2.717)	24.5 (.965)						
	5/8	16	180-L16	Ⓤ Ⓢ	17.0 (.669)	38.5(1.516)	86.8(3.417)	39.0 (1.535)						
	5/8	16	180-16	Ⓤ Ⓢ	17.0 (.669)	38.5(1.516)	69.0(2.717)	24.5 (.965)						
	11/16	18	180-18	Ⓤ Ⓢ	19.0 (.748)	38.5(1.516)	86.8(3.417)	39.0 (1.535)						
	3/4	20	180-20	Ⓤ Ⓢ	21.0 (.827)	38.5(1.516)	86.8(3.417)	39.0 (1.535)						
	7/8	22	180-22	Ⓤ Ⓢ	23.0 (.906)	38.5(1.516)	86.8(3.417)	39.0 (1.535)						
	15/16	24	180-24	Ⓤ Ⓢ	25.0 (.984)	38.5(1.516)	86.8(3.417)	39.0 (1.535)						
	1	27	180-27	Ⓤ Ⓢ	28.0 (1.102)	38.5(1.516)	86.8(3.417)	39.0 (1.535)						

Note:1) Products with the JIS mark Ⓙ conform to JIS C2805.
2) Part numbers containing "S0" or "L0" do not have stud holes.
3) Delivery lead times may vary depending on the product. Contact JST for details.



Actual
Refer to page 139 to 140 for actual size of the terminal.

Applicable Wire AWG#(mm²)	Stud size		Part No.	Standard	Dimensions mm (in.)								Tool No.	Qty/box
	American	Metric			ød2	B	L	F	E	øD	ød1	T		
400 (192.60 to 242.27)	–	–	200-S0		–	44.0(1.732)	72.0(2.835)	24.5(.965)	31.5 (1.240)	32.7 (1.287)	24.0 (.945)	4.0 (.157)	YF-1 YET-300-1 E-4 YET-300N	10
	–	–	200-L0		–	44.0(1.732)	91.0(3.583)	37.5(1.476)						
	12/16	8	200-8	UL SP	8.4 (.331)	44.0(1.732)	72.0(2.835)	24.5(.965)						
	5/16	8	200-L8	UL SP	8.4 (.331)	44.0(1.732)	91.0(3.583)	37.5(1.476)						
	3/8	9	200-9	UL SP	9.8 (.386)	44.0(1.732)	72.0(2.835)	24.5(.965)						
	3/8	10	200-10	UL SP	10.5 (.413)	44.0(1.732)	72.0(2.835)	24.5(.965)						
	3/8	10	200-L10	UL SP	10.5 (.413)	44.0(1.732)	91.0(3.583)	37.5(1.476)						
	7/16	11	200-11	UL SP	11.5 (.453)	44.0(1.732)	72.0(2.835)	24.5(.965)						
	7/16	12	200-12	UL SP	13.0 (.512)	44.0(1.732)	72.0(2.835)	24.5(.965)						
	7/16	12	R200-12	UL SP JET	13.0 (.512)	44.0(1.732)	78.0(3.071)	24.5(.965)						
	7/16	12	200-L12	UL SP	13.0 (.512)	44.0(1.732)	91.0(3.583)	37.5(1.476)						
	1/2	14	200-14	UL SP	15.0 (.591)	44.0(1.732)	72.0(2.835)	24.5(.965)						
	1/2	14	R200-14	UL SP JET	15.0 (.591)	44.0(1.732)	78.0(3.071)	24.5(.965)						
	5/8	16	200-16	UL SP	17.0 (.669)	44.0(1.732)	72.0(2.835)	24.5(.965)						
	5/8	16	R200-16	UL SP JET	17.0 (.669)	44.0(1.732)	78.0(3.071)	24.5(.965)						
	5/8	16	200-L16	UL SP	17.0 (.669)	44.0(1.732)	91.0(3.583)	37.5(1.476)						
	11/16	18	R200-18	UL SP JET	19.0 (.748)	44.0(1.732)	91.0(3.583)	37.5(1.476)						
	3/4	20	R200-20	UL SP JET	21.0 (.827)	44.0(1.732)	91.0(3.583)	37.5(1.476)						
	7/8	22	R200-22	UL SP JET	23.0 (.906)	44.0(1.732)	91.0(3.583)	37.5(1.476)						
	15/16	24	R200-24	UL SP JET	25.0 (.984)	44.0(1.732)	91.0(3.583)	37.5(1.476)						
	1	27	R200-27	UL SP JET	28.0 (1.102)	44.0(1.732)	91.0(3.583)	37.5(1.476)						
600/650 (242.27 to 325)	–	–	325-S0		–	50.5(1.988)	88.0(3.465)	33.5(1.319)	35.5 (1.398)	37.6 (1.480)	28.0 (1.102)	4.5 (.177)	YF-1 YET-300-1 E-4 YET-300N	5
	–	–	325-L0		–	50.5(1.988)	105.7(4.161)	45.0(1.772)						
	12/16	8	325-8	UL SP	8.4 (.331)	50.5(1.988)	88.0(3.465)	33.5(1.319)						
	5/16	8	325-L8	UL SP	8.4 (.331)	50.5(1.988)	105.7(4.161)	45.0(1.772)						
	3/8	10	325-10	UL SP	10.5 (.413)	50.5(1.988)	88.0(3.465)	33.5(1.319)						
	3/8	10	325-L10	UL SP	10.5 (.413)	50.5(1.988)	105.7(4.161)	45.0(1.772)						
	7/16	11	325-11	UL SP	11.5 (.453)	50.5(1.988)	88.0(3.465)	33.5(1.319)						
	7/16	12	325-12	UL SP	13.0 (.512)	50.5(1.988)	88.0(3.465)	33.5(1.319)						
	7/16	12	325-L12	UL SP	13.0 (.512)	50.5(1.988)	105.7(4.161)	45.0(1.772)						
	1/2	14	325-14	UL SP	15.0 (.591)	50.5(1.988)	88.0(3.465)	33.5(1.319)						
	5/8	16	325-16	UL SP	17.0 (.669)	50.5(1.988)	88.0(3.465)	33.5(1.319)						
	5/8	16	R325-16	UL SP JET	17.0 (.669)	50.5(1.988)	94.2(3.709)	33.5(1.319)						
	5/8	16	325-L16	UL SP	17.0 (.669)	50.5(1.988)	105.7(4.161)	45.0(1.772)						
	11/16	18	325-M18	UL SP	19.0 (.748)	50.5(1.988)	94.2(3.709)	33.5(1.319)						
	11/16	18	R325-18	UL SP JET	19.0 (.748)	50.5(1.988)	105.7(4.161)	45.0(1.772)						
	3/4	20	R325-20	UL SP JET	21.0 (.827)	50.5(1.988)	105.7(4.161)	45.0(1.772)						
	7/8	22	R325-22	UL SP JET	23.0 (.906)	50.5(1.988)	105.7(4.161)	45.0(1.772)						
	15/16	24	R325-24	UL SP JET	25.0 (.984)	50.5(1.988)	105.7(4.161)	45.0(1.772)						
	1	27	R325-27	UL SP JET	28.0 (1.102)	50.5(1.988)	105.7(4.161)	45.0(1.772)						

Note:1) Products with the JIS mark JET conform to JIS C2805.
2) Part numbers containing "S0" or "L0" do not have stud holes.
3) Delivery lead times may vary depending on the product. Contact JST for details.