

SACC-M12MS-5CON-PG 7

Order No.: 1662256



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1662256>

Sensor/actuator connector, male, straight, 5-pos., M12, A-coded, screw connection, plastic knurl, cable screw connection Pg7

Commercial data

EAN	4017918100445
Pack	1 Pcs.
Customs tariff	85366990
Weight/Piece	0.01815 KG
Catalog page information	Page 34 (PC-2007)

Product notes

WEEE/RoHS-compliant since:
03/23/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Nominal current I_N	4 A
Nominal voltage U_N	60 V
Number of positions	5
Volume resistance	$\leq 8 \text{ m}\Omega$

Insulation resistance	$\geq 100 \text{ M}\Omega$
Ambient temperature (operation)	-40 °C ... 85 °C (Connector)
Pg screw connection	Pg7

General characteristics

Coding	A - standard
Inflammability class acc. to UL 94	V0
Surge voltage category	II
Pollution degree	3
Degree of protection	IP67
Contact material	CuZn
Contact surface material	CuSnZn
Material, knurls	Plastic
Type of connection	Screw connection
Conductor cross section stranded min.	0.25 mm ²
Conductor cross section stranded max.	0.75 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	18
Min. diameter	4 mm
Max. diameter	6 mm

Certificates / Approvals

Approval logo




requested approbations


Certification	GOST
---------------	------

Drawings


Dimensioned drawing




Schematic diagram



Male/Female M12



Cable connection side M12 (screw connection)



Pin assignment, connector M 12 (male side)

Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2008 Phoenix Contact
Technical modifications reserved;