

NorComp Quick Reference Guide to Backshells

Series	Material			Cable Entry					Hardware			Strain Relief type	Standard	High Density
	70db Die Cast	60db Metalized	Plastic	180 Degree	45 Degree	40 Degree	90 Degree	3 way	4-40 std. screws	4-40 thumb-screws	Other screw types available		Connector Size	Connector Size
970	x	x	x	x						x	x	Compression	9,15,25,37	15,26,44,62
971	x	x	x		x					x	x	Compression	9,15,25,37	15,26,44,62
972			x	x						x		Mechanical	9,15,25,37	15,26,44,62
973		x	x	x						x		Mechanical	9,15,25,37	15,26,44,62
974		x	x			x				x		Mechanical	9,15,25,37	15,26,44,62
975		x	x					x		x		Mechanical	9,15,25,37	15,26,44,62
976		x	x	x					x			Compression	9,15,25,37	15,26,44,62
977		x	x	x					x	x		Mechanical	9,15,25,37,50	15,26,44,62,78
978		x	x	x					x	x		Compression	9,15,25,37,50	15,26,44,62,78
979	x	x	x	x					x	x	x	Compression	9,15,25,37,50	15,26,44,62,78
981	x						x		x	x		Compression	9,15,25	15,26,44
982		x	x	x			x		x			Mechanical	9,15,25,37,50	15,26,44,62,78
983		x	x	x					x	x		Mechanical	9,15,25,37,50	15,26,44,62,78
993		x	x		x					x		Mechanical	9,25	15,44
994	x			x					x			Mechanical	9,15,25	15,26,44