

- Series 180, 182, and 183 DIL Headers are equipped with solder cups for wiring applications.
- Series 180 terminations are pluggable 0,51 dia. solder tails MM #8000, See page 174 for details. Series 182 and 183 terminations are two or three level wraposts MM #8301. See page 184 for details.
- Insulators are high temperature thermoplastic.

Total number of pins				Quantity per tube	<div style="border: 2px solid black; border-radius: 50%; padding: 5px; display: inline-block;"> XX=Plating Code See Below </div> <div style="border: 1px solid green; padding: 2px; display: inline-block; margin-left: 10px;"> Ordering Information <i>For RoHS compliance select ◇ plating code.</i> </div> <div style="border: 1px solid green; padding: 5px; display: inline-block; margin-left: 10px; text-align: center;"> RoHS 2002/95/EC </div>		
	A	B	C		Solder Tail	2 Level Wrapost L = 9,4	3 Level Wrapost L = 12,95
	10	12,6	5,08		7,6	41	180-XX-210-00-001000
4	5,0	7,62	10,1	102	180-XX-304-00-001000	182-XX-304-00-001000	183-XX-304-00-001000
6	7,6	7,62	10,1	67	180-XX-306-00-001000	182-XX-306-00-001000	183-XX-306-00-001000
8	10,1	7,62	10,1	50	180-XX-308-00-001000	182-XX-308-00-001000	183-XX-308-00-001000
10	12,6	7,62	10,1	40	180-XX-310-00-001000	182-XX-310-00-001000	183-XX-310-00-001000
14	17,7	7,62	10,1	28	180-XX-314-00-001000	182-XX-314-00-001000	183-XX-314-00-001000
16	20,3	7,62	10,1	25	180-XX-316-00-001000	182-XX-316-00-001000	183-XX-316-00-001000
18	22,8	7,62	10,1	22	180-XX-318-00-001000	182-XX-318-00-001000	183-XX-318-00-001000
20	25,3	7,62	10,1	20	180-XX-320-00-001000	182-XX-320-00-001000	183-XX-320-00-001000
22	27,8	7,62	10,1	18	180-XX-322-00-001000	182-XX-322-00-001000	183-XX-322-00-001000
24	30,4	7,62	10,1	16	180-XX-324-00-001000	182-XX-324-00-001000	183-XX-324-00-001000
28	35,5	7,62	10,1	14	180-XX-328-00-001000	182-XX-328-00-001000	183-XX-328-00-001000
20	25,4	10,16	12,7	20	180-XX-420-00-001000	182-XX-420-00-001000	183-XX-420-00-001000
22	27,8	10,16	12,7	18	180-XX-422-00-001000	182-XX-422-00-001000	183-XX-422-00-001000
24	30,4	10,16	12,7	16	180-XX-424-00-001000	182-XX-424-00-001000	183-XX-424-00-001000
28	35,5	10,16	12,7	14	180-XX-428-00-001000	182-XX-428-00-001000	183-XX-428-00-001000
32	40,6	10,16	12,7	12	180-XX-432-00-001000	182-XX-432-00-001000	183-XX-432-00-001000
24	30,5	15,24	17,7	16	180-XX-624-00-001000	182-XX-624-00-001000	183-XX-624-00-001000
28	35,5	15,24	17,7	14	180-XX-628-00-001000	182-XX-628-00-001000	183-XX-628-00-001000
32	40,6	15,24	17,7	12	180-XX-632-00-001000	182-XX-632-00-001000	183-XX-632-00-001000
36	45,7	15,24	17,7	11	180-XX-636-00-001000	182-XX-636-00-001000	183-XX-636-00-001000
40	50,8	15,24	17,7	10	180-XX-640-00-001000	182-XX-640-00-001000	183-XX-640-00-001000
42	53,3	15,24	17,7	9	180-XX-642-00-001000	182-XX-642-00-001000	183-XX-642-00-001000
48	60,9	15,24	17,7	8	180-XX-648-00-001000	182-XX-648-00-001000	183-XX-648-00-001000
50	63,5	15,24	17,7	8	180-XX-650-00-001000	182-XX-650-00-001000	183-XX-650-00-001000
52	66,0	15,24	17,7	7	180-XX-652-00-001000	182-XX-652-00-001000	183-XX-652-00-001000
50	63,5	22,86	25,3	8	180-XX-950-00-001000	182-XX-950-00-001000	183-XX-950-00-001000
52	66,0	22,86	25,3	7	180-XX-952-00-001000	182-XX-952-00-001000	183-XX-952-00-001000
64	81,2	22,86	25,3	6	180-XX-964-00-001000	182-XX-964-00-001000	183-XX-964-00-001000
SPECIFY PLATING CODE XX=					10◇		
Pin Plating					0,25µm Au		