

WSI 25CC
WSI 25 10x38

WSI 25CC/LED
WSI 25 10x38/LED

NEW



Weidmüller offers DIN rail mounted terminal blocks for the popular 10.3 mm x 38 mm midget fuses. Compact and touch safe, these terminals meet CSA, UL and IEC requirements.

Features:

- CSA certified for 600 V, 30 A max.
- UL rated 600 V, 30 A max.
- 1, 2, 3 pole and 1 pole indicator versions available
- Mounting on 35 mm DIN rail
- Only 17.8 mm wide per pole
- Lever mechanism for quick and safe fuse replacement
- Vented housing to reduce internal heating and extend fuse life
- 3 W power dissipation maximum
- Short Circuit Current Rating (SCCR) of 200 kA simplifies compliance to KL 508 A Standard

USA

W-Interconnections, Inc.
821 Southlake Boulevard,
Richmond, VA 23236
Phone +1 804 7942877
Fax +1 804 3792593
info@weidmuller.com
www.weidmuller.com

Canada

W Interconnections Canada Inc.
10 Spy Court, Markham,
Ontario L3 R5 H6
Phone +1 905 475-1507
Fax +1 905 475-5855
info1@weidmuller.ca
www.weidmuller.ca

Mexico

W Interconnections, S.A. de C.V.
Blvd. Hermanos Serdán No. 698
Col. San Rafael Oriente
Puebla, Pue. C.P. 72029
Phone +52 222 2686266 to 68 ext.101
Fax +52 222 2686219
clientes@weidmuller.com.mx
www.weidmuller.com.mx

WSI 25 10x38

25 mm²

For fuses 10x38



width x length x height with TS 35 x 7.5 mm
max. current / max. cond. cross-section A/mm²
max. clamping range mm²

17.8 x 58 x 81
32 / 25
1.5 ... 25

Technical data

Rated data	
Rated voltage, adjacent terminal	V
Rated current	A
Rated cross-section	mm ²
Rated isolation voltage	V
Power loss 1 pole / 2 pole / 3 pole	
UL94 Flammability class	
Approvals	
Clamped conductors (H05V/H07V)	
Solid / stranded	mm ²
Flexible / Flexible with wire end ferrule	mm ²
Tightening torque range (clamping screw)	Nm
Stripping length	mm

IEC 60947-7-3			
IEC	UL	CSA	EN 60079-7
690	600	600	
32	30	30	
25	AWG 18 ... 4	AWG 18 ... 4	
800			
0.3 / 0.6 / 0.9			
V-0			
Rated connection			
1.5 ... 16 / 1.5 ... 16			
0.75 ... 25 / 0.75 ... 25			
2.0 ... 2.4			
11			

WSI 25 CC

25 mm²

For fuses CC



17.8 x 58 x 81
32 / 25
1.5 ... 25

IEC 60947-7-3			
IEC	UL	CSA	EN 60079-7
690	600	600	
32	30	30	
25	AWG 18 ... 4	AWG 18 ... 4	
800			
0.3 / 0.6 / 0.9			
V-0			
Rated connection			
1.5 ... 16 / 1.5 ... 16			
0.75 ... 25 / 0.75 ... 25			
2.0 ... 2.4			
11			

Note

Ordering data

Version
1 pole without LED
2 pole without LED
3 pole without LED
1 pole with LED

Type	Qty.	Order No.
WSI 25/1 10x38	12	1966020000
WSI 25/2 10x38	6	1966090000
WSI 25/3 10x38	4	1966080000
WSI 25/1 10x38/LED	12	1966060000

Note

Type	Qty.	Order No.
WSI 25/1 CC	12	1966050000
WSI 25/2 CC	6	1966040000
WSI 25/3 CC	4	1966030000
WSI 25/1 CC/LED	12	1966070000

Accessories

Type
Marking Systems

Type	Qty.	Order No.
Tag ESG 6/15 K MC	200	1880100000

Type	Qty.	Order No.
Tag ESG 6/15 K MC	200	1880100000

Dimensional drawing

