

Product SKU: C2536.41.10

Product Description: Communication & Control Cable, Multi-Conductor, Foil Shield, UL 2106, NEC Type CL2 and CM (UL) c(UL) CMH, No. of Conductors: 2, Gauge Size (AWG): 16, Conductor/Strands: 19/.0117, Jacket: Gray PVC, Temperature Range: -20Â°C to +75Â°C - Gray - 1000 Ft. Reel

Product Category: Electronics - Communication & Control Cable, Multi-Conductor - Foil Shield, Various Approvals - UL STYLE 2106, CSA, 600V - Gray



Product Construction:

- | | |
|-------------|---|
| Conductor: | <ul style="list-style-type: none">• 24 thru 12 AWG fully-annealed, solid or stranded tinned copper per ASTM B-33 |
| Insulation: | <ul style="list-style-type: none">• Premium grade color-coded polyethylene |
| Shield: | <ul style="list-style-type: none">• 100% Flexfoil® aluminum/polyester with 25% overlap, foil facing out• Stranded tinned copper drain wire |
| Jacket: | <ul style="list-style-type: none">• PVC, gray• Temperature Range: -20Â°C to +75Â°C |

Product Specification:

- | | |
|------------------------------------|--|
| No. of Conductors: | <ul style="list-style-type: none">• 2 |
| Conductor Size (AWG): | <ul style="list-style-type: none">• 16 |
| Conductor/Strands: | <ul style="list-style-type: none">• 19/.0117 |
| Jacket Color: | <ul style="list-style-type: none">• Gray |
| Nominal Insulation Thickness (in): | <ul style="list-style-type: none">• 0.031 |
| Nominal Insulation Thickness (mm): | <ul style="list-style-type: none">• 0.79 |
| Nominal Jacket Thickness (in): | <ul style="list-style-type: none">• 0.032 |
| Nominal Jacket Thickness (mm): | <ul style="list-style-type: none">• 0.81 |

Nominal Outside Diameter (in):	<ul style="list-style-type: none"> 0.308
Nominal Outside Diameter (mm):	<ul style="list-style-type: none"> 7.8
Nominal Capacitance (pF/ft A):	<ul style="list-style-type: none"> 27.0
Nominal Capacitance (pF/ft B):	<ul style="list-style-type: none"> 49.0
Standard Packaging:	<ul style="list-style-type: none"> 1000' Non-returnable Wood Reels
Standard Package Quantity:	<ul style="list-style-type: none"> 1
UPC #:	<ul style="list-style-type: none"> 079407714568
Footnote:	<ul style="list-style-type: none"> CM (UL) c(UL) Nominal Cap. A: Capacitance between conductors Nominal Cap. B: Capacitance between one conductor and other conductors connected to shield
Put-up:	<ul style="list-style-type: none"> 1000
SCC-14:	<ul style="list-style-type: none"> 50079407714566
Cube:	<ul style="list-style-type: none"> 2420
Weight Per Unit of Measure:	<ul style="list-style-type: none"> .05
ColorOption:	<ul style="list-style-type: none"> Gray

Product Information:	
Applications:	<ul style="list-style-type: none"> Broadcast and sound systems Computers Industrial equipment control Recording studios and sound stages Suggested voltage rating: 600 Volts
Compliances:	<ul style="list-style-type: none"> UL Style 2106 (UL: 60°C, 600V) CSA, 600V

Features:

- 25% shield overlap provides excellent shielding efficiency
- Excellent electrical properties
- Good flexibility
- Superior shielding effectiveness

Packaging:

- 1000' (305 m) Spools or Reels
- 500' (152 m) Spools or Reels
- Other put-ups available- consult Customer Service

Reference Charts

[Color Code Chart](#)

Technical Specifications

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)



**CAROL
BRAND**