

ProductSKU: C1357.18.90
ProductDescription: SpeakerWire,ULListed(Wires,Misc.)120Vmax.,No.ofConductors:2,GaugeSize(AWG):18,Conductor/Strands:16/30,Jacket:PremiumGradePVC-Clear-500Ft.Spool
ProductCategory: Electronics-RetailProductsandMerchandising-SpeakerWire-18AWGCONDUCTORS

**ProductConstruction:**

- | | |
|-------------|--|
| Conductor: | • 24through14AWGfully-annealed1bare,1tinnedstrandedcopperconductorperASTMB-174 |
| Insulation: | • Premiumgrade,clearPVC
• TemperatureRange:-20°Cto+60°C |

ProductSpecification:

- | | |
|-------------------------------|----------------------------------|
| No.ofConductors: | • 2 |
| ConductorSize(AWG): | • 18 |
| Conductor/Strands: | • 16/30 |
| JacketColor: | • Clear |
| StandardPackaging: | • 500'
• Spool
• 500'Spool |
| StandardPackageQuantity: | • 2 |
| ApproximateCartonWeight(lbs): | • 16.0 |
| CartonDimensions(LxWxH): | • 6.6x6.6x6.6 |
| CartonCube: | • 0.166 |
| UPC#: | • 079407900688 |
| Put-up: | • 500 |
| SCC-14: | • 50079407900688 |
| Cube: | • 530.196 |
| WeightPerUnitofMeasure: | • .02 |

ProductInformation:

- | | |
|---------------|--|
| Applications: | • Radios
• Stereosystems |
| Compliances: | • ULWiresMisc.(UL:120V)(notforin-wallinstallation) |

Technical Specifications

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)



**CAROL
BRAND**