

CENTERLINE OF PIN IN AREA SHOWN
NOT TO VARY FROM CENTERLINE
OF PIN AT DATUM -E- BY
MORE THAN (0.20)/.008 IN ANY DIRECTION

DIM. W
TYP. REF.

DIM. X
TYP. (± 1.02)
 $\pm .040$

DIM. Y
TYP. (± 5.1)
 $\pm .020$

DIM. Z
TYP. REF.

CENTERLINE OF PIN IN AREA SHOWN
NOT TO VARY FROM CENTERLINE
OF PIN AT DATUM -D- BY
MORE THAN (0.13)/.005 IN ANY DIRECTION

A-4094-N * * *

NO. OF CKTS.

VERSION
LETTER CHANGES WHEN PIN
NO. OR PRESS DIM. CHANGES.

PLATING CODE
SEE NOTE 2

SECONDARY OPERATIONS	
CODE	PACKAGE
BLANK	BULK PER PK-4094-001
A	PK-40873-0020

CKTS. NO. OF	DIM. B	DIM. A
2	.100 $\pm$.002 (2.54 $\pm$.05)	.190 $\pm$.008 (4.83 $\pm$.20)
3	.200 $\pm$.005 (5.08 $\pm$.13)	.290 $\pm$.008 (7.37 $\pm$.20)
4	.300 $\pm$.005 (7.62 $\pm$.13)	.390 $\pm$.008 (9.91 $\pm$.20)
5	.400 $\pm$.005 (10.16 $\pm$.13)	.490 $\pm$.008 (12.45 $\pm$.20)
6	.500 $\pm$.006 (12.70 $\pm$.15)	.590 $\pm$.009 (14.99 $\pm$.23)
7	.600 $\pm$.006 (15.24 $\pm$.15)	.690 $\pm$.009 (17.53 $\pm$.23)
8	.700 $\pm$.006 (17.78 $\pm$.15)	.790 $\pm$.009 (20.07 $\pm$.23)
9	.800 $\pm$.007 (20.32 $\pm$.18)	.890 $\pm$.010 (22.61 $\pm$.25)
10	.900 $\pm$.007 (22.86 $\pm$.18)	.990 $\pm$.010 (25.15 $\pm$.25)
11	1.000 $\pm$.007 (25.40 $\pm$.18)	1.090 $\pm$.010 (27.69 $\pm$.25)
12	1.100 $\pm$.008 (27.94 $\pm$.20)	1.190 $\pm$.011 (30.23 $\pm$.28)
13	1.200 $\pm$.008 (30.48 $\pm$.20)	1.290 $\pm$.011 (32.77 $\pm$.28)
14	1.300 $\pm$.008 (33.02 $\pm$.20)	1.390 $\pm$.011 (35.31 $\pm$.28)
15	1.400 $\pm$.008 (35.56 $\pm$.20)	1.490 $\pm$.011 (37.85 $\pm$.28)
16	1.500 $\pm$.008 (38.10 $\pm$.20)	1.590 $\pm$.011 (40.39 $\pm$.28)
17	1.600 $\pm$.009 (40.64 $\pm$.23)	1.690 $\pm$.012 (42.93 $\pm$.30)
18	1.700 $\pm$.009 (43.18 $\pm$.23)	1.790 $\pm$.012 (45.47 $\pm$.30)
19	1.800 $\pm$.009 (45.72 $\pm$.23)	1.890 $\pm$.012 (48.01 $\pm$.30)
20	1.900 $\pm$.009 (48.26 $\pm$.23)	1.990 $\pm$.012 (50.55 $\pm$.30)
21	2.000 $\pm$.010 (50.80 $\pm$.25)	2.090 $\pm$.013 (53.09 $\pm$.33)
22	2.100 $\pm$.010 (53.34 $\pm$.25)	2.190 $\pm$.013 (55.63 $\pm$.33)
23	2.200 $\pm$.010 (55.88 $\pm$.25)	2.290 $\pm$.013 (58.17 $\pm$.33)
24	2.300 $\pm$.010 (58.42 $\pm$.25)	2.390 $\pm$.013 (60.71 $\pm$.33)
25	2.400 $\pm$.011 (60.96 $\pm$.28)	2.490 $\pm$.014 (63.25 $\pm$.36)
26	2.500 $\pm$.011 (63.50 $\pm$.28)	2.590 $\pm$.014 (65.79 $\pm$.36)
27	2.600 $\pm$.011 (66.04 $\pm$.28)	2.690 $\pm$.014 (68.33 $\pm$.36)
28	2.700 $\pm$.011 (68.58 $\pm$.28)	2.790 $\pm$.014 (70.87 $\pm$.36)

14	AD1
13	AD1
12	AD1
11	AD1
10	AD1
9	AD1
8	AD1
7	AD1
6	AD1
5	AD1
4	AD1
3	AD1
2	AD1
1	AD3
SHEET	REV.

ADD 1:18 DIMENSION
EC NO: UCP2009-0323
DRAWING: 08/22
CHKD: HKP
APPR: FSL/TH
REV

DESCRIPTION
2008/08/26
2008/08/27

QUALITY SYMBOLS
▽=0
▽=0

GENERAL TOLERANCES
(UNLESS SPECIFIED)
mm INCH
4 PLACES $\pm$ --- $\pm$ ---
3 PLACES $\pm$ --- $\pm$.005
2 PLACES $\pm$.013 $\pm$.01
1 PLACE $\pm$ 0.25 $\pm$ ---
ANGULAR $\pm$ 1/2°
DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

DIMENSION STYLE
MM/IN
DRAWN BY DATE
KSS 1984/09/10
CHECKED BY DATE
NP 1984/09/10
APPROVED BY DATE
KJA 1984/09/10
MATERIAL NO.
SEE CHART
SIZE C

SCALE

DESIGN UNITS
INCH
THIRD ANGLE
PROJECTION
TITLE
WAFER ASSY FLAT MINI KK
(4030 WITH BENT PINS)
4094 SERIES DRAWING
MOLEX INCORPORATED
DOCUMENT NO.
SDA-4094
SHEET NO.
1 OF 14
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX
INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

(2.54 $\pm$.05)
.100 $\pm$.002
TYP. BETWEEN ANY
TWO CONSECUTIVE
CKTS.
AT DATUM -D-

(3.30 $\pm$.38)
.130 $\pm$.015
TYP.

(2.54 $\pm$.05)
.100 $\pm$.002 TYP.
NON-ACCUM.
(1.02 $\pm$.05)
.040 $\pm$.002 DIA
HOLE TYP.

PCB LAYOUT: COMPONENT SIDE
TYPICAL PCB THICKNESS: (1.57)/.062

NOTES:

- MATERIAL: NYLON, UL 94V-0, COLOR: WHITE
- FINISH:
 - (102) OVERALL TIN: 0.00508/.000200 MIN. OVER COPPER UNDERPLATE: 0.00254/.000100 MIN.
 - (103) OVERALL TIN: 0.00508/.000200 MIN. OVER COPPER UNDERPLATE: 0.00127/.000050 MIN.
 - (501) OVERALL GOLD: 0.00051/.000020 MIN. OVER NICKEL UNDERPLATE: 0.00076/.000030 MIN.
 - (503) OVERALL GOLD: 0.00076/.000030 MIN. OVER NICKEL UNDERPLATE: 0.00127/.000050 MIN.
 - (508) OVERALL GOLD: 0.00076/.000030 MIN. OVER NICKEL UNDERPLATE: 0.00076/.000030 MIN.
 - (516) OVERALL GOLD: 0.00025/.000010 MIN. OVER NICKEL UNDERPLATE: 0.00076/.000030 MIN.
- PARTS CONFORM TO PRODUCT SPECIFICATION PS-10-07.
- PACKAGING INFORMATION: SEE LEGEND.
- PINS MUST CONFORM TO SOLDERABILITY SPECIFICATION SMES-152.
- PIN PUSHOUT FORCE: 2 LBS. MIN.
- PARTS ARE STACKABLE END TO END AND SIDE TO SIDE ON (2.54)/.100 CENTERS.
- THE PRIMARY SHIPPING CARTON WILL BE LABELED, "COMPLIANT TO ROHS DIRECTIVE 2002/95/EC AND ELV ANNEX II OF DIRECTIVE 2000/53/EC." CARTONS WITHOUT THIS LABEL MAY CONTAIN PRODUCT WITH TIN-LEAD PLATING.
- PARTS CONFORM TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.

	13	12	11	10	9	8	7	6	5	4	3	2	1						
J	ENG. NO.	PIN NO.	DIM. L	DIM. X	DIM. Z	DIM. Y	DIM. W	DIM. T		ENG. NO.	PIN NO.	DIM. L	DIM. X	DIM. Z	DIM. Y	DIM. W	DIM. T	J	
I	A-4094-NA102	2766-3(102)	(17.45) .687	(9.30) .366	(3.15) .124	(6.30) .248	90°			A-4094-NCM501	2766-1(501)	(14.22) .560	(4.47) .176	(5.92) .233	(5.11) .201	90°			
	A-4094-NA501	2766-3(501)	(17.45) .687	(9.30) .366	(3.15) .124	(6.30) .248	90°			A-4094-NCN501	2766-53(501)	(20.85) .821	SEE SHT. 7				90°		
	A-4094-NAB102	2766-40(102)	(23.80) .937	(14.99) .590	(3.78) .149	(6.30) .248	90°			A-4094-NCR501	2766-73(501)	(22.71) .894	(13.92) .548	(3.48) .137	(6.60) .260	90°			
	A-4094-NAC102	2766-54(102)	(17.86) .703	(9.68) .381	(4.32) .170	(5.13) .202	90°			A-4094-NCS501	4166-74(501)	(31.24) 1.230	(22.23) .875	(3.71) .146	(6.60) .260	90°			
H	A-4094-NAJ102	2766-8(102)	(21.39) .842	(10.19) .401	(4.09) .161	(8.41) .331	90°			A-4094-NCV501	2766-28(501)	(15.88) .625	(7.65) .301	(3.23) .127	(6.30) .248	90°			
	A-4094-NAL102	2766-8(102)	(21.39) .842	(12.47) .491	(3.91) .154	(6.30) .248	90°			A-4094-NCY508	SEE SHT. 8					90°			
	A-4094-NAM102	2766-3(102)	(17.45) .687	(4.93) .194	(7.29) .287	(6.53) .257	90°			A-4094-NCZ501	2766-3(501)	(17.45) .687	(9.30) .366	(2.31) .091	(7.11) .280	90°			
	A-4094-NAP102	2766-3(102)	(17.45) .687	(8.41) .331	(3.78) .149	(6.55) .258	90°			A-4094-NJ102	2766-28(102)	(15.88) .625	(6.63) .261	(3.02) .119	(9.73) .383	55°			
G	A-4094-NB102	2766-43(102)	(13.46) .530	(4.85) .191	(3.61) .142	(6.30) .248	90°			A-4094-NM102	2766-3(102)	(17.45) .687	(7.44) .293	(2.84) .112	(8.46) .333	90°			
	A-4094-NBE102	2766-37(102)	(20.32) .800	(11.53) .454	(3.56) .140	(6.50) .256	90°			A-4094-NR102	2766-37(102)	(20.32) .800	(12.24) .482	(3.07) .121	(6.30) .248	90°			
	A-4094-NBE501	2766-37(501)	(20.32) .800	(11.53) .454	(3.56) .140	(6.50) .256	90°			A-4094-NRG501	2766-53(501)	(20.85) .821	(12.32) .485	(3.53) .139	(6.30) .248	90°			
	A-4094-NBF102	2766-4(102)	(18.69) .736	(9.30) .366	(2.79) .110	(7.87) .310	90°			A-4094-NW102	2766-37(102)	(20.32) .800	(9.30) .366	(3.61) .142	(8.71) .343	90°			
F	A-4094-NBF501	2766-4(501)	(18.69) .736	(9.30) .366	(2.79) .110	(7.87) .310	90°			A-4094-NZ102	2766-3(102)	(17.45) .687	(5.13) .202	(7.95) .313	(5.66) .223	90°			
	A-4094-NBH102	2766-37(102)	(20.32) .800	(11.71) .461	(2.31) .091	(7.57) .298	90°			A-4094-NH102	2766-1(102)	(14.22) .560	(5.23) .206	(3.96) .156	(6.30) .248	90°			
	A-4094-NBK103	4166-11(103)	(16.51) .650	(5.00) .197	(7.67) .302	(5.13) .202	90°			A-4094-NDA102	4166-38(102)	(27.00) 1.063	(9.30) .366	(3.15) .124	(15.82) .623	90°			
	A-4094-NBJ102	2766-4(102)	(18.69) .736	(9.42) .371	(3.63) .143	(6.93) .273	90°			A-4094-NDB102	4166-30(102)	(30.48) 1.200	(9.30) .366	(3.07) .121	(9.38) .763	90°			
E	A-4094-NBJ501	2766-4(501)	(18.69) .736	(9.42) .371	(3.63) .143	(6.93) .273	90°			A-4094-NDC102	2766-40(102)	(23.80) .937	(12.70) .500	(3.15) .124	(9.22) .363	90°			
	A-4094-NBL102	2766-8(102)	(21.39) .842	(3.81) .150	(3.05) .120	(17.60) .693	25°			A-4094-NA508	2766-3(508)	(17.45) .687	(9.30) .366	(3.15) .124	(6.30) .248	90°			
	A-4094-NBM102	2766-28(102)	(15.88) .625	(5.79) .228	(4.06) .160	(6.30) .248	139°			A-4094-NDD102	2766-60(102)	(23.24) .915	(9.53) .375	(8.64) .340	(6.35) .250	90°			
	A-4094-NBP102	2766-3(102)	(17.45) .687	(9.07) .357	(7.87) .310	(5.82) .229	105°			A-4094-NAR102	2766-26(102)	(14.99) .590	(4.06) .160	(8.03) .316	(4.09) .161	90°			
D	A-4094-NBR501	2766-52(501)	(14.61) .575	(9.30) .366	(1.63) .064	(4.90) .193	90°			A-4094-NAT102	2766-4(102)	(18.69) .736	(8.26) .325	(3.28) .129	(12.75) .502	45°			
	A-4094-NBT102	2766-39(102)	(12.70) .500	(6.38) .251	(2.79) .110	(4.78) .188	90°			A-4094-NAT501	2766-4(501)	(18.69) .736	(8.26) .325	(3.28) .129	(12.75) .502	45°			
	A-4094-NCA102	2766-57(102)	(13.84) .545	(5.23) .206	(3.61) .142	(6.30) .248	90°			A-4094-NDE501	2766-73(501)	(22.71) .894	(9.98) .393	(3.00) .118	(11.00) .433	90°			
	A-4094-NCC102	2766-73(102)	(22.71) .894	(10.74) .423	(3.25) .128	(13.61) .536	60°			A-4094-NDF102	2766-16(102)	(22.23) .875	(6.12) .241	(11.05) .435	(6.35) .250	90°			
C	A-4094-NCE102	2766-54(102)	(17.86) .703	(9.14) .360	(3.91) .154	(6.10) .240	90°			A-4094-NDG102	2766-39(102)	(12.70) .500	(4.60) .181	(3.10) .122	(6.30) .248	90°			
	A-4094-NCM102	2766-1(102)	(14.22) .560	(4.47) .176	(5.92) .233	(5.11) .201	90°			A-4094-NBK102	4166-11(102)	(16.51) .650	(5.00) .197	(7.67) .302	(5.13) .202	90°			
B	UPDATE TITLE BLOCK EC NO: UCP2005-2329 DRAWN:ADRR 2005/07/26 CHKD:LSCHM DT 2005/07/27 APPR:FSM TH 2005/07/27 REV AD1						QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE		SCALE	DESIGN UNITS		THIRD ANGLE PROJECTION		B			
MM/IN									---	INCH									
DRAWN BY KSS									DATE 1984/09/10	TITLE WAFER ASSY FLAT MINI KK (4030 WITH BENT PINS) 4094 SERIES DRAWING									
CHECKED BY NP									DATE 1984/09/10										
A								APPROVED BY KJA		DATE 1984/09/10	MATERIAL NO. SDA-4094		DOCUMENT NO. SDA-4094		SHEET NO. 2 OF 14		A		
								DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE C	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION								

tb_frame_C_P_ME_T
Rev. D 2004/04/02

	13	12	11	10	9	8	7	6	5	4	3	2	1	
	A-4094-NA I02		A-4094-NA50 I		A-4094-NAB I02		A-4094-NAC I02		A-4094-NAJ I02		A-4094-NAL I02			
J	PART NO.	ENG. NO.	PART NO.	ENG. NO.	PART NO.	ENG. NO.	PART NO.	ENG. NO.	PART NO.	ENG. NO.	PART NO.	ENG. NO.	J	
	22-05-202 I	* A-4094-2A I02	22- I2-202 I	* A-4094-2A50 I	22-05-2026	A-4094-2AB I02		A-4094-2AC I02		A-4094-2AJ I02	22-05-2027	A-4094-2AL I02		
	22-05-203 I	* A-4094-3A I02	22- I2-203 I	* A-4094-3A50 I	22-05-2036	A-4094-3AB I02		A-4094-3AC I02		A-4094-3AJ I02	22-05-2037	A-4094-3AL I02		
	22-05-204 I	* A-4094-4A I02	22- I2-204 I	* A-4094-4A50 I	22-05-2046	A-4094-4AB I02		A-4094-4AC I02		A-4094-4AJ I02	22-05-2047	A-4094-4AL I02		
I	22-05-205 I	* A-4094-5A I02	22- I2-205 I	* A-4094-5A50 I	22-05-2056	A-4094-5AB I02		A-4094-5AC I02		A-4094-5AJ I02	22-05-2057	A-4094-5AL I02	I	
	22-05-206 I	* A-4094-6A I02	22- I2-206 I	* A-4094-6A50 I	22-05-2066	A-4094-6AB I02		A-4094-6AC I02		A-4094-6AJ I02	22-05-2067	A-4094-6AL I02		
	22-05-207 I	* A-4094-7A I02	22- I2-207 I	* A-4094-7A50 I	22-05-2076	A-4094-7AB I02		A-4094-7AC I02		A-4094-7AJ I02	22-05-2077	A-4094-7AL I02		
	22-05-208 I	* A-4094-8A I02	22- I2-208 I	* A-4094-8A50 I	22-05-2086	A-4094-8AB I02		A-4094-8AC I02		A-4094-8AJ I02	22-05-2087	A-4094-8AL I02		
	22-05-209 I	* A-4094-9A I02	22- I2-209 I	* A-4094-9A50 I	22-05-2096	A-4094-9AB I02		A-4094-9AC I02		A-4094-9AJ I02	22-05-2097	A-4094-9AL I02		
H	22-05-2 I0 I	* A-4094- I0A I02	22- I2-2 I0 I	* A-4094- I0A50 I	22-05-2 I06	A-4094- I0AB I02		A-4094- I0AC I02		A-4094- I0AJ I02	22-05-2 I07	A-4094- I0AL I02	H	
	22-05-2 I I I	* A-4094- I I A I02	22- I2-2 I I I	* A-4094- I I A50 I	22-05-2 I I6	A-4094- I I AB I02		A-4094- I I AC I02		A-4094- I I AJ I02	22-05-2 I I7	A-4094- I I AL I02		
	22-05-2 I2 I	* A-4094- I2A I02	22- I2-2 I2 I	* A-4094- I2A50 I	22-05-2 I26	A-4094- I2AB I02		A-4094- I2AC I02		A-4094- I2AJ I02	22-05-2 I27	A-4094- I2AL I02		
	22-05-2 I3 I	* A-4094- I3A I02	22- I2-2 I3 I	* A-4094- I3A50 I	22-05-2 I36	A-4094- I3AB I02		A-4094- I3AC I02		A-4094- I3AJ I02	22-05-2 I37	A-4094- I3AL I02		
	22-05-2 I4 I	* A-4094- I4A I02	22- I2-2 I4 I	* A-4094- I4A50 I	22-05-2 I46	A-4094- I4AB I02		A-4094- I4AC I02		A-4094- I4AJ I02	22-05-2 I47	A-4094- I4AL I02		
	22-05-2 I5 I	* A-4094- I5A I02	22- I2-2 I5 I	* A-4094- I5A50 I	22-05-2 I56	A-4094- I5AB I02		A-4094- I5AC I02		A-4094- I5AJ I02	22-05-2 I57	A-4094- I5AL I02		
G	22-05-2 I6 I	* A-4094- I6A I02	22- I2-2 I6 I	* A-4094- I6A50 I	22-05-2 I66	A-4094- I6AB I02		A-4094- I6AC I02		A-4094- I6AJ I02	22-05-2 I67	A-4094- I6AL I02	G	
	22-05-2 I7 I	* A-4094- I7A I02	22- I2-2 I7 I	* A-4094- I7A50 I	22-05-2 I76	A-4094- I7AB I02		A-4094- I7AC I02		A-4094- I7AJ I02	22-05-2 I77	A-4094- I7AL I02		
	22-05-2 I8 I	* A-4094- I8A I02	22- I2-2 I8 I	* A-4094- I8A50 I	22-05-2 I86	A-4094- I8AB I02		A-4094- I8AC I02		A-4094- I8AJ I02	22-05-2 I87	A-4094- I8AL I02		
	22-05-2 I9 I	* A-4094- I9A I02	22- I2-2 I9 I	* A-4094- I9A50 I	22-05-2 I96	A-4094- I9AB I02		A-4094- I9AC I02		A-4094- I9AJ I02	22-05-2 I97	A-4094- I9AL I02		
	22-05-220 I	* A-4094-20A I02	22- I2-220 I	* A-4094-20A50 I	22-05-2206	A-4094-20AB I02		A-4094-20AC I02		A-4094-20AJ I02	22-05-2207	A-4094-20AL I02		
F	22-05-22 I I	* A-4094-2 I A I02	22- I2-22 I I	* A-4094-2 I A50 I	22-05-22 I6	A-4094-2 I AB I02		A-4094-2 I AC I02		A-4094-2 I AJ I02	22-05-22 I7	A-4094-2 I AL I02	F	
	22-05-222 I	* A-4094-22A I02	22- I2-222 I	* A-4094-22A50 I	22-05-2226	A-4094-22AB I02		A-4094-22AC I02		A-4094-22AJ I02	22-05-2227	A-4094-22AL I02		
	22-05-223 I	* A-4094-23A I02	22- I2-223 I	* A-4094-23A50 I	22-05-2236	A-4094-23AB I02		A-4094-23AC I02		A-4094-23AJ I02	22-05-2237	A-4094-23AL I02		
	22-05-224 I	* A-4094-24A I02	22- I2-224 I	* A-4094-24A50 I	22-05-2246	A-4094-24AB I02		A-4094-24AC I02		A-4094-24AJ I02	22-05-2247	A-4094-24AL I02		
	22-05-225 I	* A-4094-25A I02	22- I2-225 I	* A-4094-25A50 I	22-05-2256	A-4094-25AB I02		A-4094-25AC I02		A-4094-25AJ I02	22-05-2257	A-4094-25AL I02		
	22-05-226 I	A-4094-26A I02	22- I2-226 I	A-4094-26A50 I	22-05-2266	A-4094-26AB I02		A-4094-26AC I02		A-4094-26AJ I02	22-05-2267	A-4094-26AL I02		
E	22-05-227 I	A-4094-27A I02	22- I2-227 I	A-4094-27A50 I	22-05-2276	A-4094-27AB I02		A-4094-27AC I02		A-4094-27AJ I02	22-05-2277	A-4094-27AL I02	E	
	22-05-228 I	A-4094-28A I02	22- I2-228 I	A-4094-28A50 I	22-05-2286	A-4094-28AB I02		A-4094-28AC I02		A-4094-28AJ I02	22-05-2287	A-4094-28AL I02		
D													D	
C													C	
B													B	
A													A	
UPDATE TITLE BLOCK EC NO: UCP2005-2329 DRW:ADER CHKD: SCHM DT APPR:FSM TH 2005/07/26 2005/07/27 2005/07/27 DESCRIPTION REV QUALITY SYMBOLS ▽=0 ▽=0 GENERAL TOLERANCES (UNLESS SPECIFIED) 4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± --- 1 PLACE ± --- ± --- ANGULAR ±1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS DIMENSION STYLE MM/IN DRAWN BY KSS CHECKED BY NP APPROVED BY KJA MATERIAL NO. SIZE C DATE 1984/09/10 DATE 1984/09/10 DATE 1984/09/10 DOCUMENT NO. SDA-4094 SHEET NO. 4 OF 14 SCALE --- DESIGN UNITS INCH THIRD ANGLE PROJECTION WAFER ASSY FLAT MINI KK (4030 WITH BENT PINS) 4094 SERIES DRAWING MOLEX MOLEX INCORPORATED THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION														
ib_frame_C_P_ME_T Rev. D 2004/04/02	12	11	10	9	8	7	6	5	4	3	2	1		