




2348/2301/2506



2348-X-00-XX-00-00-07-0
Swage mount in 1,63 hole




2301-X-00-XX-00-00-07-0
Swage mount in 1,70 hole



2506-X-00-XX-00-00-07-0
Swage mount in 1,70 hole

- X -	Board Thickness	Length V
1	0,79	1,35
2	1,57	2,13
3	2,39	2,92
4	3,18	3,73


2310



2310-X-00-XX-00-00-07-0
Swage mount in 1,70 hole

- X -	Board Thickness	Length V
1	0,79	1,35
2	1,57	2,08
3	2,39	2,87
4	3,18	3,68


2505




2505-X-00-XX-00-00-07-0
Swage mount in 1,93 hole

- X -	Board Thickness	Length V
1	0,79	1,57
2	1,57	2,36
3	2,39	3,18
4	3,18	3,96


2325/2355/2365



2325-X-00-XX-00-00-07-0
Swage mount in 1,85 hole



2355-X-00-XX-00-00-07-0
Swage mount in 1,85 hole



2365-X-00-XX-00-00-07-0
Swage mount in 1,93 hole

- X -	Board Thickness	Length V
1	0,79	1,35
2	1,57	2,13
3	2,39	2,92
4	3,18	3,73

SPECIFICATIONS

PIN MATERIAL:
Brass Alloy 360, 1/2 Hard
(Except Swage pins which are annealed)

PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY

TOLERANCES ON:

LENGTHS: $\pm 0,13$
DIAMETERS: $\pm 0,05$
ANGLES: $\pm 2^\circ$

ORDER CODE: 2XXX - X - 00 - XX - 00 - 00 - 07 - 0

BASIC PART #

SPECIFY PIN FINISH:

01 5,08 μm TIN/LEAD OVER NICKEL
80 5,08 μm TIN OVER NICKEL $\diamond$
44 7,62 μm SILVER OVER COPPER $\diamond$
50 7,62 μm ELECTRO-SOLDER (60/40 SnPb)

