


2315




2315-X-01-XX-00-00-07-0

Swage mount in 1,70 hole

- X -	Board Thickness	Length V	Depth D
1	0,79	1,14	1,02
2	1,57	2,39	
3	2,39	3,18	1,57
4	3,18	3,96	

2302




2302-X-01-XX-00-00-07-0

Swage mount in 1,70 hole.

- X -	Board Thickness	Length V
1	0,79	1,35
2	1,57	2,13
3	2,39	2,92
4	3,18	3,73

2352




2352-X-01-XX-00-00-07-0

Swage mount in 1,70 hole

- X -	Board Thickness	Length V
1	0,79	1,14
2	1,57	2,39
3	2,39	3,18
4	3,18	3,96

2362




2362-X-01-XX-00-00-07-0

Swage mount in 1,70 hole


- X -	Board Thickness	Length V
5	0,41	0,94
1	0,79	1,35
2	1,57	2,13
3	2,39	2,92
4	3,18	3,73

2507/2526



2507-X-01-XX-00-00-07-0

Swage mount in 1,70 hole



2526-X-01-XX-00-00-07-0

Swage mount in 1,63 hole

- X -	Board Thickness	Length V
1	0,79	1,35
2	1,57	2,13
3	2,39	2,92
4	3,18	3,73

SPECIFICATIONS

PIN MATERIAL:
Brass Alloy 360, 1/2 Hard
(Except Swage pins which are annealed)

PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY

TOLERANCES ON:
LENGTHS: $\pm 0,13$
DIAMETERS: $\pm 0,05$
ANGLES: $\pm 2^\circ$

ORDER CODE: 2XXX - X - 01 - XX - 00 - 00 - 07 - 0

BASIC PART #

SPECIFY PIN FINISH:

- 01** 5,08 μm TIN/LEAD OVER NICKEL
- 80** 5,08 μm TIN OVER NICKEL $\diamond$
- 44** 7,62 μm SILVER OVER COPPER $\diamond$
- 50** 7,62 μm ELECTRO-SOLDER (60/40 SnPb)

