



2319



- X -	Board Thickness	Length V
1	0,79	1,30
2	1,57	2,08
3	2,39	2,87

2319-X-00-XX-00-00-07-0
Swage mount in 1,93 hole


2313



- X -	Board Thickness	Length V
1	0,79	1,30
2	1,57	2,13
3	2,39	2,87
4	3,18	3,68

2313-X-00-XX-00-00-07-0
Swage mount in 1,93 hole


2321



- X -	Board Thickness	Length V
1	0,79	1,30
2	1,57	2,08
3	2,39	2,87
4	3,18	3,68

2321-X-00-XX-00-00-07-0
Swage mount in 1,93 hole


2706



- X -	Board Thickness	Length V
1	0,79	1,60
2	1,57	2,36
3	2,39	3,18
4	3,18	3,96

2706-X-00-XX-00-00-07-0
Swage mount in 3,05 hole


2530



- X -	Board Thickness	Length V
2	1,57	2,39
3	2,39	3,18
4	3,18	3,96

2530-X-00-XX-00-00-07-0
Swage mount in 2,39 hole

3156



Basic Part Number	Board Thickness	Length V
3156-1	0,79	1,30
3156-2	1,57	2,08
3156-3	2,39	2,87
3156-4	3,18	3,68

3156-X-00-XX-00-00-08-0
Swage mount in 1,93 hole

SPECIFICATIONS

PIN MATERIAL:
Brass Alloy 360, 1/2 Hard
(Except Swage pins which are annealed)

PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY

TOLERANCES ON:
LENGTHS: $\pm 0,13$
DIAMETERS: $\pm 0,05$
ANGLES: $\pm 2^\circ$

ORDER CODE: 2XXX - X - 00 - XX - 00 - 00 - 07 - 0

BASIC PART #

SPECIFY PIN FINISH:

01	5,08 μ m	TIN/LEAD OVER NICKEL
80	5,08 μ m	TIN OVER NICKEL $\diamond$
44	7,62 μ m	SILVER OVER COPPER $\diamond$
50	7,62 μ m	ELECTRO-SOLDER (60/40 SnPb)

