



## 2802/2804




**2802-X-00-XX-00-00-07-0**  
Swage mount in 3,0 hole



**2804-X-00-XX-00-00-07-0**  
Swage mount in 3,0 hole

| - X - | Board Thick-ness | Length V |
|-------|------------------|----------|
| 1     | 0,79             | 1,98     |
| 2     | 1,57             | 2,77     |
| 3     | 2,39             | 3,56     |
| 4     | 3,18             | 4,34     |


## 2805



**2805-X-00-XX-00-00-07-0**  
Swage mount in 2,95 hole

| - X - | Board Thick-ness | Length V | Depth D |
|-------|------------------|----------|---------|
| 1     | 0,79             | 1,88     | 1,73    |
| 2     | 1,57             | 2,67     |         |
| 3     | 2,39             | 3,43     | 2,49    |
| 4     | 3,18             | 4,19     |         |


## 2801



**2801-X-00-XX-00-00-07-0**  
Swage mount in 2,95 hole

| - X - | Board Thick-ness | Length V |
|-------|------------------|----------|
| 1     | 0,79             | 1,98     |
| 2     | 1,57             | 2,77     |
| 3     | 2,39             | 3,58     |
| 4     | 3,18             | 4,37     |
| 5     | 4,78             | 5,94     |


## 2806



**2806-X-00-XX-00-00-07-0**  
Swage mount in 2,95 hole

| - X - | Board Thick-ness | Length V |
|-------|------------------|----------|
| 1     | 0,79             | 1,98     |
| 2     | 1,57             | 2,77     |
| 3     | 2,39             | 3,58     |
| 4     | 3,18             | 4,37     |

## 2811



**2811-X-00-XX-00-00-07-0**  
Swage mount in 2,95 hole

| - X - | Board Thick-ness | Length V |
|-------|------------------|----------|
| 1     | 0,79             | 1,91     |
| 2     | 1,57             | 2,67     |
| 3     | 2,39             | 3,43     |
| 4     | 3,18             | 4,19     |

### SPECIFICATIONS

**PIN MATERIAL:**  
Brass Alloy 360, 1/2 Hard  
( Except Swage pins which  
are annealed )

**PART MANUFACTURED IN  
INCHES, METRIC FOR REF ONLY**

**TOLERANCES ON:**

LENGTHS: ± 0,13

DIAMETERS: ± 0,05

ANGLES: ± 2°

**ORDER CODE: 28XX - X - 00 - XX - 00 - 00 - 07 - 0**

**BASIC PART #**

**SPECIFY PIN FINISH:**

- 01** 5,08µm TIN/LEAD OVER NICKEL
- 80** 5,08µm TIN OVER NICKEL ◇
- 44** 7,62µm SILVER OVER COPPER ◇
- 50** 7,62µm ELECTRO-SOLDER (60/40 SnPb)

