



NOTES:

1. METAL SHELLS: STEEL; min. 320μ" TIN
2. INSULATORS: PBT GF UL 94 V-0, GREEN
3. SIGNAL CONTACTS: COPPER ALLOY
SOLDER CUP ACCEPTS CABLE AWG 20
4. PLATING: min. 30μ" HARD GOLD OVER min. 50μ" NICKEL
5. CONNECTOR IS PART MARKED: 3007W2SCM99A10X CONEC Y/WW
6. = CRITICAL DIMENSION

Directive 2002/95/EC
"RoHS"
Compliant

THIS DRAWING MAY NOT BE COPIED OR
REPRODUCED IN ANY WAY, AND MAY NOT
BE PASSED ON TO A THIRD PARTY WITHOUT
WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH
NOT ALTER CAD DRAWING BY HAND

				tolerance				scale: 2:1				
								material: SEE NOTES				
				2002	date	name		title: D-SUB COMBINATION FEMALE 7W2S SOLDER CUP				
				drawn	07.05.	Parei						
				appd.	07.05.	E. Mickenbecker						
				norm								
				d-old					dwg no:		AutoCAD 2000	DIN-A
								13K1A563		3		
								sh: 1/1				
rev.	description	date	name					part no: 3007W2SCM99A10X				