





used for: D-SUB COMBINATION



NOTES:

1. METAL SHELLS: STEEL; min. 320μ " TIN
2. INSULATORS: PBT GF UL 94 V-0, GREEN
3. SIGNAL CONTACTS: COPPER ALLOY
PLATING: 30μ " HARD GOLD OVER min. 50μ " NICKEL
SOLDER CUP ACCEPTS CABLE AWG 20
4. NO CONTACTS ON POS. A1-A5
5. THREADED INSERT: COPPER ALLOY; min. 200μ " TIN over 80μ " NICKEL
6. COLLAR: COPPER ALLOY; min. 200μ " TIN over 80μ " NICKEL
7. MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
8. CONNECTOR IS PART MARKED: 3017W5SCM99A30X CONEC ABC
9. = CHECK DIMENSION

Directive 2002/95/EC
RoHS
Compliant

APPROVAL * FREIGABE * DEBLOCAGE * AUTORIZACION * APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL * FREIGABE * DEBLOCAGE * AUTORIZACION * APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR
REPRODUCED IN ANY WAY, AND MAY NOT
BE PASSED ON TO A THIRD PARTY WITHOUT
WRITTEN PERMISSION.
OWNERSHIP AND COPYRIGHT OF CONEC GmbH
DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name
a	Origin		

tolerance	dim. in mm
2006	date
drawn	08.02.
appd.	09.02.
norm	
d-old	

scale:	2:1 (5:1)
material:	SEE NOTES
title: D-SUB COMBINATION FEMALE 17W5S SOLDER CUP with threaded insert	
dwg no:	AutoCAD 2004 DIN-A
13K1A1712	
part no: 3017W5SCM99A30X	