



Wiha ComfortGrip Pliers & Cutters

ComfortGrip Standard Adjustable Pliers



With box joint



329 62 Adjustable Pliers DIN ISO 8976

10 opening settings provides optimal adjustment to objects being gripped. Long life achieved through additional induction hardening of jaws to approx. 58-60 HRC. Chrome-vanadium tool steel forgings, hardened and tempered. Two component ComfortGrip ergonomic handle. Chrome finish.

| Item | ↔ | ↔ | Capacities | | 🔧 | 🔧 |
|------------------|-----|------|------------|-----|------|-----|
| No. | mm | Inch | Round | Hex | Pkg. | wt. |
| 329 62 Z21025005 | 250 | 10.0 | 1 3/4 | 2" | 1 | .76 |

ComfortGrip Slide Lock Adjustable Pliers



With box joint



- Open and slide to adjust opening size
- Close to lock
- Audible click at each locking position

329 69 Slide Lock Adjustable Pliers - Wiha QuickFix - Box Joint

DIN ISO 8976 Super fast and easily adjusted pliers. Long durability achieved through additional induction hardening of jaws to approx. 56 HRC. Finger jam protection for safe operation at all settings. Chrome-vanadium tool steel forgings, hardened and tempered. Chrome finish with ergonomic ComfortGrip handles.

| Item | ↔ | ↔ | Capacities | | 🔧 | 🔧 |
|------------------|-----|------|------------|-------|------|-----|
| No. | mm | Inch | Round | Hex | Pkg. | wt. |
| 329 69 Z23025005 | 250 | 10.0 | 1 1/4 | 1 1/2 | 1 | .80 |

ComfortGrip Push Button Adjustable Pliers



With box joint



329 67 Slide Lock Adjustable Pliers - Box Joint - With Push

Button Setting. DIN ISO 8976 Extra narrow head for working small spaces. Rapid and simple push button setting and locking. Long life achieved through additional induction hardening of jaws to approx. 58-60 HRC. Finger jam protection for safe operation at all settings. CVM tool steel forgings, hardened and tempered. ComfortGrip handles.

| Item | ↔ | ↔ | Capacities | | 🔧 | 🔧 |
|------------------|-----|------|------------|-----|------|-----|
| No. | mm | Inch | Round | Hex | Pkg. | wt. |
| 329 67 Z22025005 | 250 | 10.0 | 1 3/4 | 2" | 1 | .79 |

