



3116



Basic Part Number	Board Thickness	Length V	Length D
3116-1	0,79	1,30	0,89
3116-2	1,57	2,08	1,57
3116-3	2,39	2,87	1,57
3116-4	3,18	3,68	1,57

3116-X-00-XX-00-00-08-0
Swage mount in 1,32 hole


5435



Basic Part Number	Length L
5435-0	7,70
5435-1	5,08
5435-2	10,49


5435-X-05-XX-00-00-03-0
Square press-fit in 0,56 plated thru hole

3135




3135-1-00-XX-00-00-08-0
Swage mount in 1,02 hole.
For 0,79 thick board.

3210




3210-2-00-XX-00-00-08-0
Swage mount in 0,79 hole.
For 1,57 thick board.

3129




3129-1-00-XX-00-00-08-0
Swage mount in 0,89 hole.
For 0,79 thick board.

3147




3147-3-00-XX-00-00-08-0
Swage mount in 1,09 hole.
For 2,39 thick board.

4366




4366-0-00-XX-00-00-03-0
Hex press-fit in 0,86 plated thru hole

1267




1267-0-00-XX-00-00-03-0
Press-fit in 0,89 mounting hole

7827



7827-0-00-XX-00-00-03-0
Press-fit in 0,89 mounting hole

1130



1130-0-00-XX-00-00-03-0
Press-fit in 1,45 mounting hole
Pin material is Ph Br. 544 (B2)

SPECIFICATIONS

PIN MATERIAL:
Brass Alloy 360, 1/2 Hard
(Except Swage pins which are annealed)

PART MANUFACTURED IN
INCHES, METRIC FOR REF ONLY

TOLERANCES ON:
LENGTHS: $\pm 0,13$
DIAMETERS: $\pm 0,05$
ANGLES: $\pm 2^\circ$

ORDER CODE: XXXX - X - 0X - XX - 00 - 00 - 0X - 0

BASIC PART #

SPECIFY PIN FINISH:

- 01 5,08 μm TIN/LEAD OVER NICKEL
- 80 5,08 μm TIN OVER NICKEL $\diamond$
- 15 0,25 μm GOLD OVER NICKEL $\diamond$
- 21 0,51 μm GOLD OVER NICKEL $\diamond$
- 34 1,27 μm GOLD OVER NICKEL $\diamond$

