



## 3231



| Basic Part Number | Board Thickness | Length V |
|-------------------|-----------------|----------|
| 3231-2            | 1,57            | 2,39     |
| 3231-3            | 2,39            | 3,18     |
| 3231-4            | 3,18            | 3,96     |

**3231-X-00-XX-00-00-08-0**  
Swage mount in 2,39 hole.


## 3609



| Basic Part Number | Pin Length A |
|-------------------|--------------|
| 3609-1            | 5,08         |
| 3609-2            | 9,53         |
| 3609-3            | 12,7         |

**3609-X-07-XX-00-00-08-0**  
#16A Crimp barrel


## 3601



| Basic Part Number | Pin Length A |
|-------------------|--------------|
| 3601-1            | 5,08         |
| 3601-2            | 9,53         |
| 3601-3            | 12,7         |

**3601-X-07-XX-00-00-08-0**  
#20A Crimp barrel

## 3133/3138/3152




| Basic Part Number | Pin Length A |
|-------------------|--------------|
| 3152-X            | 2,39         |
| 3133-X            | 5,56         |
| 3138-X            | 7,16         |

| - X - | Board Thickness | Length V |
|-------|-----------------|----------|
| 1     | 0,79            | 1,60     |
| 2     | 1,57            | 2,39     |
| 3     | 2,39            | 3,18     |
| 4     | 3,18            | 3,96     |

**31XX-X-00-XX-00-00-08-0**  
Specify board thickness  
Swage mount in 1,63 hole


## 3144



| Basic Part Number | Board Thickness | Length V |
|-------------------|-----------------|----------|
| 3144-1            | 0,79            | 1,35     |
| 3144-2            | 1,57            | 2,13     |
| 3144-3            | 2,39            | 2,92     |


**3144-X-00-XX-00-00-08-0**  
Swage mount in 1,70 hole.

## 3233



**3233-2-00-XX-00-00-08-0**  
Swage mount in 2,39 hole.  
For 1,57 thick board.

## 0520



**0520-0-00-XX-00-00-03-0**  
Annealed  
#18 Gage crimp barrel

### SPECIFICATIONS

**PIN MATERIAL:**  
Brass Alloy 360, 1/2 Hard  
(Except Swage pins which are annealed)

**PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY**

**TOLERANCES ON:**  
LENGTHS:  $\pm 0,13$   
DIAMETERS:  $\pm 0,05$   
ANGLES:  $\pm 2^\circ$

**ORDER CODE: XXXX - X - 0X - XX - 00 - 00 - 0X - 0**

**BASIC PART #**

**SPECIFY PIN FINISH:**

- 01 5,08µm TIN/LEAD OVER NICKEL
- 80 5,08µm TIN OVER NICKEL
- 15 0,25µm GOLD OVER NICKEL
- 21 0,51µm GOLD OVER NICKEL
- 34 1,27µm GOLD OVER NICKEL

