


8685/9036




Basic Part Number	Length A
8685-0	3,18
9036-0	4,45

XXXX-0-00-XX-00-00-03-0

Press-fit in 0,84 mounting hole.
Pin material is Ph. Br. 544 (B2)


9051



9051-0-00-XX-00-00-03-0

Press-fit in 1,45 mounting hole


8969



8969-0-05-XX-00-00-03-0

Square press-fit in 0,58 plated thru hole (use .7 mm drill prior to plating)


8979



8979-0-00-XX-00-00-03-0

Hex press-fit in 1,88 plated thru hole


9159



9159-0-00-XX-00-00-03-0

Press-fit in 0,66 mounting hole

3155/5155




X155-0-00-XX-00-00-03-0

Press-fit in 0,66 mounting hole
Pin material is Ph. Br. 544 (B2)

Basic Part Number	Length A
3155-0	4,57
5155-0	3,30


4194



4194-0-00-XX-00-00-08-0

Wire termination and
Press-fit in 0,91 hole


5556



5556-0-00-XX-00-00-08-0

Wire termination


3790



3790-0-00-XX-00-00-03-0

Press-fit in 1,45 mounting hole

3796



3796-0-00-XX-00-00-03-0

Press-fit in 1,45 mounting hole

SPECIFICATIONS

PIN MATERIAL:
Brass Alloy 360, 1/2 Hard
(Except where noted)

**PART MANUFACTURED IN
INCHES, METRIC FOR REF ONLY**

TOLERANCES ON:
LENGTHS: $\pm 0,13$
DIAMETERS: $\pm 0,05$
ANGLES: $\pm 2^\circ$

ORDER CODE: XXXX - X - 0X - XX - 00 - 00 - 0X - 0

BASIC PART #

SPECIFY PIN FINISH:

- 01 5,08 μm TIN/LEAD OVER NICKEL
- 80 5,08 μm TIN OVER NICKEL $\diamond$
- 15 0,25 μm GOLD OVER NICKEL $\diamond$
- 21 0,51 μm GOLD OVER NICKEL $\diamond$
- 34 1,27 μm GOLD OVER NICKEL $\diamond$

