






SPECIALTY PRODUCTS Shrink DIP Sockets and Strips Solder Tail and Wrapost

Series 117, 127, 217,
227, 317, 327

- High density DIP sockets and strips for devices featuring .070" lead spacing.
- Hi-Rel, 4-finger #30 clip is rated at 3 amps. See page 208 for details.
- Solder tail is MM# 1802 receptacle (see page 138 for details). Wraposts are MM# 1702-2 or 1703-3 pins. See page 162 for details.

Total number of pins				Quantity per tube	Ordering Information				
	A	B	C		Solder Tail	2 Level Wrapost L = .370	3 Level Wrapost L = .510		
					OPEN FRAME DIP SOCKET				
16	0.572	0.3	0.39	35	117-93-316-41-005	127-93-316-41-002	127-93-316-41-003		
28	0.992	0.4	0.49	20	117-93-428-41-005	127-93-428-41-002	127-93-428-41-003		
30	1.062	0.4	0.49	18	117-93-430-41-005	127-93-430-41-002	127-93-430-41-003		
48	1.692	0.4	0.49	12	117-93-448-41-005	127-93-448-41-002	127-93-448-41-003		
20	0.712	0.6	0.69	28	117-93-620-41-005	127-93-620-41-002	127-93-620-41-003		
28	0.992	0.6	0.69	20	117-93-628-41-005	127-93-628-41-002	127-93-628-41-003		
40	1.412	0.6	0.69	14	117-93-640-41-005	127-93-640-41-002	127-93-640-41-003		
42	1.482	0.6	0.69	13	117-93-642-41-005	127-93-642-41-002	127-93-642-41-003		
48	1.692	0.6	0.69	12	117-93-648-41-005	127-93-648-41-002	127-93-648-41-003		
52	1.832	0.6	0.69	11	117-93-652-41-005	127-93-652-41-002	127-93-652-41-003		
56	1.972	0.6	0.69	10	117-93-656-41-005	127-93-656-41-002	127-93-656-41-003		
64	2.252	0.6	0.69	9	117-93-664-41-005	127-93-664-41-002	127-93-664-41-003		
68	2.392	0.6	0.69	8	117-93-668-41-005	127-93-668-41-002	127-93-668-41-003		
64	2.252	0.75	0.84	9	117-93-764-41-005	127-93-764-41-002	127-93-764-41-003		
					CLOSED FRAME DIP SOCKET				
64	2.252	0.75	0.84	9	217-93-764-41-005	227-93-764-41-002	227-93-764-41-003		
					SINGLE ROW STRIP SOCKET If desired, we will supply any length up to 21 pins.				
21	1.482				317-93-121-41-005	327-93-121-41-002	327-93-121-41-003		
					SPECIFY PLATING CODE XX=			93	
					Sleeve (Pin) 			200μ" Sn/Pb	
					Contact (Clip) 			30μ" Au	