



## 3130/3134/3151



**31XX-X-00-XX-00-00-08-0**  
Swage mount in 1,32 hole

| Basic Part Number | Board Thickness | Length A | Length V |
|-------------------|-----------------|----------|----------|
| 3134-1            | 0,79            | 2,01     | 1,30     |
| 3134-2            | 1,57            | 2,01     | 2,08     |
| 3134-3            | 2,39            | 2,01     | 2,87     |
| 3134-4            | 3,18            | 2,01     | 3,68     |
| 3130-1            | 0,79            | 4,55     | 1,30     |
| 3130-2            | 1,57            | 4,55     | 2,08     |
| 3130-3            | 2,39            | 4,55     | 2,87     |
| 3130-4            | 3,18            | 4,55     | 3,68     |
| 3151-1            | 0,79            | 12,17    | 1,30     |
| 3151-2            | 1,57            | 12,17    | 2,08     |
| 3151-3            | 2,39            | 12,17    | 2,87     |
| 3151-4            | 3,18            | 12,17    | 3,68     |


## 3113



**3113-X-00-XX-00-00-08-0**  
Swage mount in 1,57 hole

| Basic Part Number | Board Thickness | Length V | Depth D |
|-------------------|-----------------|----------|---------|
| 3113-1            | 0,79            | 1,57     | 1,02    |
| 3113-2            | 1,57            | 2,39     | 1,57    |
| 3113-3            | 2,39            | 3,18     | 1,57    |
| 3113-4            | 3,18            | 3,96     | 1,57    |


## 3360



**3360-X-14-XX-00-00-08-0**  
Shorting Jumper

| Basic Part Number | Pin Centers A |
|-------------------|---------------|
| 3360-1            | 5,08          |
| 3360-2            | 6,35          |
| 3360-3            | 7,62          |
| 3360-4            | 10,16         |
| 3360-5            | 12,7          |

## 3301⇒3304




**330X-X-14-XX-00-00-08-0**  
Specify board thickness  
Swage mount in 1,09 hole

| Basic Part Number | Pin Centers A |
|-------------------|---------------|
| 3301-X            | 6,53          |
| 3302-X            | 9,07          |
| 3303-X            | 9,53          |
| 3304-X            | 14,27         |

| - X - | Board Thickness | Length V |
|-------|-----------------|----------|
| 1     | 0,79            | 1,30     |
| 2     | 1,57            | 2,08     |
| 3     | 2,39            | 2,87     |


## 3620



**3620-X-32-XX-00-00-08-0**  
Board edge rivet mount


| Basic Part Number | Board Thickness | Slot S |
|-------------------|-----------------|--------|
| 3620-1            | 0,79            | 1,19   |
| 3620-2            | 1,57            | 1,91   |

## 0940



**0940-0-00-XX-00-00-03-0**  
Press-fit in 1,45 mounting hole

## 3621



**3621-0-32-XX-00-00-08-0**  
Board edge rivet mount

### SPECIFICATIONS

**PIN MATERIAL:**  
Brass Alloy 360, 1/2 Hard  
(Except Swage pins which are annealed)

**PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY**

**TOLERANCES ON:**  
LENGTHS: ± 0,13  
DIAMETERS: ± 0,05  
ANGLES: ± 2°

**ORDER CODE: XXXX - X - XX - XX - 00 - 00 - 0X - 0**

**BASIC PART #**

**SPECIFY PIN FINISH:**

- 01 5,08µm TIN/LEAD OVER NICKEL
- 80 5,08µm TIN OVER NICKEL
- 15 0,25µm GOLD OVER NICKEL
- 21 0,51µm GOLD OVER NICKEL
- 34 1,27µm GOLD OVER NICKEL

